

**REPORT NUMBER: 208-MGA-2005-003**

**VEHICLE SAFETY COMPLIANCE TESTING  
FOR  
FMVSS 208, OCCUPANT CRASH PROTECTION  
FMVSS 212, WINDSHIELD MOUNTING  
FMVSS 219, WINDSHIELD INTRUSION (PARTIAL)  
FMVSS 301, FUEL SYSTEM INTEGRITY**

**Toyota Motor Corporation  
2005 Toyota Corolla Passenger Car  
NHTSA No.: C55101**

**PREPARED BY:  
MGA RESEARCH CORPORATION  
5000 WARREN ROAD  
BURLINGTON, WI 53105**



**Test Dates: September 30, 2004 - March 23, 2005**

**Final Report Date: May 27, 2005**

**FINAL REPORT**

**PREPARED FOR:  
U.S. DEPARTMENT OF TRANSPORTATION  
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION  
OFFICE OF ENFORCEMENT  
OFFICE OF VEHICLE SAFETY COMPLIANCE  
MAIL CODE: NVS-220  
400 SEVENTH STREET, SW, ROOM 6115  
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-03-D-11002.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: Jeff Lewandowski Date: May 27, 2005  
Jeff Lewandowski, Project Engineer

Reviewed by: David Winkelbauer Date: May 27, 2005  
David Winkelbauer, Facility Director

FINAL REPORT ACCEPTED BY OVSC:

Accepted By: \_\_\_\_\_

Acceptance Date: \_\_\_\_\_

### Technical Report Documentation Page

<b>1. Report No.</b> 208-MGA-2005-003	<b>2. Government Accession No.</b>	<b>3. Recipient's Catalog No.</b>	
<b>4. Title and Subtitle</b> Final Report of FMVSS 208 Compliance Testing of a 2005 Toyota Corolla NHTSA No.: C55101		<b>5. Report Date</b> May 27, 2005	
		<b>6. Performing Organization Code</b> MGA	
<b>7. Author(s)</b> Jeff Lewandowski, Project Engineer		<b>8. Performing Organization Report No.</b> 208-MGA-2005-003	
<b>9. Performing Organization Name and Address</b> MGA Research Corporation 5000 Warren Road Burlington, WI 53105		<b>10. Work Unit No.</b>	
		<b>11. Contract or Grant No.</b> DTNH22-03-D-11002	
<b>12. Sponsoring Agency Name and Address</b> U.S. Department of Transportation National Highway Traffic Safety Administration Office of Enforcement Office of Vehicle Safety Compliance 400 Seventh St., S.W., Room 6115 NVS-220 Washington, D.C. 20590		<b>13. Type of Report and Period Covered</b> 09/30/04 to 05/27/05	
		<b>14. Sponsoring Agency Code</b> NVS-220	
<b>15. Supplementary Notes</b>			
<b>16. Abstract</b> Compliance tests were conducted on the subject 2005 Toyota Corolla in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP208-12 for the determination of FMVSS 208 compliance. Test failures identified were as follows:  <b>TEST FAILURES:</b> FMVSS 208 S4.5.1 (b)(3) Data Sheet 5 3.3.1 The driver and passenger sun visor air bag warning labels are not permanently affixed to the sun visor. The labels are easily peeled off of the visor. FMVSS 208 S.5.1.2 / S6.6 The 50 <sup>th</sup> % Passenger Dummy SN403 had a Compression Flexion Neck Injury of 1.3 at a 96.9 ms time and a Neck Compression of 5367N during the 25mph unbelted frontal impact test.			
<b>17. Key Words</b>  Frontal Impact 40 kmph Vehicle Safety Compliance Testing FMVSS 208, "Occupant Crash Protection" FMVSS 212, "Windshield Mounting" FMVSS 219, (partial), "Windshield Zone Intrusion" FMVSS 301, "Fuel System Integrity"		<b>18. Distribution Statement</b> Copies of this report are available from the following: NHTSA Technical Information Services (TIS), Mail Code: NPO-230 400 Seventh Street, S.W., Room 5108 Washington, D.C. 20590 Tel. No.: (202) 366-4946	
<b>19. Security Classif. (of this report)</b> Unclassified	<b>20. Security Classif. (of this page)</b> Unclassified	<b>21. No. of Pages</b> 352	<b>22. Price</b>

Form DOT F1700.7 (8-72)

## TABLE OF CONTENTS

<u>Section</u>	<u>Page No</u>
1 Purpose of Compliance Test	1
2 Tests Performed	2
3 Injury Result Summary	4
4 Discussion of Test (if applicable)	6
5 Test Data Sheets	7
 <u>Data Sheet</u>	
1 COTR Vehicle Work Order	8
2 Report of Vehicle Condition	12
3 Certification Label and Tire Placard Information	14
4 Rear Outboard Seating Position Seat Belts	15
5 Air Bag Labels	16
6 Readiness Indicator	29
7 Passenger Air Bag Manual Cut-Off Device	30
8 Lap Belt Lockability	34
9 Seat Belt Warning System	42
10 Belt Contact Force	44
11 Latch Plate Access	50
12 Seat Belt Retraction	54
13 Seat Belt Guides and Hardware	58
14 Marking of Reference Points for Various Test Positions & Points	64
15 Summary of Suppression Test Using 12-Month CRABI Dummy	70
16 Summary of Suppression Test Using Newborn Infant Dummy	77
17 Summary of Suppression Test Using 3-YO Dummy and Booster Seats	78
18 Summary of Suppression Test Using 3-YO Dummy and Fwd Facing Restraints	80
19 Summary of Suppression Test Using an Unbelted 3-YO Dummy	83
20 Summary of Suppression Test Using 6-YO Dummy and Booster Seats	84
21 Summary of Suppression Test Using an Unbelted 6-YO Dummy	87
27 Summary of Low Risk Deployment Using an Unbelted 5 <sup>th</sup> % Dummy Position 1	88
28 Summary of Low Risk Deployment Using an Unbelted 5 <sup>th</sup> % Dummy Position 2	89
30 Vehicle Weight, Fuel Tank, and Attitude Data	90



<u>Data Sheet</u>		<u>Page No</u>
31	Vehicle Accelerometer Locations and Measurements	94
32	Photographic Targets	97
33	Camera Locations	103
34	Dummy Positioning	105
35	Dummy Measurements	114
36	Crash Test	117
38	Accident Investigation Measurements	119
39	Windshield Mounting (FMVSS 212)	121
40	Windshield Zone Intrusion (FMVSS 219)	123
41	Fuel System Integrity (FMVSS 301)	126
 <u>Appendix</u>		
A	Crash Test Data	A-1
B	Low Risk Test Data	B-1
C	Crash Test Photographs	C-1
D	Low Risk Photographs	D-1
E	Suppression Photographs	E-1
F	Instrumentation Calibration	F-1
G	Notice of Test Failure (If Applicable)	G-1

**SECTION 1**  
**PURPOSE OF COMPLIANCE TEST**

The tests performed are part of a program conducted for the National Highway Traffic Safety Administration (NHTSA) by MGA Research Corporation (MGA) under Contract No. DTNH22-03-D-11002. The purpose of this test was to determine whether the subject vehicle, a 2005 Toyota Corolla, NHTSA No. C55101, meets certain performance requirements of FMVSS 208, "Occupant Crash Protection"; FMVSS 212, "Windshield Mounting"; FMVSS 219, "Windshield Zone Intrusion"; and FMVSS 301, "Fuel System Integrity". The compliance test was conducted in accordance with OVSC Laboratory Test Procedure No. TP208-12 dated January 14, 2003.

## SECTION 2 TESTS PERFORMED

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
Test Dates: 9/30/04-3/23/05

The following checked items indicate the tests that were performed:

- |                                     |     |   |
|-------------------------------------|-----|---|
| <input checked="" type="checkbox"/> | 1.  | Rear outboard seating position seat belts (S4.1.1.2(b) & (S4.2.4))  |
| <input checked="" type="checkbox"/> | 2.  | Air bag labels (S4.5.1)   |
| <input checked="" type="checkbox"/> | 3.  | Readiness indicator (S4.5.2)  |
| <input checked="" type="checkbox"/> | 4.  | Passenger air bag manual cut-off device (S4.5.4)  |
| <input checked="" type="checkbox"/> | 5.  | Lap belt lockability (S7.1.1.5)   |
| <input checked="" type="checkbox"/> | 6.  | Seat belt warning system (S7.3)   |
| <input checked="" type="checkbox"/> | 7.  | Seat belt contact force (S7.4.4)  |
| <input checked="" type="checkbox"/> | 8.  | Seat belt latch plate access (S7.4.4)   |
| <input checked="" type="checkbox"/> | 9.  | Seat belt retraction (S7.4.5)   |
| <input checked="" type="checkbox"/> | 10. | Seat belt guides and hardware (S7.4.6)  |
| <input checked="" type="checkbox"/> | 11. | Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R)   |
| <input checked="" type="checkbox"/> | 12. | Suppression tests with newborn infant (Part 572, Subpart K)   |
| <input checked="" type="checkbox"/> | 13. | Suppression tests with 3-year-old dummy (Part 572, Subpart P)   |
| <input checked="" type="checkbox"/> | 14. | Suppression tests with 6-year-old dummy (Part 572, Subpart N)   |
| <input checked="" type="checkbox"/> | 15. | Test of reactivation of the passenger air bag system with an unbelted 5 <sup>th</sup> percentile female dummy |
| <input type="checkbox"/>            | 16. | Low risk deployment test with 12-month-old dummy (Part 572, Subpart R)  |
| <input type="checkbox"/>            | 17. | Low risk deployment test with 3-year-old dummy (Part 572, Subpart P)  |
| <input type="checkbox"/>            | 18. | Low risk deployment test with 6-year-old dummy (Part 572, Subpart N)  |
| <input checked="" type="checkbox"/> | 19. | Low risk deployment test with 5 <sup>th</sup> female dummy (Part 572, Subpart O)                              |
| <input checked="" type="checkbox"/> | 20. | Impact Tests  |
| <input type="checkbox"/>            |     | Frontal Oblique   |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))                            |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))                       |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a) (1) or S5.1.2(b))        |
| <input checked="" type="checkbox"/> |     | Frontal 0°  |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))                         |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))                      |
| <input type="checkbox"/>            |     | Belted 5 <sup>th</sup> female dummy driver (0 to 48 kmph) (S16.1(a))  |
| <input type="checkbox"/>            |     | Belted 5 <sup>th</sup> female dummy passenger (0 to 48 kmph) (S16.1(a))                                       |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2))                        |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1))                      |
| <input checked="" type="checkbox"/> |     | Unbelted 50 <sup>th</sup> male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))                      |
| <input checked="" type="checkbox"/> |     | Unbelted 50 <sup>th</sup> male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))                   |

		Unbelted 5 <sup>th</sup> female dummy driver (32 to 40 kmph) (S16.1(b))
		Unbelted 5 <sup>th</sup> female dummy passenger (32 to 40 kmph) (S16.1(b))
		40% Offset 0° Belted 5 <sup>th</sup> male dummy driver and passenger (0 to 40 kmph) (S18.1)
	21.	Sled Test: unbelted 50 <sup>th</sup> male dummy driver and passenger (S13)
	22.	FMVSS 204 Indicant Test
X	23.	FMVSS 212 Indicant Test
X	24.	FMVSS 219 Indicant Test
X	25.	FMVSS 301 Frontal Indicant Test

For the crash tests, the vehicle was instrumented with 8 accelerometers. The accelerometer data from the vehicle and dummies were sampled at 10,000 samples per second and processed as specified in SAE J211/1 MAR95 and FMVSS 208, S4.13.

The dynamic tests were recorded using high-speed film and high-speed digital video.

The vehicle appears to meet all of the performance requirements to which it was tested with the exception of the following:

FMVSS 208 S4.5.1 (b)(3) Data Sheet 5 3.3.1 The driver and passenger sun visor air bag warning labels are not permanently affixed to the sun visor. The labels are easily peeled off of the visor.

FMVSS 208 S.5.1.2 / S6.6 The 50<sup>th</sup>% Passenger Dummy SN403 had a Compression Flexion Neck Injury of 1.3 at a 96.9 ms time and a Neck Compression of 5367N during the 25mph unbelted frontal impact test.

### SECTION 3

#### INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
 Test Dates: 1/28/05

#### 5<sup>th</sup> Percentile Female Low Risk Deployments

##### 5<sup>th</sup> Percentile Female SN 506 Position 1 (Chin On Module) 1-28-05

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	76
Peak Nij (Nte)	1.0	0.7
Time (ms)	NA	52.2
Peak Nij (Ntf)	1.0	0.3
Time (ms)	NA	9.8
Peak Nij (Nce)	1.0	0.4
Time (ms)	NA	165.0
Peak Nij (Ncf)	1.0	0.0
Time (ms)	NA	19.8
Neck Tension	2070 N	1607
Neck Compression	2520 N	386
Chest g	60 g	14
Chest Displacement	52 mm	8
Left Femur	6805 N	28
Right Femur	6805 N	36

Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

##### 5<sup>th</sup> Percentile Female SN 511 Position 2 (Chin On Rim) 1-28-05

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	58
Peak Nij (Nte)	1.0	0.6
Time (ms)	NA	52.3
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	88.0
Peak Nij (Nce)	1.0	0.0
Time (ms)	NA	9.8
Peak Nij (Ncf)	1.0	0.3
Time (ms)	NA	92.7
Neck Tension	2070 N	1062
Neck Compression	2520 N	173
Chest g	60 g	18
Chest Displacement	52 mm	13
Left Femur	6805 N	125
Right Femur	6805 N	7

Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

### SECTION 3...(continued)

#### INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
 Test Date: 03/23/05

#### 40 kmph Frontal Crash

Impact Angle: Zero degrees

Belted Dummies:      Yes   X   No  
 Speed Range:      0 to 40 kmph   X   32 to 40 kmph  
                        0 to 48 kmph      0 to 56 kmph

Test Speed: 39.9 kmph                      Test Weight: 1363.5 kg

Driver Dummy:      5<sup>th</sup> female   X   50<sup>th</sup> male  
 Passenger Dummy:      5<sup>th</sup> female   X   50<sup>th</sup> male

#### 50<sup>th</sup> Percentile Male Frontal Crash Test

Vehicles certified to S5.1.1(b)(1), S5.1.1(b)(2), S5.1.2(a)(2), or S5.1.2(b)

Injury Criteria	Max. Allowable Injury Assessment Values	Driver	Passenger
HIC15	700	237	282
N <sub>te</sub>	1.0	0.1	0.0
N <sub>tf</sub>	1.0	0.2	0.0
N <sub>ce</sub>	1.0	0.0	0.3
N <sub>cf</sub>	1.0	0.5	1.3
Neck Tension	4170 N	434	280
Neck Compression	4000 N	3039	5367
Chest g	60 g	34	25
Chest Displacement	63 mm	26	8
Left Femur	10,000 N	4514	2981
Right Femur	10,000 N	2784	3876

## SECTION 4

### DISCUSSION OF TESTS

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
 Test Date: 9/30/04-3/23/05

The vehicle failed to meet the requirements of FMVSS 208 S4.5.1 (b)(3) Data Sheet 5 3.3.1 The driver and passenger sun visor air bag warning labels are not permanently affixed to the sun visor. The labels are easily peeled off of the visor.

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.


The vehicle failed to meet the requirements of FMVSS 208 S.5.1.2 / S6.6 The 50<sup>th</sup> Passenger Dummy SN403 had a Compression Flexion Neck Injury of 1.3 at a 96.9 ms time and a Neck Compression of 5367N during the 25mph unbelted frontal impact test.

Instrument Panel X was not valid after 100 msec during the frontal impact test.

The post test FMVSS 301 rollover was not conducted due to the apparent test failure.

An advanced load cell rigid barrier was used for the test. The details of the barrier are shown below. A photograph of the vehicle in relation to the load cell grid is included in Appendix A. Plots of the total force of all 9 rows and an overlay plot of the summed force from each row are included in Appendix B. The vehicle impacted the barrier 6mm lower than the initial target.

**144 Load Cell Rigid Barrier**  
**Load Cell Locations on Fixed Barrier**



Load Cells are 121 mm x 121 mm with a 7 mm gap between each load cell.

Load cells 2-7 and 9-4 were not functioning during the test.

**SECTION 5**  
**TEST DATA SHEETS**

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
Test Dates: 9/30/04-3/23/05



# DATA SHEET 1

## COTR VEHICLE WORK ORDER

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
 Test Dates: 9/30/04-3/23/05

COTR Signature: Charles R. Case

Test to be performed for this vehicle are checked below:

- |                                     |   |
|-------------------------------------|---|
| <input checked="" type="checkbox"/> | 1. Rear Outboard Seating Position Seat Belts (S4.1.2(b)) & (S4.2.4)   |
| <input checked="" type="checkbox"/> | 2. Air Bag Labels (S4.5.1)  |
| <input checked="" type="checkbox"/> | 3. Readiness Indicator (S4.5.2)   |
| <input checked="" type="checkbox"/> | 4. Passenger Air Bag Manual Cut-off Device (S4.5.4)   |
| <input checked="" type="checkbox"/> | 5. Lap Belt Lockability (S7.1.1.5)  |
| <input checked="" type="checkbox"/> | 6. Seat Belt Warning System (S7.3)  |
| <input checked="" type="checkbox"/> | 7. Seat Belt Contact Force (S7.4.4)   |
| <input checked="" type="checkbox"/> | 8. Seat Belt Latch Plate Access (S7.4.4)  |
| <input checked="" type="checkbox"/> | 9. Seat Belt Retraction (S7.4.5)  |
| <input checked="" type="checkbox"/> | 10. Seat Belt Guides and Hardware (S7.4.6)  |
| <input checked="" type="checkbox"/> | 11. Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) using the following indicated child restraints. |

### Section B

<input checked="" type="checkbox"/>	Britax Handle with Care 191	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
	Century Assura 4553		Full Rearward		Mid Position		Full Forward
	Century Avanta SE 41530		Full Rearward		Mid Position		Full Forward
	Century Smart Fit 4543		Full Rearward		Mid Position		Full Forward
	Cosco Arriva 02727		Full Rearward		Mid Position		Full Forward
	Cosco Opus 35 02603		Full Rearward		Mid Position		Full Forward
	Evenflo Discovery Adjust Right 212		Full Rearward		Mid Position		Full Forward
<input checked="" type="checkbox"/>	Evenflo First Choice 204	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
	Evenflo On My Way Position Right V 282		Full Rearward		Mid Position		Full Forward
<input checked="" type="checkbox"/>	Graco Infant 8457	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward

### Section C

<input checked="" type="checkbox"/>	Britax Roundabout 161	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Century Encore 4612	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
	Century STE 1000 4416		Full Rearward		Mid Position		Full Forward
	Cosco Olympian 02803		Full Rearward		Mid Position		Full Forward
	Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
	Evenflo Horizon V 425		Full Rearward		Mid Position		Full Forward
<input checked="" type="checkbox"/>	Evenflo Medallion 254	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	12. Suppression tests with newborn infant (Part 572, Subpart K) using the following indicated child restraints.						

### Section A

<input checked="" type="checkbox"/>	Cosco Dream Ride 02-719	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	13. Suppression tests with 3-year-old dummy (Part 572, Subpart P) using the following indicated child restraints where a child restraint is required.						

### Section C

<b>X</b>	Britax Roundabout 161	<b>X</b>	Full Rearward	<b>X</b>	Mid Position	<b>X</b>	Full Forward
<b>X</b>	Century Encore 4612	<b>X</b>	Full Rearward	<b>X</b>	Mid Position	<b>X</b>	Full Forward
	Century STE 1000 4416		Full Rearward		Mid Position		Full Forward
	Cosco Olympian 02803		Full Rearward		Mid Position		Full Forward
	Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
	Evenflo Horizon V 425		Full Rearward		Mid Position		Full Forward
<b>X</b>	Evenflo Medallion 254	<b>X</b>	Full Rearward	<b>X</b>	Mid Position	<b>X</b>	Full Forward

### Section D

	Britax Roadster 9004		Full Rearward		Mid Position		Full Forward
<b>X</b>	Century Next Step 4920	<b>X</b>	Full Rearward	<b>X</b>	Mid Position	<b>X</b>	Full Forward
<b>X</b>	Cosco High Back Booster 02-442	<b>X</b>	Full Rearward	<b>X</b>	Mid Position	<b>X</b>	Full Forward
	Evenflo Right Fit 245		Full Rearward		Mid Position		Full Forward

- 14.** Suppression tests with representative 3-year-old child using the following indicated child restraints where a child restraint is required. (Appendix H, Data Sheet 16H and 17H)

### Section C

	Britax Roundabout 161		Full Rearward		Mid Position		Full Forward
	Century Encore 4612		Full Rearward		Mid Position		Full Forward
	Century STE 1000 4416		Full Rearward		Mid Position		Full Forward
	Cosco Olympian 02803		Full Rearward		Mid Position		Full Forward
	Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
	Evenflo Horizon V 425		Full Rearward		Mid Position		Full Forward
	Evenflo Medallion 254		Full Rearward		Mid Position		Full Forward

### Section D

	Britax Roadster 9004		Full Rearward		Mid Position		Full Forward
	Century Next Step 4920		Full Rearward		Mid Position		Full Forward
	Cosco High Back Booster 02-442		Full Rearward		Mid Position		Full Forward
	Evenflo Right Fit 245		Full Rearward		Mid Position		Full Forward

- X** **15.** Suppression tests with 3-year-old dummy (Part 572, Subpart P) in the following Forward, Middle, and Rearward seat track positions

<b>X</b>	Sitting on seat with back against seat back (S22.2.2.1)
<b>X</b>	Sitting on seat with back against reclined seat back (S22.2.2.2)
<b>X</b>	Sitting on seat with back not against seat back (S22.2.2.3)
<b>X</b>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
<b>X</b>	Standing on seat, facing forward (S22.2.2.5)
<b>X</b>	Kneeling on seat facing forward (S22.2.2.6)
<b>X</b>	Kneeling on seat facing rearward (S22.2.2.7)
<b>X</b>	Lying on seat (S22.2.2.8)

- 16.** Suppression tests with representative 3-year-old child in the following positions

	Sitting on seat with back against seat back (S22.2.2.1)
	Sitting on seat with back against reclined seat back (S22.2.2.2)
	Sitting on seat with back not against seat back (S22.2.2.3)
	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
	Standing on seat, facing forward (S22.2.2.5)
	Kneeling on seat facing forward (S22.2.2.6)
	Kneeling on seat facing rearward (S22.2.2.7)
	Lying on seat (S22.2.2.8)

- X** **17.** Suppression tests with 6-year-old dummy (Part 572, Subpart N) using the following indicated child restraints where a child restraint is required.

#### Section D

	Britax Roadster 9004		Full Rearward		Mid Position		Full Forward
X	Century Next Step 4920	X	Full Rearward	X	Mid Position	X	Full Forward
X	Cosco High Back Booster 02-442	X	Full Rearward	X	Mid Position	X	Full Forward
X	Evenflo Right Fit 245	X	Full Rearward	X	Mid Position	X	Full Forward

18. Suppression tests with representative 6-year-old child using the following indicated child restraints where a child restraint is required.

#### Section D

	Britax Roadster 9004		Full Rearward		Mid Position		Full Forward
	Century Next Step 4920		Full Rearward		Mid Position		Full Forward
	Cosco High Back Booster 02-442		Full Rearward		Mid Position		Full Forward
	Evenflo Right Fit 245		Full Rearward		Mid Position		Full Forward

- X 19. Suppression tests with 6-year-old dummy (Part 572, Subpart N) in the following Forward, Middle, and Rearward seat track positions

X	Sitting on seat with back against seat back (S22.2.2.1)
X	Sitting on seat with back against reclined seat back (S22.2.2.2)
X	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
X	Sitting back in the seat and leaning on the right front passenger door (S24.2.3)

20. Suppression tests with representative 6-year-old child in the following positions

	Sitting on seat with back against seat back (S22.2.2.1)
	Sitting on seat with back against reclined seat back (S22.2.2.2)
	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
	Sitting back in the seat and leaning on the right front passenger door (S24.2.3)

- X 21. Test of Reactivation of the Passenger Air Bag System with an Unbelted 5<sup>th</sup> percentile female dummy (S20.3, 22.3, S24.3). Perform this test after the following suppression tests: After each restraint.

22. Test of Reactivation of the passenger air bag system with a representative 5<sup>th</sup> percentile female (S20.3, 22.3, S24.3). Perform this test after the following suppression tests:

23. Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) using the following indicated child restraints.

#### Section B

	Britax Handle with Care 191		Full Rearward		Mid Position		Full Forward
	Century Assura 4553		Full Rearward		Mid Position		Full Forward
	Century Avanta SE 41530		Full Rearward		Mid Position		Full Forward
	Century Smart Fit 4543		Full Rearward		Mid Position		Full Forward
	Cosco Arriva 02727		Full Rearward		Mid Position		Full Forward
	Cosco Opus 35 02603		Full Rearward		Mid Position		Full Forward
	Evenflo Discovery Adjust Right 212		Full Rearward		Mid Position		Full Forward
	Evenflo First Choice 204		Full Rearward		Mid Position		Full Forward
	Evenflo On My Way Position Right V 282		Full Rearward		Mid Position		Full Forward
	Graco Infant 8457		Full Rearward		Mid Position		Full Forward

#### Section C

	Britax Roundabout 161		Full Rearward		Mid Position		Full Forward
	Century Encore 4612		Full Rearward		Mid Position		Full Forward
	Century STE 1000 4416		Full Rearward		Mid Position		Full Forward
	Cosco Olympian 02803		Full Rearward		Mid Position		Full Forward
	Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
	Evenflo Horizon V 425		Full Rearward		Mid Position		Full Forward
	Evenflo Medallion 254		Full Rearward		Mid Position		Full Forward

- ☐ 24. Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) in the following positions
- ☐ Position 1
- ☐ Position 2
- ☐ 25. Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) in the following positions
- ☐ Position 1
- ☐ Position 2
- ☒ 26. Low risk deployment test with 5<sup>th</sup> percentile female dummy (Part 572, Subpart O) in the following positions
- ☒ Position 1
- ☒ Position 2
- ☒ 27. Impact Tests
- ☐ Frontal Oblique – Test Speed:
- ☐ Belted 50<sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))
- ☐ Unbelted 50<sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))
- ☐ Unbelted 50<sup>th</sup> male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a) (1) or S5.1.2(b))
- ☒ Frontal 0° - Test Speed: 39.9 kmph
- ☐ Belted 50<sup>th</sup> male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
- ☐ Belted 50<sup>th</sup> male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
- ☐ Belted 5<sup>th</sup> female dummy driver (0 to 48 kmph) (S16.1(a))
- ☐ Belted 5<sup>th</sup> female dummy passenger (0 to 48 kmph) (S16.1(a))
- ☐ Belted 50<sup>th</sup> male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2))
- ☐ Unbelted 50<sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1))
- ☒ Unbelted 50<sup>th</sup> male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
- ☒ Unbelted 50<sup>th</sup> male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
- ☐ Unbelted 5<sup>th</sup> female dummy driver (32 to 40 kmph) (S16.1(b))
- ☐ Unbelted 5<sup>th</sup> female dummy passenger (32 to 40 kmph) (S16.1(b))
- ☐ 40% Offset 0° Belted 5<sup>th</sup> male dummy driver and passenger (0 to 40 kmph) (S18.1) – Test Speed:
- ☐ 28. Sled Test: Unbelted 50<sup>th</sup> male dummy driver and passenger (S13)
- ☐ 29. FMVSS 204 Indicant Test
- ☒ 30. FMVSS 212 Indicant Test
- ☒ 31. FMVSS 219 Indicant Test
- ☒ 32. FMVSS 301 Frontal Indicant Test

**DATA SHEET 2**  
**REPORT OF VEHICLE CONDITION**

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
Test Dates: 9/30/04-3/23/05

CONTRACT NO. DTNH22- 03-D-11002 Date: 3/31/05  
FROM (Lab and rep name): MGA Research Corporation  
TO: NHTSA, OVSC (NVS-220)

PURPOSE: (X) Initial Receipt ( ) Received via Transfer (X ) Present vehicle condition

MODEL YEAR/MAKE/MODEL/BODY STYLE: 2005 Toyota Corolla  
MANUFACTURE DATE: 07/04  
NHTSA NO. C55101 GVWR: 1626 kg (3585 lbs)  
BODY COLOR: White GAWR (Fr): 855 kg (1885 lbs)  
VIN: JTDBR32E952055812 GAWR (Rr): 780 kg (1720 lbs)

ODOMETER READINGS: ARRIVAL (miles): 151 DATE: 9/20/04  
COMPLETION (miles): 158 DATE: 3/23/05

PURCHASE PRICE: (\$) 16,562

DEALER'S NAME: Safro Imports of Brookfield; 20445 W Capital Dr; Brookfield WI 53008.

- A. All options listed on window sticker are present on the test vehicle:  
X Yes      No
- B. Tires and wheel rims are new and the same as listed: X Yes      No
- C. There are no dents or other interior or exterior flaws: X Yes      No
- D. The vehicle has been properly prepared and is in running condition:  
X Yes      No
- E. Keyless remote is available and working: X Yes      No
- F. The glove box contains an owner's manual, warranty document, consumer information, and extra set of keys: X Yes      No
- G. Proper fuel filler cap is supplied on the test vehicle: X Yes      No
- H. Using permanent marker, identify vehicle with NHTSA number and FMVSS test type(s) on roof line above driver door or for school buses, place a placard with NHTSA number inside the windshield and to the exterior front and rear side of bus:  
X Yes      No
- I. Place vehicle in storage area: X Yes      No
- J. Inspect the vehicle's interior and exterior, including all windows, seats, doors, etc. to confirm that each system is complete and functional per the manufacturer's specifications. Any damage, misadjustment, or other unusual condition that could influence the test program or test results shall be recorded. Report any abnormal condition to the NHTSA COTR before beginning any test:  
X Vehicle OK      Conditions reported below

## REPORT OF VEHICLE CONDITION AT THE COMPLETION OF TESTING

LIST OF FMVSS TESTS PERFORMED BY THIS LAB: FMVSS 208, 212, 219, 301

VEHICLE: 2005 Toyota Corolla NHTSA NO. C55101

REMARKS:

Equipment that is no longer on the test vehicle as noted on previous page:

Rear seat bottom, spare tire, trunk interior, RH rear tail light

Explanation for equipment removal:

Components removed for instrumentation installation and to meet target weight.

Test Vehicle Condition:

25 mph frontal impact damage- front suspension & structure damaged, hood & front quarter panels damaged, radiator damaged, air bags & pretensioners deployed, Stoddard in fuel system

RECORDED BY: Jeff Lewandowski DATE: 3/31/2005

APPROVED BY: David Winkelbauer DATE: 3/31/2005

#####

## RELEASE OF TEST VEHICLE

The vehicle described above is released from MGA to be delivered to:

Date: Time: Odometer:

Lab Rep's Signature:

Title:

Carrier/Customer Rep:

Date:

**DATA SHEET 3****CERTIFICATION LABEL AND TIRE PLACARD INFORMATION**

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance  
Test Technician: Nick Kosinski

NHTSA No.: C55101  
Test Date: 3/23/05

Certification Label	
Manufacturer:	Toyota Motor Corporation
Date of Manufacture:	07/04
VIN:	JTDBR32E952055812
Vehicle Certified As (Pass. Car/MPV/Truck/Bus):	Passenger Car
Front Axle GVWR:	855 kg (1885 lbs)
Rear Axle GVWR:	780 kg (1720 lbs)
Total GVWR:	1626 kg (3585 lbs)

Tire Placard	
Not applicable, vehicle is not a passenger car and does not have a tire placard.	Passenger Car
This is not a passenger car, but all or part of this information is still contained on a vehicle label and is reported here.	Passenger Car
Vehicle Capacity Weight:	385 kg (850 lbs)
Designated Seating Capacity Front:	2
Designated Seating Capacity Rear:	3
Total Designated Seating Capacity:	5
Recommended Cold Tire Inflation Pressure Front:	210 kpa (30 psi)
Recommended Cold Tire Inflation Pressure Rear:	210 kpa (30 psi)
Recommended Tire Size:	P195/65R15

Signature: 

Date: 03/21/05

#### DATA SHEET 4

##### REAR OUTBOARD SEATING POSITION SEAT BELTS

Test Vehicle: 2005 Toyota Corolla 4 Door  
Test Program: FMVSS 208 Compliance  
Test Technician: Wayne Dahlke

NHTSA No.: C55101  
Test Date: 9/30/04

	Yes	No
Do all rear outboard seating positions have Type 2 seat belts?	X	

If NO, describe the seat belt installed, the seat location, and any other information about the seat that would explain why a Type 2 seat belt was not installed.

REMARKS:

Signature: Wayne Dahlke

Date: 9/30/04



# **DATA SHEET 5** **AIR BAG LABELS (S4.5.1)**

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

- |                                     |     |  |
|-------------------------------------|-----|--|
| <input checked="" type="checkbox"/> | 1.  | Air bag maintenance label and owner's manual instructions: (S4.5.1(a))   |
| <input checked="" type="checkbox"/> | 1.1 | Does the manufacturer recommend periodic maintenance or replacement of the air bag?  |
|                                     |     | <input type="checkbox"/> Yes, go to 1.2  |
|                                     |     | <input checked="" type="checkbox"/> No – go to 2   |
| <input type="checkbox"/>            | 1.2 | Does the vehicle have a label specifying air bag maintenance or replacement?   |
|                                     |     | <input type="checkbox"/> Yes – Pass  |
|                                     |     | <input type="checkbox"/> No – Fail   |
| <input type="checkbox"/>            | 1.3 | Does the label contain one of the following?   |
|                                     |     | <input type="checkbox"/> Yes – Pass  |
|                                     |     | <input type="checkbox"/> No – Fail   |
|                                     |     | Check applicable schedule:   |
|                                     |     | ___ Schedule on label specifies month and year (Record date_____)  |
|                                     |     | ___ Schedule on label specified vehicle mileage (Record mileage_____)  |
|                                     |     | ___ Schedule on label specifies interval measured from date on certification label (Record interval_____)  |
| <input type="checkbox"/>            | 1.4 | Is the label permanently affixed within the passenger compartment such that it cannot be removed without destroying or defacing the label or the sunvisor? |
|                                     |     | <input type="checkbox"/> Yes – Pass  |
|                                     |     | <input type="checkbox"/> No – Fail   |
| <input type="checkbox"/>            | 1.5 | Is the label lettered in English?  |
|                                     |     | <input type="checkbox"/> Yes – Pass  |
|                                     |     | <input type="checkbox"/> No – Fail   |
| <input type="checkbox"/>            | 1.6 | Is the label in block capitals and numerals?   |
|                                     |     | <input type="checkbox"/> Yes – Pass  |
|                                     |     | <input type="checkbox"/> No – Fail   |
| <input type="checkbox"/>            | 1.7 | Are the letters and numerals at least 3/32 inches high?  |
|                                     |     | <input type="checkbox"/> Yes – Pass  |
|                                     |     | <input type="checkbox"/> No – Fail   |
| <input type="checkbox"/>            | 1.8 | Does the owner's manual set forth the recommended schedule for maintenance or replacement?   |
| <input checked="" type="checkbox"/> | 2.  | Does the owner's manual: (S4.5.1(f))   |
| <input checked="" type="checkbox"/> | 2.1 | Include a description of the vehicle's air bag system in an easily understandable format?  |
|                                     |     | <input checked="" type="checkbox"/> Yes – Pass   |
|                                     |     | <input type="checkbox"/> No – Fail   |
| <input checked="" type="checkbox"/> | 2.2 | Include a statement that the vehicle is equipped with an air bag and a lap/shoulder belt at the front outboard seating position?                           |
|                                     |     | <input checked="" type="checkbox"/> Yes – Pass   |
|                                     |     | <input type="checkbox"/> No – Fail   |


- ☒ 2.3 Include a statement that the air bag is a supplement restraint at the front outboard seating position?
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.4 Emphasize that all occupants, including the driver, should always wear their seat belts whether or not an air bag is also provided at their seating positions to minimize the risk of severe injury or death in the event of a crash?
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.5 Provide any necessary precautions regarding the proper positioning of occupants, including children, at seating positions equipped with air bags to ensure maximum safety protection for those occupants?
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.6 Explain that no objects should be placed over or near the air bag on the steering wheel or on the instrument panel, because any such objects could cause harm if the vehicle is in a crash severe enough to cause the air bag to inflate?
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7 Is the vehicle certified to meet the requirements of S14.5, S15, S17, S19, S21, S23, and S25? (Obtain answer from COTR) (S4.5.1(f)(2))
- ☒ Yes – (Go to 2.7.1)  
☐ No – (Go to 3.)
- ☒ 2.7.1 Explain the proper functioning of the advanced air bag system? (S4.5.1(f)(2))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.2 Provide a summary of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.3 Present and explain the main components of the advanced passenger air bag system? (S4.5.1(f)(2)(i))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.4 Explain how the components function together as part of the advanced passenger air bag system? (S4.5.1(f)(2)(ii))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.5 Contain the basic requirements for proper operation, including an explanation of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2)(iii))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.6 Is the vehicle certified to the requirements of S19.2, S21.2, or 23.2 (automatic suppression)?
- ☒ Yes, continue with 2.7.6  
☐ No, go to 2.7.7
- ☒ 2.7.6.1 Contain a complete description of the passenger air bag suppression system installed in the vehicle, including a discussion of any suppression zone? (S4.5.1(f)(2)(iv))
- ☒ Yes – Pass  
☐ No – Fail

- ☒ 2.7.6.2 Discuss the telltale light, specifying its location in the vehicle and explaining when the light is illuminated?
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.7 Explain the interaction of the advanced passenger air bag system with other vehicle components, such as seat belts, seats or other components? (S4.5.1(f)(2)(v))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.8 Summarize the expected outcomes when child restraint systems, children and small teenagers or adults are both properly and improperly positioned in the passenger seat, including cautionary advice against improper placement of child restraint systems? (S4.5.1(f)(2)(vi))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 2.7.9 Provide information on how to contact the vehicle manufacturer concerning modifications for persons with disabilities that may affect the advanced air bag system? (S4.5.1(f)(2)(vii))
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 3. Sun Visor Air Bag Warning Label (S4.5.1(b)) Check only one of the following:
- ☐ The vehicle is not certified to meet the requirements of S19, S21, and S23 (Obtain answer from COTR) (S4.5.1(b)(1)) Go to 3.1 and skip 3.2 and 3.3
- ☐ The vehicle is certified to meet the requirements of S19, S21, and S23 before 9/1/03. (Obtain answer from COTR) (S4.5.1(b)(2)) Go to 3.2 and skip 3.1 and 3.3
- ☒ The vehicle is certified to meet the requirements of S19, S21, and S23 on 9/1/03 or later. (Obtain answer from COTR) (S4.5.1(b)(3)) Go to 3.3 and skip 3.1 and 3.2
- ☐ 3.1 Vehicles not certified to meet the requirements of S19, S21, and S23.
- ☐ 3.1.1 Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing it? (S4.5.1(b)(1))
- ☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail



3.1.2

Does the label conform in content to the label shown in either Figure 6A or 6B (Figure 6b is for vehicles with passenger air bag on-off switches), as appropriate, at each front outboard seating position? (S4.5.1(b)(1)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(1)(iv))



Driver Side, Yes – Pass



Driver Side, No – Fail



Passenger Side, Yes – Pass



Passenger Side, No – Fail



3.1.3

Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(1)(i))



Driver Side, Yes – Pass



Driver Side, No – Fail



Passenger Side, Yes – Pass



Passenger Side, No – Fail



3.1.4

Is the message area white with black text? (S4.5.1(b)(1)(ii))



Driver Side, Yes – Pass



Driver Side, No – Fail



Passenger Side, Yes – Pass




Passenger Side, No – Fail

- ☐ 3.1.5 Is the message area at least 30 cm<sup>2</sup>? (S4.5.1(b)(1)(ii))  
 Driver Side: Length \_\_\_\_, Width \_\_\_\_  
 Passenger Side: Length \_\_\_\_, Width \_\_\_\_  
 Actual message area \_\_\_\_ cm<sup>2</sup>  
☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☐ 3.1.6 Is the pictogram black with a red circle and slash on a white background? (S4.5.1(b)(2)(iii))  
☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☐ 3.1.7 Is the pictogram at least 30 mm in diameter? (S4.5.1(b)(2)(iii))  
 Actual diameter \_\_\_\_ mm  
☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☐ 3.2 Vehicles certified to meet the requirements of S19, S21, and S23 before 9/1/03.
- ☐ 3.2.1 Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(b)(2))  
☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail



3.2.2

Does the label conform in content to the label shown in either Figure 8 or 11 at each front outboard seating position? (S4.5.1(b)(2)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(2)(iv)) Vehicles without back seats or the back seat is too small to accommodate a rear-facing child restraint may omit the statement "Never put a rear-facing child seat in the front."(S4.5.1(b)(2)(v))



- Driver Side, Yes – Pass
- Driver Side, No – Fail
- Passenger Side, Yes – Pass
- Passenger Side, No – Fail



3.2.3

Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(2)(i))



- Driver Side, Yes – Pass
- Driver Side, No – Fail
- Passenger Side, Yes – Pass
- Passenger Side, No – Fail



3.2.4

Is the message area white with black text? (S4.5.1(b)(2)(ii))



- Driver Side, Yes – Pass
- Driver Side, No – Fail
- Passenger Side, Yes – Pass
- Passenger Side, No – Fail

- ☐ 3.2.5 Is the message area at least 30 cm<sup>2</sup>? (S4.5.1(b)(2)(ii))  
 Driver Side: Length\_\_\_\_\_, Width\_\_\_\_\_  
 Passenger Side: Length\_\_\_\_\_, Width\_\_\_\_\_  
 Actual message area \_\_\_\_\_ cm<sup>2</sup>
- ☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☐ 3.2.6 Is the pictogram black on a white background? (S4.5.1(b)(2)(iii))
- ☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☐ 3.2.7 Is the pictogram at least 30 mm (1.2 inches) in length? (S4.5.1(b)(2)(iii))  
 Driver Side: Length\_\_\_\_\_  
 Passenger Side: Length\_\_\_\_\_
- ☐ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☐ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☒ 3.3 Vehicles certified to meet the requirements of S19, S21, and S23 on 9/1/03 and later. (S4.5.1(b)(3))
- ☒ 3.3.1 Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(b)(3))
- ☐ Driver Side, Yes – Pass  
☒ Driver Side, **No – Fail**  
☐ Passenger Side, Yes – Pass  
☒ Passenger Side, **No – Fail**

- X** 3.3.2 Does the label conform in content to the label shown in either Figure 11 at each front outboard seating position? (S4.5.1(b)(2)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(3)(iv)) Vehicles without back seats or the back seat is too small to accommodate a rear-facing child restraint may omit the statement "Never put a rear-facing child seat in the front." (S4.5.1(b)(3)(v))



Figure 11. Sun Visor Label Visible when Visor is in Down Position.

- X** Driver Side, Yes – Pass  
 Driver Side, No – Fail  
**X** Passenger Side, Yes – Pass  
 Passenger Side, No – Fail
- X** 3.3.3 Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(3)(i))
- X** Driver Side, Yes – Pass  
 Driver Side, No – Fail  
**X** Passenger Side, Yes – Pass  
 Passenger Side, No – Fail
- X** 3.3.4 Is the message area white with black text? (S4.5.1(b)(3)(ii))
- X** Driver Side, Yes – Pass  
 Driver Side, No – Fail  
**X** Passenger Side, Yes – Pass  
 Passenger Side, No – Fail
- X** 3.3.5 Is the message area at least 30 cm<sup>2</sup>? (S4.5.1(b)(3)(ii))
- Driver Side: Length 15.0 cm , Width 6.0 cm  
 Passenger Side: Length 15.0 cm, Width 6.0 cm  
 Driver Actual message area 90.0 cm<sup>2</sup>  
 Passenger Actual message area 90.0 cm<sup>2</sup>
- X** Driver Side, Yes – Pass  
 Driver Side, No – Fail  
**X** Passenger Side, Yes – Pass  
 Passenger Side, No – Fail
- X** 3.3.6 Is the pictogram black on a white background? (S4.5.1(b)(3)(iii))
- X** Driver Side, Yes – Pass  
 Driver Side, No – Fail  
**X** Passenger Side, Yes – Pass  
 Passenger Side, No – Fail



- ☒ 3.3.7 Is the pictogram at least 30 mm (1.2 inches) in length? (S4.5.1(b)(3)(iii))  
 Driver Side: Length 32 mm  
 Passenger Side: Length 32 mm  
☒ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☒ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☒ 3.4 Is the same side of the sun visor that contains the air bag warning label free of other information with the exception of the air bag maintenance label and/or the rollover-warning label? (S4.5.1(b)(5)(i))  
☒ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☒ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☒ 3.5 Is the sun visor free of other information about air bags or the need to wear seat belts with the exception of the air bag alert label and/or the rollover-warning label? (S4.5.1(b)(5)(ii))  
☒ Driver Side, Yes – Pass  
☐ Driver Side, No – Fail  
☒ Passenger Side, Yes – Pass  
☐ Passenger Side, No – Fail
- ☒ 3.6 Does the driver side visor contain a rollover-warning label on the same side of the visor as the air bag warning label?  
 \_\_\_ Yes, go to 3.6.1  
X No, go to 4 (skipping 3.6.1 through 3.6.3)
- ☐ 3.6.1 Are both the rollover-warning label and the air bag warning label surrounded by a continuous solid-lined border?  
 \_\_\_ Yes, go to 3.6.2 and skip 3.6.3  
 \_\_\_ No, go to 3.6.3 and skip 3.6.2
- ☐ 3.6.2 Is the shortest distance from the border of the rollover label to the border of the air bag warning label at least 1 cm? (575.105 (d)(1)(iv)(B))  
 \_\_\_\_\_ actual distance
- ☐ 3.6.3 Is the shortest distance from any of the lettering or graphics on the rollover-warning label to any of the lettering or graphics of the air bag warning label at least 3 cm? (575.105 (d)(1)(iv)(A))  
 \_\_\_\_\_ actual distance  
 \_\_\_ Yes-Pass    \_\_\_ No-FAIL
- ☒ 4. Air Bag Alert Label (S4.5.1(c) (A “Rollover Warning Label” or “Rollover Alert Label” may be on the same side of the driver’s sun visor as the “Air Bag Alert Label.” 575.105(d))

☒ 4.1 Is the sun visor warning label visible when the sun visor is in the stowed position?

☒ If yes for driver and passenger, go to 5.

☒ Driver Side, Yes - Pass

☐ Driver Side, No - Fail

☒ Passenger Side, Yes - Pass

☐ Passenger Side, No - Fail

☐ 4.2 Is the air bag alert label permanently affixed (including permanent marking on the visor material or molding into the visor material) to the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(c))

☐ Driver Side, Yes - Pass

☐ Driver Side, No - Fail

☐ Passenger Side, Yes - Pass

☐ Passenger Side, No - Fail

☐ 4.3 Is the air bag alert label visible when the visor is in the stowed position? (S4.5.1(c))

☐ Driver Side, Yes - Pass

☐ Driver Side, No - Fail

☐ Passenger Side, Yes - Pass

☐ Passenger Side, No - Fail

☐ 4.4 Does the label conform in content to the label shown in Figure 6C? (S4.5.1(c))




Figure 6c. Sun Visor Label Visible When Visor is in Up Position.

☐ Driver Side, Yes - Pass

☐ Driver Side, No - Fail

☐ Passenger Side, Yes - Pass

☐ Passenger Side, No - Fail

☐ 4.5 Is the message area black with yellow text? (S4.5.1(c)(1))

☐ Driver Side, Yes - Pass

☐ Driver Side, No - Fail

☐ Passenger Side, Yes - Pass

☐ Passenger Side, No - Fail

<input type="checkbox"/>	4.6	Is the message area at least 20 cm <sup>2</sup> ? (S4.5.1(c)(1)) Driver Side: Length ____, Width ____ Passenger Side: Length ____, Width ____ Actual message area ____ <input type="checkbox"/> Driver Side, Yes - Pass <input type="checkbox"/> Driver Side, No - Fail <input type="checkbox"/> Passenger Side, Yes - Pass <input type="checkbox"/> Passenger Side, No - Fail
<input type="checkbox"/>	4.7	Is the pictogram black with a red circle and slash on a white background? (S4.5.1(c)(2)) <input type="checkbox"/> Driver Side, Yes - Pass <input type="checkbox"/> Driver Side, No - Fail <input type="checkbox"/> Passenger Side, Yes - Pass <input type="checkbox"/> Passenger Side, No - Fail
<input type="checkbox"/>	4.8	Is the pictogram at least 20 mm in diameter? (S4.5.1(c)(2)) Driver Side Diameter ____ mm Passenger Side Diameter ____ mm <input type="checkbox"/> Driver Side, Yes - Pass <input type="checkbox"/> Driver Side, No - Fail <input type="checkbox"/> Passenger Side, Yes - Pass <input type="checkbox"/> Passenger Side, No - Fail
<input checked="" type="checkbox"/>	5.	Label on the Dashboard
<input checked="" type="checkbox"/>	5.1	Is the vehicle certified to meet the requirements of S19, S21, and S23? (Obtain answer from COTR) (S4.5.1(3)(2)) <input checked="" type="checkbox"/> Yes, go to 5.1.1 and <b>skip 5.2</b> <input type="checkbox"/> No, go to 5.2, skipping 5.1.1 through 5.1.6
<input checked="" type="checkbox"/>	5.1.1	Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(2)) <input checked="" type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail
<input checked="" type="checkbox"/>	5.1.2	Is the label clearly visible from all front seating positions? (S4.5.1(e)(2)) <input checked="" type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail
<input checked="" type="checkbox"/>	5.1.3	Does the label conform in content to the label shown in Figure 9? (S4.5.1(e)(2)) Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(e)(2)(iii)) <input checked="" type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail



Figure 9. Removable Label on Dash.

- ☒ 5.1.4 Is the heading area yellow with black text? (S4.5.1(e)(2)(i))
- ☒ Yes - Pass
- ☐ No - Fail
- ☒ 5.1.5 Is the message white with black text? (S4.5.1(e)(2)(ii))
- ☒ Yes - Pass
- ☐ No - Fail
- ☒ 5.1.6 Is the message area at least 30 cm<sup>2</sup>? (S4.5.1(e)(2)(ii))
- Length 10.1 cm , Width 3.9 cm
- Actual message area 39.39 cm<sup>2</sup>
- ☒ Yes - Pass
- ☐ No - Fail
- ☐ 5.2 Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(1))
- ☐ Yes - Pass
- ☐ No - Fail
- ☐ 5.2.1 Is the label clearly visible from all front seating positions? (S4.5.1(e)(1))
- ☐ Yes - Pass
- ☐ No - Fail
- ☐ 5.2.2 Does the label conform in content to the label shown in Figure 7? (S4.5.1(e)(1)(iii))
- Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(e)(2)(iii))
- ☐ Yes - Pass
- ☐ No - Fail




Figure 7. Removable Label on Dash.

- ☐ 5.2.3 Is the heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(e)(1)(i))
- ☐ Yes - Pass
- ☐ No - Fail
- ☐ 5.2.4 Is the message white with black text? (S4.5.1(e)(1)(ii))
- ☐ Yes - Pass
- ☐ No - Fail
- ☐ 5.2.5 Is the message area at least 30 cm<sup>2</sup>? (S4.5.1(e)(1)(ii))
- Length \_\_, Width \_\_
- Actual message area \_\_ cm<sup>2</sup>
- ☐ Yes - Pass
- ☐ No - Fail

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 9/30/04

## DATA SHEET 6

### FMVSS 208 READINESS INDICATOR (S4.5.2)

Test Vehicle: 2005 Toyota Corolla 4 Door  
Test Program: FMVSS 208 Compliance  
Test Technician: Wayne Dahlke

NHTSA No.: C55101  
Test Date: 9/30/04

An occupant restraint system that deploys in the event of a crash shall have a monitoring system with a readiness indicator. A totally mechanical system is exempt from this requirement. (11/8/94 legal interpretation to Lawrence F. Hennegerger on behalf of Breed)

- ☒ 1. Is the system totally mechanical? If Yes, this data sheet is complete.  
☐ Yes  
☒ No
- ☒ 2. Describe the location of the readiness indicator: bottom left side of instrument cluster
- ☒ 3. Is the readiness indicator clearly visible to the driver?  
☒ Yes - Pass  
☐ No - Fail
- ☒ 4. Is a list of the elements in the occupant restraint system, being monitored by the readiness indicator, provided on a label or in the owner's manual?  
☒ Yes - Pass  
☐ No - Fail
- ☒ 5. Does the vehicle have an on-off switch for the passenger air bag?  
☐ If Yes, go to 6  
☒ If No, this form is complete.
- ☐ 6. Is the air bag readiness indicator off when the passenger air bag switch is in the off position?  
☐ Yes - Pass  
☐ No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Dahlke

Date: 9/30/04

## DATA SHEET 7

### PASSENGER AIR BAG MANUAL CUT-OFF DEVICE (S4.5.4)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

- |                                     |     |  |
|-------------------------------------|-----|--|
| <input checked="" type="checkbox"/> | 1.  | Is the vehicle equipped with an on-off switch that deactivates the air bag installed at the right front outboard seating position?   |
|                                     |     | <input type="checkbox"/> Yes, go to 2  |
|                                     |     | <input checked="" type="checkbox"/> No, this sheet is complete   |
| <input type="checkbox"/>            | 2.  | Does the vehicle have any forward-facing rear designated seating positions? (S4.5.4(a))  |
|                                     |     | <input type="checkbox"/> Yes, go to 3  |
|                                     |     | <input type="checkbox"/> No, go to 4   |
| <input type="checkbox"/>            | 3.  | Verification of the lack of room for a child restraint in the rear seat behind the driver's seat. (S4.5.4(b))  |
| <input type="checkbox"/>            | 3.1 | Position the seat's adjustable lumbar supports to that the lumbar support is in its lowest, retracted or deflated adjustment position (S8.1.3)   |
|                                     |     | <input type="checkbox"/> N/A, no lumbar adjustment   |
| <input type="checkbox"/>            | 3.2 | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.02)   |
|                                     |     | <input type="checkbox"/> N/A, no additional support adjustment   |
| <input type="checkbox"/>            | 3.3 | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)  |
|                                     |     | <input type="checkbox"/> N/A, no independent fore-aft seat cushion adjustment  |
| <input type="checkbox"/>            | 3.4 | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position (S16.2.10.3.1)  |
|                                     |     | <input type="checkbox"/> N/A, no independent seat cushion height adjustment  |
| <input type="checkbox"/>            | 3.5 | Put the seat in its full rearward position. (S16.2.10.3.1)   |
|                                     |     | <input type="checkbox"/> N/A, the seat does not have a fore-aft adjustment   |
| <input type="checkbox"/>            | 3.6 | If the seat height is adjustable, put it in the full down position. (S16.2.10.3.1)   |
|                                     |     | <input type="checkbox"/> N/A, no seat height adjustment  |
| <input type="checkbox"/>            | 3.7 | Draw a horizontal reference line on the side of the seat cushion.  |
| <input type="checkbox"/>            | 3.8 | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
|                                     |     | <input type="checkbox"/> N/A – the seat does not have a fore-aft adjustment.   |
| <input type="checkbox"/>            | 3.9 | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position. (S8.1.2)   |
|                                     |     | <input type="checkbox"/> N/A – the seat does not have fore-aft adjustment.   |
|                                     |     | <input type="checkbox"/> Mid position  |

<input type="checkbox"/>		If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat:
<input type="checkbox"/>	3.10	If seat adjustments, other than fore-aft, are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal.
<input type="checkbox"/>		<input type="checkbox"/> N/A – No adjustments
<input type="checkbox"/>		Angle of reference line as tested:
<input type="checkbox"/>	3.11	The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
<input type="checkbox"/>		<input type="checkbox"/> N/A – No seat back angle adjustment
<input type="checkbox"/>		Manufacturers design seat back angle:
<input type="checkbox"/>		Tested seat back angle:
<input type="checkbox"/>	3.12	Is the driver seat a bucket seat?
<input type="checkbox"/>		<input type="checkbox"/> Yes, go to 3.12.1 and skip 3.12.2
<input type="checkbox"/>		<input type="checkbox"/> No, go to 3.12.2 and skip 3.12.1
<input type="checkbox"/>	3.12.1	Bucket Seats:
<input type="checkbox"/>	3.12.1.1	Locate and mark a vertical Plane B through the longitudinal centerline of the seat driver's seat cushion. (S22.2.1.3) The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle.
<input type="checkbox"/>		Record the width of the seat:
<input type="checkbox"/>		Record the distance from the edge of the seat to Plane B:
<input type="checkbox"/>	3.12.1.2	Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion behind the driver's seat. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the driver's seat.
<input type="checkbox"/>		Distance (mm):
<input type="checkbox"/>		<input type="checkbox"/> Less than 720 mm – Pass
<input type="checkbox"/>		<input type="checkbox"/> More then 720 mm – Fail
<input type="checkbox"/>		Go to 4
<input type="checkbox"/>	3.12.2	Bench seats (including split bench seats):
<input type="checkbox"/>	3.12.2.1	Locate and mark a vertical Plane B through the center of the steering wheel parallel to the vehicle longitudinal centerline.
<input type="checkbox"/>	3.12.2.2	Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the front seat.
<input type="checkbox"/>		Distance (mm):
<input type="checkbox"/>		<input type="checkbox"/> Less than 720 mm – Pass
<input type="checkbox"/>		<input type="checkbox"/> More then 720 mm – Fail



<input type="checkbox"/>		Go to 4
<input type="checkbox"/>	4.	Does the device turn the air bag on and off using the vehicle's ignition key? (S4.5.4.2)
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input type="checkbox"/>	5.	Is the on-off device separate from the ignition switch? (S4.5.4.2)
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input type="checkbox"/>	6.	Is there a telltale light that comes on when the passenger air bag is turned off? (S4.5.4.2)
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input type="checkbox"/>	7.	Telltale light (S4.5.4.3)
<input type="checkbox"/>	7.1	Is the light yellow? S4.5.4.3(a))
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input type="checkbox"/>	7.2	Are the words "PASSENGER AIR BAG OFF" (S4.5.4.3(b))
<input type="checkbox"/>	7.2.1	on the telltale?
		<input type="checkbox"/> Yes – Pass, go to 7.3
		<input type="checkbox"/> No – go to 7.2.2
<input type="checkbox"/>	7.2.2	within 25 mm of the telltale?
<input type="checkbox"/>		Measurement from the edge of the telltale light (mm):
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input type="checkbox"/>	7.3	Does the telltale remain illuminated while the air bag is turned off? (S4.5.4.3c)) (Leave the air bag off for 5 minutes.)
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input type="checkbox"/>	7.4	Is the telltale illuminated while the air bag is turned on? (S4.5.4.3(d))
		<input type="checkbox"/> Yes – Fail
		<input type="checkbox"/> No – Pass
<input type="checkbox"/>	7.5	Is the telltale combined with the air bag readiness indicator? (S4.5.4.3(e))
		<input type="checkbox"/> Yes – Fail
		<input type="checkbox"/> No – Pass
<input type="checkbox"/>	8.	Owner's Manual
<input type="checkbox"/>	8.1	Does the owner's manual contain complete instructions on the operation of the on-off switch? (S4.5.4.4(a))
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail

<input type="checkbox"/>	8.2	<p>Does the owner's manual contain a statement that the on-off switch should only be used when a member of one of the following risk groups is occupying the right front passenger seating position? (S4.5.4.4(b))</p> <p>Infants:      there is no back seat                         the rear seat is too small to accommodate a child restraint                         there is a medical condition that must be monitored constantly</p> <p>Children      there is no back seat          aged        space is not always available in the rear seat          1 to 12:    there is a medical condition that must be monitored constantly</p> <p>Medical      medical risk causes special risk for passenger          condition:   greater risk for harm than with the air bag on</p>
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	8.3	<p>Does the owner's manual contain a warning about the safety consequences of using the on-off switch at other times?</p>
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 9/30/04

## DATA SHEET 8

### LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger  
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2005 Toyota Corolla 4 Door  
Test Program: FMVSS 208 Compliance  
Test Technician: Wayne Dahlke

NHTSA No.: C55101  
Test Date: 9/30/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Front Passenger
------------------------------	-----------------

<input type="checkbox"/>		N/A – no retractor is at this position	
<input type="checkbox"/>		N/A – the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: Full Aft (S7.1.1.5(c)(1)) (Any position is acceptable)	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	4.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	5.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	6.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
		<input checked="" type="checkbox"/> Yes, go to 7.1	
		<input type="checkbox"/> No, go to 8	
<input checked="" type="checkbox"/>	7.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	8.	Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))	

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 75.5 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 8.0 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 34.75 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 35 lb/sec
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 35.25 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒  $13 - 12 = 0.5$  inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 9 from the measurement in 13. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒  $9 - 13 = 40.25$  inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 9/30/04




Figure 5. - Webbing Tension Pull Device

## DATA SHEET 8

### LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger  
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2005 Toyota Corolla 4 Door  
Test Program: FMVSS 208 Compliance  
Test Technician: Wayne Dahlke

NHTSA No.: C55101  
Test Date: 9/30/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- |                                     |     |                                     |   |
|-------------------------------------|-----|-------------------------------------|---|
| <input type="checkbox"/>            |     |                                     | N/A – no retractor is at this position  |
| <input type="checkbox"/>            |     |                                     | N/A – the retractor is an automatic locking retractor ONLY  |
| <input checked="" type="checkbox"/> | 1.  |                                     | Record test fore-aft seat position: Not Adjustable (S7.1.1.5(c)(1)) (Any position is acceptable)  |
| <input checked="" type="checkbox"/> | 2.  |                                     | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))       |
|                                     |     | <input checked="" type="checkbox"/> | Yes – Pass  |
|                                     |     | <input type="checkbox"/>            | No – Fail   |
| <input checked="" type="checkbox"/> | 3.  |                                     | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))  |
|                                     |     | <input checked="" type="checkbox"/> | Yes – Pass  |
|                                     |     | <input type="checkbox"/>            | No – Fail   |
| <input checked="" type="checkbox"/> | 4.  |                                     | Buckle the seat belt. (S7.1.1.5(c)(1))  |
| <input checked="" type="checkbox"/> | 5.  |                                     | Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))  |
| <input checked="" type="checkbox"/> | 6.  |                                     | Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))  |
| <input checked="" type="checkbox"/> | 7.  |                                     | Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?  |
|                                     |     | <input checked="" type="checkbox"/> | Yes, go to 7.1  |
|                                     |     | <input type="checkbox"/>            | No, go to 8   |
| <input checked="" type="checkbox"/> | 7.1 |                                     | Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))    |
|                                     |     | <input checked="" type="checkbox"/> | Yes – Pass  |
|                                     |     | <input type="checkbox"/>            | No – Fail   |
| <input checked="" type="checkbox"/> | 8.  |                                     | Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1)) |

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 63.75 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 6.9 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 25.0 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 35 lb/sec
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 25.75 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒ 13 - 12 = 0.75 inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 9 from the measurement in 13. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒ 9 - 13 = 38.0 inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 9/30/04




Figure 5. - Webbing Tension Pull Device

## DATA SHEET 8

### LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger  
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2005 Toyota Corolla 4 Door NHTSA No.: C55101  
 Test Program: FMVSS 208 Compliance Test Date: 9/30/04  
 Test Technician: Wayne Dahlke Comple

te one of these forms for **each**

designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- |   |     |   |  |
|---|-----|---|--|
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; margin: 0 auto;"></div>                         |     | N/A – no retractor is at this position  |  |
|   |     | N/A – the retractor is an automatic locking retractor ONLY  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 1.  | Record test fore-aft seat position: Not Adjustable (S7.1.1.5(c)(1)) (Any position is acceptable)  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 2.  | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))       |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> Yes – Pass  |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;"></div> No – Fail  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 3.  | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))  |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> Yes – Pass  |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;"></div> No – Fail  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 4.  | Buckle the seat belt. (S7.1.1.5(c)(1))  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 5.  | Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 6.  | Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 7.  | Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?  |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> Yes, go to 7.1  |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;"></div> No, go to 8  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 7.1 | Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))    |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> Yes – Pass  |  |
|   |     | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;"></div> No – Fail  |  |
| <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 20px; line-height: 20px; text-align: center;">X</div> | 8.  | Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1)) |  |

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 63.0 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 8.7 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 22.5 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 35 lb/sec
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 23.5 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒ 13 - 12 = 1.0 inch
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 9 from the measurement in 13. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒ 9 - 13 = 39.5 inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 9/30/04




Figure 5. - Webbing Tension Pull Device



## DATA SHEET 8

### LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger  
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2005 Toyota Corolla 4 Door  
Test Program: FMVSS 208 Compliance  
Test Technician: Wayne Dahlke

NHTSA No.: C55101  
Test Date: 9/30/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

<input type="checkbox"/>		N/A – no retractor is at this position	
<input type="checkbox"/>		N/A – the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: Not Adjustable (S7.1.1.5(c)(1)) (Any position is acceptable)	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does <b>NOT</b> require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	4.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	5.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	6.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
		<input checked="" type="checkbox"/> Yes, go to 7.1	
		<input type="checkbox"/> No, go to 8	
<input checked="" type="checkbox"/>	7.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	8.	Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))	

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 61.5 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 5.8 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 20.5 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 35 lb/sec
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 22.5 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒  $13 - 12 = 2.0$  inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 9 from the measurement in 13. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒  $9 - 13 = 39.0$  inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 9/30/04




Figure 5. - Webbing Tension Pull Device

## DATA SHEET 9

### FMVSS 208 SEAT BELT WARNING SYSTEM CHECK (S7.3)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

- |          |     |   |
|----------|-----|---|
| <b>X</b> | 1.  | The occupant is in the driver's seat.   |
| <b>X</b> | 2.  | The seat belt is in the stowed position.  |
| <b>X</b> | 3.  | The key is in the "on" or "start" position.   |
| <b>X</b> | 4.  | The time duration of the audible signal beginning with key "on" or "start" is                       |
| <b>X</b> |     | Seconds: 6.0  |
| <b>X</b> | 5.  | The occupant is in the driver's seat.   |
| <b>X</b> | 6.  | The seat belt is in the stowed position.  |
| <b>X</b> | 7.  | The key is in the "on" or "start" position.   |
| <b>X</b> | 8.  | The time duration of the warning light beginning with key "on" or "start" is                        |
| <b>X</b> |     | Seconds: Stays On   |
| <b>X</b> | 9.  | The occupant is in the driver's seat.   |
| <b>X</b> | 10. | The seat belt is in the latched position and with at least 4 inches of belt webbing extended.       |
| <b>X</b> | 11. | The key is in the "on" or "start" position.   |
| <b>X</b> | 12. | The time duration of the audible signal beginning with key "on" or "start" is                       |
| <b>X</b> |     | Seconds: 0.0  |
| <b>X</b> | 13. | The occupant is in the driver's seat.   |
| <b>X</b> | 14. | The seat belt is in the latched position and with at least 4 inches of belt webbing extended.       |
| <b>X</b> | 15. | The key is in the "on" or "start" position.   |
| <b>X</b> | 16. | The time duration of the warning light beginning with key "on" or "start" is                        |
| <b>X</b> |     | Seconds: 0.0  |
| <b>X</b> | 17. | Complete the following table with the data from 4, 8, 12, and 16 to determine which option is used. |

		Warning light	Warning light specification	Audible signal	Audible signal specification*
S7.3 (a)(1)	Belt latched & key on or start	Item 16: 0.0		Item 12: 0.0	0 seconds**
	Belt stowed & key on or start	Item 8: Stays On	60 seconds minimum	Item 4: 6.0	4 to 8 seconds
S7.3 (a)(2)	Belt latched & key on or start	Item 16: 0.0	4 to 8 seconds	Item 12: 0.0	0 seconds**
	Belt stowed & key on or start	Item 8: Stays On	4 to 8 seconds	Item 4: 6.0	4 to 8 seconds

\* 49 USCS @ 30124 does NOT allow an audible signal to operate for more than 8 seconds.

\*\* 0 seconds means the light or audible signal are NOT permitted to operate under these conditions.  
 See 7/12/00 interpretation to Patrick Raheer of Hogan and Hartson

- ☒ 18. The seat belt warning system meets the requirements of (manufacturers may comply with either section)
- |                                     |  |
|-------------------------------------|--|
| <input checked="" type="checkbox"/> | S7.3 (a)(1)  |
| <input type="checkbox"/>            | S7.3 (a)(2)  |
| <input type="checkbox"/>            | FAIL – does not meet the requirements of either option |
- ☒ 19. Note wording of visual warning: (S7.3(a)(1) and S7.3(a)(2))
- |                                     |   |
|-------------------------------------|---|
| <input type="checkbox"/>            | Fasten seat belts                                       |
| <input type="checkbox"/>            | Fasten belts  |
| <input checked="" type="checkbox"/> | Symbol 101  |
| <input type="checkbox"/>            | FAIL – does not used any of the above working or symbol |

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 9/30/04

## DATA SHEET 10

### BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- |          |     |  |          |  |
|----------|-----|--|----------|--|
| <b>X</b> | 1.  | Does the vehicle incorporate a webbing tension-relieving device?   | <b>X</b> | Yes, this form is complete                           |
|          |     |  | <b>X</b> | No, continue with this check sheet                   |
| <b>X</b> | 2.  | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)  | <b>X</b> | N/A, no lumbar adjustment                            |
| <b>X</b> | 3.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  | <b>X</b> | N/A, no additional support adjustment                |
| <b>X</b> | 4.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  | <b>X</b> | N/A, no independent fore-aft seat cushion adjustment |
| <b>X</b> | 5.  | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)  | <b>X</b> | N/A, no independent seat cushion height adjustment   |
| <b>X</b> | 6.  | Put the seat in its full rearward position. (S16.2.10.3.1)   | <b>X</b> | N/A, the seat does not have a fore-aft adjustment    |
| <b>X</b> | 7.  | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)   | <b>X</b> | N/A, no seat height adjustment                       |
| <b>X</b> | 8.  | Draw a horizontal reference line on the side of the seat cushion.  |          |  |
| <b>X</b> | 9.  | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |          |  |
| <b>X</b> | 10. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position for this test. (S8.1.2)   | <b>X</b> | N/A, the seat does not have a fore-aft adjustment    |
|          |     |  | <b>X</b> | Mid position   |
|          |     | If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat: Not adjustable  |          |  |

- ☒ 11. If seat adjustments other than fore-aft are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2.1)
- ☒ N/A, no adjustments  
Reference line angle as tested:
- ☒ 12. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
- ☒ N/A, no seat back angle adjustment  
Manufacturer's design seat back angle:  
Tested seat back angle:
- ☒ 13. Position the test dummies according to dummy position placement instructions in Appendix F.
- ☒ 14. Fasten the seat belt latch.
- ☒ 15. Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
- ☒ 16. Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
- ☒ Contact Force (lb): 0.16
- ☒ 0.0 to 0.7 pounds – Pass
- ☐ Greater than 0.7 pounds - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 9/30/04

# DATA SHEET 10

## BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- |          |     |  |
|----------|-----|--|
| <b>X</b> | 1.  | Does the vehicle incorporate a webbing tension-relieving device?   |
|          |     | <input type="checkbox"/> Yes, this form is complete  |
|          |     | <b>X</b> No, continue with this check sheet  |
| <b>X</b> | 2.  | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)  |
|          |     | <b>X</b> N/A, no lumbar adjustment   |
| <b>X</b> | 3.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  |
|          |     | <b>X</b> N/A, no additional support adjustment   |
| <b>X</b> | 4.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  |
|          |     | <b>X</b> N/A, no independent fore-aft seat cushion adjustment  |
| <b>X</b> | 5.  | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)  |
|          |     | <b>X</b> N/A, no independent seat cushion height adjustment  |
| <b>X</b> | 6.  | Put the seat in its full rearward position. (S16.2.10.3.1)   |
|          |     | <b>X</b> N/A, the seat does not have a fore-aft adjustment   |
| <b>X</b> | 7.  | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)   |
|          |     | <b>X</b> N/A, no seat height adjustment  |
| <b>X</b> | 8.  | Draw a horizontal reference line on the side of the seat cushion.  |
| <b>X</b> | 9.  | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
|          |     | <b>X</b> N/A, the seat does not have a fore-aft adjustment   |
| <b>X</b> | 10. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position for this test. (S8.1.2)   |
|          |     | <input type="checkbox"/> Mid position  |
|          |     | If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat: Not adjustable  |

- ☒ 11. If seat adjustments other than fore-aft are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2.1)
- ☒ N/A, no adjustments  
Reference line angle as tested:
- ☒ 12. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
- ☒ N/A, no seat back angle adjustment  
Manufacturer's design seat back angle:  
Tested seat back angle:
- ☒ 13. Position the test dummies according to dummy position placement instructions in Appendix F.
- ☒ 14. Fasten the seat belt latch.
- ☒ 15. Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
- ☒ 16. Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
- ☒ Contact Force (lb): 0.20
- ☒ 0.0 to 0.7 pounds – Pass
- ☐ Greater than 0.7 pounds - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 9/30/04



# DATA SHEET 10

## BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

- |          |     |  |
|----------|-----|--|
| <b>X</b> | 1.  | Does the vehicle incorporate a webbing tension-relieving device?   |
|          |     | <input type="checkbox"/> Yes, this form is complete  |
|          |     | <b>X</b> No, continue with this check sheet  |
| <b>X</b> | 2.  | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)  |
|          |     | <b>X</b> N/A, no lumbar adjustment   |
| <b>X</b> | 3.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  |
|          |     | <b>X</b> N/A, no additional support adjustment   |
| <b>X</b> | 4.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  |
|          |     | <b>X</b> N/A, no independent fore-aft seat cushion adjustment  |
| <b>X</b> | 5.  | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)  |
|          |     | <b>X</b> N/A, no independent seat cushion height adjustment  |
| <b>X</b> | 6.  | Put the seat in its full rearward position. (S16.2.10.3.1)   |
|          |     | <b>X</b> N/A, the seat does not have a fore-aft adjustment   |
| <b>X</b> | 7.  | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)   |
|          |     | <b>X</b> N/A, no seat height adjustment  |
| <b>X</b> | 8.  | Draw a horizontal reference line on the side of the seat cushion.  |
| <b>X</b> | 9.  | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
|          |     | <b>X</b> N/A, the seat does not have a fore-aft adjustment   |
| <b>X</b> | 10. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position for this test. (S8.1.2)   |
|          |     | <input type="checkbox"/> Mid position  |
|          |     | If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat: Not adjustable  |

- ☒ 11. If seat adjustments other than fore-aft are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2.1)
- ☒ N/A, no adjustments  
Reference line angle as tested:
- ☒ 12. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
- ☒ N/A, no seat back angle adjustment  
Manufacturer's design seat back angle:  
Tested seat back angle:
- ☒ 13. Position the test dummies according to dummy position placement instructions in Appendix F.
- ☒ 14. Fasten the seat belt latch.
- ☒ 15. Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
- ☒ 16. Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
- ☒ Contact Force (lb): 0.14
- ☒ 0.0 to 0.7 pounds – Pass
- ☐ Greater than 0.7 pounds - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 9/30/04

# DATA SHEET 11

## LATCH PLATE ACCESS (S7.4.4)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke


NHTSA No.: C55101  
 Test Date: 9/30/04

Test all front outboard seat belts **other than those in** walk-in van-type vehicles and those at front outboard designated seating positions in **passenger cars**. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
------------------------------	---

- |  |     |  |
|--|-----|--|
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 1.  | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (8.1.3)   |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, no lumbar adjustment  |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 2.  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)  |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, no additional support adjustment  |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 3.  | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)  |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, no independent fore-aft seat cushion adjustment   |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 4.  | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)   |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, no independent seat cushion height adjustment   |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 5.  | Put the seat in its full rearward position. (S16.2.10.3.1)   |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, the seat does not have a fore-aft adjustment  |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 6.  | If the seat height is adjustable, put it in the full down position. (S16.2.10.3.1)   |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, no seat height adjustment   |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 7.  | Draw a horizontal reference line on the side of the seat cushion   |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 8.  | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, the seat does not have a fore-aft adjustment.   |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 9.  | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the forward most fore-aft position for this test. (S10.7)  |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> | 10. | If seat adjustments, other than fore-aft, are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal.  |
|  |     | <div style="background-color: yellow; width: 20px; height: 20px; display: inline-block; vertical-align: middle;"></div> N/A, no adjustments  |
| <div style="background-color: yellow; width: 20px; height: 20px; margin: 0 auto;"></div> |     | Reference line angle as tested: Zero   |

- ☐ 11. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
- ☐ N/A, no seat back angle adjustment
- ☐ Manufacturer's design seat back angle:
- ☐ Tested seat back angle:
- ☐ 12. Position the test dummy using the procedures in Appendix A. (Some modifications to the positioning procedure may need to be made because the seat is in its forward most position. Note on the Appendix A positioning check sheet any deviations necessary to position the Part 572, Subpart E dummy.) Include the positioning check sheet with this form.
- ☐ 13. Position the adjustable seat belt anchorage in the manufacturer's nominal design position for a 50<sup>th</sup> percentile adult male occupant.
- ☐ 14. Attach the inboard reach string to the base of the head following the instructions on Figure 3.
- ☐ 15. Attach the outboard reach string to the torso sheath following the instructions on Figure 3.
- ☐ 16. Place the latch plate in the stowed position.
- ☐ 17. Extend inboard reach string in front of the dummy and then backward and outboard to the latch plate to generate an arc of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope?
- ☐ Yes – Pass
- ☐ No
- ☐ 18. Extend outboard reach string in front of the dummy and then backward and outboard to the latch plate to generate an arc of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope?
- ☐ Yes – Pass
- ☐ No
- ☐ 19. Is the latch plate within the inboard (item 17) or outboard (item 18) reach envelope?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 20. Using the clearance test block, specified in Figure 4, is there sufficient clearance between the vehicle seat and the side of vehicle interior to allow the test block to move unhindered to the latch plate or buckle?
- ☐ Yes – Pass
- ☐ No – Fail



**Figure 3. Location of Anchoring Points for Latchplate Reach Limiting Chains or Strings to Test for Latchplate Accessibility Using Subpart E Test Device**




Figure 4—USE OF CLEARANCE TEST BLOCK TO DETERMINE HAND/ARM ACCESS

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zahl

Date: 9/30/04

## DATA SHEET 12

### SEAT BELT RETRACTION (S7.4.5)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test all front outboard seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
GVWR:	

- ☒ 1. Is the vehicle a passenger car or walk-in van-type vehicle?
  - ☒ Yes, this form is complete
  - ☐ No
- ☐ 2. Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
  - ☐ N/A, no lumbar adjustment
- ☐ 3. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
  - ☐ N/A, no additional support adjustment
- ☐ 4. If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)
  - ☐ N/A, no independent fore-aft seat cushion adjustment
- ☐ 5. If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)
  - ☐ N/A, no independent seat cushion height adjustment
- ☐ 6. Put the seat in its full rearward position.
  - ☐ N/A, the seat does not have a fore-aft adjustment
- ☐ 7. If the seat height is adjustable, put it in the full down position. (S8.1.2)
  - ☐ N/A, no seat adjustment
- ☐ 8. Draw a horizontal line on the side of the seat cushion.
- ☐ 9. Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward.
  - ☐ N/A, the seat does not have a fore-aft adjustment.
- ☐ 10. Using only the controls that change the seat in the fore-aft direction, place the seat in the middle fore-aft position. (S8.1.2)
  - ☐ If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat:

- ☐ 11. If seat adjustments, other than fore-aft, are present and the reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2)
- ☐ N/A – no seat adjustment
- ☐ Reference angle as tested:
- ☐ 12. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S8.1.3)
- ☐ N/A – no seat back angle adjustment
- ☐ Manufacturer's design seat back angle:
- ☐ Tested seat back angle:
- ☐ 13. If adjustable, set the head restraint at the full up and full forward position. (S8.1.3) Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible.
- ☐ N/A – no head restraint adjustment
- ☐ 14. Place any adjustable seat belt anchorages at the vehicle manufacturer's nominal design position for a 50th percentile adult male occupant (S8.1.3)
- ☐ N/A – no adjustable upper seat belt anchorage
- ☐ Manufacturer's specified anchorage position:
- ☐ Tested anchorage position:
- ☐ 15. Is the driver seat a bucket seat?
- ☐ Yes, go to 15.1 and skip 15.2.
- ☐ No, go to 15.2 and skip 15.1
- ☐ 15.1 Bucket seats - Locate and mark a vertical Plane B through the longitudinal centerline of the seat. The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle.
- ☐ Record the width of the seat:
- ☐ Record the distance from the edge of the seat to Plane B.
- ☐ 15.2 Bench seats (including split bench seats):
- ☐ Driver seat: Locate and mark a vertical Plane B through the center of the steering wheel parallel to the vehicle longitudinal centerline.
- ☐ Passenger seat: Locate and mark a vertical longitudinal Plane B on the seat that is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel.
- ☐ Distance from the vehicle centerline to the center of the steering wheel:
- ☐ Distance from the vehicle centerline to Plane B:
- ☐ 16. Stow outboard armrests that are capable of being stowed. (S7.4.5)
- ☐ 17. Remove the arms of a Subpart E dummy and place it in the seat such that the midsagittal plane is coincident with Plane B and the upper torso rests against the seat back. (S10.4.1.1 & S10.4.1.2)
- ☐ 18. Rest the thighs on the seat cushion



- ☐ 19. Position the H-point of the dummy within 0.5 inch of the vertical dimension and 0.5 inch of the horizontal dimension of a point 0.25 inch below the H-point determined by using the equipment and procedures specified in SAE J826 (APR 1980). (S10.4.2.1) Then measure the pelvic angle with respect to the horizontal using the pelvic angle gage. Adjust the dummy position until these three measurements are within the specifications. (S10.4.2.1 and S10.4.2.2)
- ☐ Horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)
  - ☐ Vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)
  - ☐ Pelvic angle (20° to 25°)
  - ☐ Vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)
  - ☐ Pelvic angle (20° to 25°) (S10.4.2.2)
- ☐ 20. Set the distance between the outboard knee clevis flange surfaces at 10.6 inches. Measured distance (10.6 inches) (S10.5):
- ☐ 21. To the extent practicable keep the thighs and the legs in a vertical plane (S10.5) and rest the thighs on the seat cushion while resting the feet on the floorpan or toe board.
- ☐ 22. Fasten the seat belt around the dummy.
- ☐ 23. Remove all slack from the lap belt portion. (S10.9)
- ☐ 24. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this four times. (S10.9)
- ☐ 25. Apply a 2 to 4 pound tension load to the lap belt. (S10.9)  
Pound load applied:
- ☐ 26. Is the belt system equipped with a tension relieving device?
- ☐ \_\_ Yes, continue
  - ☐ \_\_ No, go to 27
- ☐ 26.1 Introduce the maximum amount of slack into the upper torso bet that is recommended by the vehicle manufacturer in the vehicle owner's manual. (S10.9). Go to 25.
- ☐ 27. Check the statement that applies to this test vehicle:
- ☐ 27.1 Check the statement that applies to this test vehicle:  
The torso and lap belt webbing of the seat belt system automatically retracts to a stowed position when the adjacent vehicle door is in an open position and the seat belt latch plate is released.
- ☐ Pass
- ☐ 27.2 The torso and lap belt webbing of the seat belt system automatically retracts when the seat belt latch plate is released.
- ☐ Pass
- ☐ 27.3 Neither A or B apply
- ☐ Fail
- ☐ 28. With the webbing and hardware in the stowed position are the webbing and hardware prevented from being pinched when the door is closed?
- ☐ Yes – Pass
  - ☐ No – Fail

☐ 29. If this test vehicle has an open body (without doors) and has a belt system with a tension-relieving device, does the belt system fully retract when the tension-relieving device is deactivated?

- ☐ N/A  
☐ Yes – Pass  
☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 9/30/04

## DATA SHEET 13

### SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- |          |    |  |
|----------|----|--|
| <b>X</b> | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b))<br><div style="margin-left: 20px;"> <input type="checkbox"/> Yes, this form is complete<br/> <input checked="" type="checkbox"/> No, go to 2                 </div>   |
| <b>X</b> | 2. | Is the seat removable? (S7.4.6.1(b))<br><div style="margin-left: 20px;"> <input type="checkbox"/> Yes, this form is complete<br/> <input checked="" type="checkbox"/> No, go to 3                 </div>   |
| <b>X</b> | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b))<br><div style="margin-left: 20px;"> <input type="checkbox"/> Yes, this form is complete<br/> <input checked="" type="checkbox"/> No, go to 4                 </div>  |
| <b>X</b> | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a))<br><div style="margin-left: 20px;"> <input checked="" type="checkbox"/> Yes, go to 5<br/> <input type="checkbox"/> No, this form is complete                 </div>  |
| <b>X</b> | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a))<br><div style="margin-left: 20px;"> <input checked="" type="checkbox"/> Yes – Pass<br/> <input type="checkbox"/> No – Fail<br/>                     Identify the part(s) on top or above the seat.<br/> <div style="margin-left: 20px;"> <input checked="" type="checkbox"/> Seat belt latch plate<br/> <input checked="" type="checkbox"/> Buckle<br/> <input checked="" type="checkbox"/> Seat belt webbing                     </div> </div> |
| <b>X</b> | 6. | Are the remaining two seat belt parts accessible under normal conditions?<br><div style="margin-left: 20px;"> <input checked="" type="checkbox"/> Yes – Pass<br/> <input type="checkbox"/> No – Fail                 </div>  |
| <b>X</b> | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2)<br><div style="margin-left: 20px;"> <input checked="" type="checkbox"/> Yes – Pass<br/> <input type="checkbox"/> No – Fail                 </div>   |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes – Pass  
☐ No – Fail  
☒ N/A – Rear seat

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 9/30/04

## DATA SHEET 13

### SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- |          |    |  |
|----------|----|--|
| <b>X</b> | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b))   |
|          |    | <input type="checkbox"/> Yes, this form is complete  |
|          |    | <input checked="" type="checkbox"/> No, go to 2  |
| <b>X</b> | 2. | Is the seat removable? (S7.4.6.1(b))   |
|          |    | <input type="checkbox"/> Yes, this form is complete  |
|          |    | <input checked="" type="checkbox"/> No, go to 3  |
| <b>X</b> | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b))  |
|          |    | <input type="checkbox"/> Yes, this form is complete  |
|          |    | <input checked="" type="checkbox"/> No, go to 4  |
| <b>X</b> | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a))  |
|          |    | <input checked="" type="checkbox"/> Yes, go to 5   |
|          |    | <input type="checkbox"/> No, this form is complete   |
| <b>X</b> | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) |
|          |    | <input checked="" type="checkbox"/> Yes – Pass   |
|          |    | <input type="checkbox"/> No – Fail   |
|          |    | Identify the part(s) on top or above the seat.   |
|          |    | <input checked="" type="checkbox"/> Seat belt latch plate  |
|          |    | <input checked="" type="checkbox"/> Buckle   |
|          |    | <input checked="" type="checkbox"/> Seat belt webbing  |
| <b>X</b> | 6. | Are the remaining two seat belt parts accessible under normal conditions?  |
|          |    | <input checked="" type="checkbox"/> Yes – Pass   |
|          |    | <input type="checkbox"/> No – Fail   |
| <b>X</b> | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2)   |
|          |    | <input checked="" type="checkbox"/> Yes – Pass   |
|          |    | <input type="checkbox"/> No – Fail   |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes – Pass  
☐ No – Fail  
☒ N/A – Rear seat

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Z. Ahl

Date: 9/30/04

## DATA SHEET 13

### SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2005 Toyota Corolla 4 Door  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 9/30/04

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

- |          |    |  |
|----------|----|--|
| <b>X</b> | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b))   |
|          |    | <input type="checkbox"/> Yes, this form is complete  |
|          |    | <input checked="" type="checkbox"/> No, go to 2  |
| <b>X</b> | 2. | Is the seat removable? (S7.4.6.1(b))   |
|          |    | <input type="checkbox"/> Yes, this form is complete  |
|          |    | <input checked="" type="checkbox"/> No, go to 3  |
| <b>X</b> | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b))  |
|          |    | <input type="checkbox"/> Yes, this form is complete  |
|          |    | <input checked="" type="checkbox"/> No, go to 4  |
| <b>X</b> | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a))  |
|          |    | <input checked="" type="checkbox"/> Yes, go to 5   |
|          |    | <input type="checkbox"/> No, this form is complete   |
| <b>X</b> | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) |
|          |    | <input checked="" type="checkbox"/> Yes – Pass   |
|          |    | <input type="checkbox"/> No – Fail   |
|          |    | Identify the part(s) on top or above the seat.   |
|          |    | <input checked="" type="checkbox"/> Seat belt latch plate  |
|          |    | <input checked="" type="checkbox"/> Buckle   |
|          |    | <input checked="" type="checkbox"/> Seat belt webbing  |
| <b>X</b> | 6. | Are the remaining two seat belt parts accessible under normal conditions?  |
|          |    | <input checked="" type="checkbox"/> Yes – Pass   |
|          |    | <input type="checkbox"/> No – Fail   |
| <b>X</b> | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2)   |
|          |    | <input checked="" type="checkbox"/> Yes – Pass   |
|          |    | <input type="checkbox"/> No – Fail   |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes – Pass  
☐ No – Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes – Pass  
☐ No – Fail  
☒ N/A – Rear seat

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Z. Ahl

Date: 9/30/04



## DATA SHEET 14

### MARKING OF REFERENCE POINTS FOR VARIOUS TEST POSITIONS AND POINTS

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Eric Peschman

NHTSA No.: C55101  
 Test Date: 3/23/05

1. Driver Designated Seating Position:

- |                                     |      |  |
|-------------------------------------|------|--|
| <input checked="" type="checkbox"/> | 1.1  | Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1)   |
|                                     |      | <input checked="" type="checkbox"/> N/A – No lumbar adjustment   |
| <input checked="" type="checkbox"/> | 1.2  | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position (S16.2.10.2)   |
|                                     |      | <input checked="" type="checkbox"/> N/A – No additional support adjustment   |
| <input checked="" type="checkbox"/> | 1.3  | Mark a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion.   |
| <input checked="" type="checkbox"/> | 1.4  | Draw a line (seat cushion reference line) through the seat cushion reference point.  |
| <input checked="" type="checkbox"/> | 1.5  | Using only the controls that primarily move the seat in the fore-aft direction, move the seat cushion reference point to the rearmost position.  |
| <input checked="" type="checkbox"/> | 1.6  | If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position (S16.2.10.3)  |
|                                     |      | <input checked="" type="checkbox"/> N/A – No independent fore-aft seat cushion adjustment  |
| <input checked="" type="checkbox"/> | 1.7  | Using any part of any control, other than the parts just used for fore-aft positioning, determine the range of angles of the seat cushion reference line and set the seat cushion reference line at the mid-angle.   |
| <input checked="" type="checkbox"/> |      | Maximum Angle: 1.8° Nose Up  |
| <input checked="" type="checkbox"/> |      | Minimum Angle: 4.8° Nose Down  |
| <input checked="" type="checkbox"/> |      | Mid-angle: 1.5° Nose Down  |
| <input checked="" type="checkbox"/> | 1.8  | If the seat and/or seat cushion height is adjustable, use any part of any control other than those which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.7.  |
|                                     |      | <input type="checkbox"/> N/A – No seat height adjustment   |
| <input checked="" type="checkbox"/> | 1.9  | Using only the controls that primarily move the seat in the fore-aft direction, verify the seat is in the rearmost position.   |
| <input checked="" type="checkbox"/> | 1.10 | Using only the controls that primarily move the seat in the fore-aft direction, mark for future reference the fore-aft seat positions. Mark each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and mark each detent. For power seats, mark only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost. |
| <input checked="" type="checkbox"/> | 1.11 | Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.   |
| <input checked="" type="checkbox"/> | 1.12 | Using any controls, other than the controls that primarily move the seat and/or seat cushion in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.7.   |

- ☒ 1.13 Using only the controls that primarily move the seat and/or seat cushion in the fore-aft direction, place the seat in the mid-fore-aft position.
- ☒ 1.14 Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.7.
- ☒ 1.15 Using only the controls that change the seat in the fore-aft direction, place the seat in the foremost position.
- ☒ 1.16 Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.7.
- ☒ 1.17 Visually mark for future reference the seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50<sup>th</sup> percentile adult male in the manner specified by the manufacturer.
- ☐ N/A – No seat back angle adjustment
- ☒ Manufacturer's design seat back angle: 88.3 degrees on Head Rest Post
- ☒ 1.18 Is the seat a bucket seat?
- ☒ Yes, go to 1.18.1 and skip 1.18.2
- ☐ No, go to 1.18.2 and skip 1.18.1
- 1.18.1 Bucket seats:
- ☒ Locate and mark for future reference the longitudinal centerline of the seat cushion. The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle. (S16.3.1.10)
- ☒ Record the width of the seat cushion: Used SRP Provided By Manufacturer
- ☒ One half the width of the seat cushion is: Used SRP Provided By Manufacturer
- ☒ Record the distance from the edge of the seat cushion to the seat mark: 260 mm
- 1.18.2 Bench seats:
- ☐ Locate and mark for future reference the longitudinal line on the seat cushion that marks the longitudinal vertical plane through the centerline of the steering wheel.
2. Passenger Designated Seating Position
- ☒ 2.1 Is the seat adjustable independent of the driver seating position?
- ☒ Yes, go to 2.2
- ☐ No, go to 2.18
- ☒ 2.2 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions (S16.2.10.1, S20.1.9.1, S22.1.7.1)
- ☒ N/A – No lumbar adjustment
- ☒ 2.3 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S22.1.7.2)
- ☒ N/A – No additional support adjustment
- ☒ 2.4 Mark a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion.
- ☒ 2.5 Draw a line (seat cushion reference line) through the seat cushion reference point.
- ☒ 2.6 Using only the controls that primarily move the seat in the fore-aft direction, move the seat cushion reference point to the rearmost position.

<b>X</b>	2.7	If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position (S16.2.10.3, S20.1.9.3, S22.1.7.3)
<b>X</b>		N/A – No independent fore-aft seat cushion adjustment.
<b>X</b>	2.8	Using any part of the control, other than the parts just used for fore-aft positioning, determine the range of angles of the seat cushion reference line and set the seat cushion reference line at the mid-angle.
<b>X</b>		Maximum Angle: Not Adjustable
<b>X</b>		Minimum Angle: Not Adjustable
<b>X</b>		Mid-angle: Not Adjustable
<b>X</b>	2.9	If the seat and/or seat cushion height is adjustable, use any part of any control other than those which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-range angle.
<b>X</b>		N/A – No seat height adjustment
<b>X</b>	2.10	Using only the controls that primarily move the seat and/or seat cushion in the fore-aft direction, verify the seat is in the rearmost position.
<b>X</b>	2.11	Using only the controls that primarily move the seat in the fore-aft direction, mark for future reference the fore-aft seat positions. Mark each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and mark each detent. For power seats, mark only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
<b>X</b>	2.12	Using only the controls that primarily move the seat in the fore-aft direction, place the seat in the rearmost position.
<b>X</b>	2.13	Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 2.8.
<b>X</b>		N/A – No seat height adjustment Go to 2.18
	2.14	Using only the controls that primarily move the seat in the fore-aft direction, place the seat in the mid-fore-aft position.
	2.15	Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 2.8.
	2.16	Using only the controls that change the seat in the fore-aft direction, place the seat in the foremost position.
	2.17	Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 2.8.

<input checked="" type="checkbox"/>	2.18	Visually mark for future reference the seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50 <sup>th</sup> percentile adult male in the manner specified by the manufacturer.
		<input type="checkbox"/> N/A – No seat back angle adjustment
		<input type="checkbox"/> N/A – The seat back angle adjustment is controlled by the setting of the driver seat back angle.
<input checked="" type="checkbox"/>		Manufacturer's design seat back angle: 89° on Head Rest Post
<input checked="" type="checkbox"/>		Actual seat back angle: 88.7° on Head Rest Post
<input checked="" type="checkbox"/>	2.19	Is the seat a bucket seat?
		<input checked="" type="checkbox"/> Yes, go to 2.19.1 and skip 2.19.2
		<input type="checkbox"/> No, go to 2.19.2 and skip 2.19.1
		2.19.1 Bucket seats:
		<input checked="" type="checkbox"/> Locate and mark for future reference the longitudinal centerline of the seat cushion. (S20.2.1.3, S22.2.1.3) The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle. (S20.1.10)
<input checked="" type="checkbox"/>		Record the width of the seat cushion: Used SRP Provided By Manufacturer
<input checked="" type="checkbox"/>		One half the width of the seat cushion is: Used SRP Provided By Manufacturer
		<input checked="" type="checkbox"/> Record the distance from the edge of the seat cushion to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.) 260 mm
		2.19.2 Bench seats:
		<input type="checkbox"/> Locate and mark for future reference the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S20.2.1.3, S22.2.1.3)
		<input type="checkbox"/> Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel:
		<input type="checkbox"/> Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.)
<input checked="" type="checkbox"/>	3.	Head Restraints
		<input type="checkbox"/> N/A, vehicle contains automatic head restraints
		<input type="checkbox"/> N/A, there is no head restraint adjustment
<input checked="" type="checkbox"/>	3.1	Left outboard
<input checked="" type="checkbox"/>	3.1.1	Adjust the head restraint to its lowest position. (S16.3.4.2)
	3.1.2	Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. <b>Mark</b> the foremost position.
<input checked="" type="checkbox"/>	3.1.3	Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and <b>mark</b> a horizontal plane through the midpoint of this distance.
<input checked="" type="checkbox"/>		Vertical height of head restraint (mm): 180
<input checked="" type="checkbox"/>		Mid-point height (mm): 90
<input checked="" type="checkbox"/>	3.2	Right outboard
<input checked="" type="checkbox"/>	3.2.1	Adjust the head restraint to its lowest position. (S16.3.4.2)

- ☐ 3.2.2 Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. **Mark** the foremost position.
- ☒ 3.2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance.
- ☒ Vertical height of head restraint (mm): 180
- ☒ Mid-point height (mm): 90
- ☒ 4. Steering Wheel
- ☒ 4.1 Is the steering wheel adjustable up and down and/or in and out?
- ☒ Yes, go to 4.2
- ☐ No, this form is complete
- ☒ 4.2 Find and **mark** for future reference each up and down position. Label three of the positions with the following: H for highest, M for mid-position (if there is no mid-position, label the next lowest adjustment position), and L for lowest.
- ☐ N/A, steering wheel is not adjustable up and down
- ☒ 4.3 Find and **mark** for future references each in and out position. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the next rearmost adjustment position), and R for rearmost.
- ☒ N/A, steering wheel is not adjustable in and out
- ☒ 5. Driver Low Risk Deployment
- ☐ N/A, no low risk deployment tests scheduled
- ☒ 5.1 Position the steering wheel so the front wheels are in the straight-ahead position. (S26.2.1)
- ☒ 5.2 Position any adjustable parts of the steering controls to the mid-position as determined in item 3 above. If a mid-position adjustment is not achievable, position the controls to the next lowest detent position. (S26.2.1)
- ☒ 5.3 Locate the vertical plane parallel to the vehicle longitudinal centerline through the geometric center of the opening through which the driver air bag deploys into the occupant compartment. This is referred to as "Plane E". (Check determination method below.) (S26.2.6)
- ☒ Plane E determined using manufacturer's information supplied by the COTR. (Found in Appendix D on page D-39)
- ☐ Plane E determined by test lab personnel and approved by the COTR. (Include supporting documentation in the test report.)

	Ey (mm)
"Plane E" Measurement::	
Measured:	
Specified:	
Verify Measured Equals Specified +/- 6mm:	

- ☒ 5.4 Locate the horizontal plane through the highest point of the air bag module cover. This is referred to as "Plane F." (Check determination method below.) (S26.2.6)

☒ Plane F determined using manufacturer's information supplied by the COTR.  
(Found in Appendix D on page D-39)

☐ Plane F determined by test lab personnel and approved by the COTR.  
(Include supporting documentation in the test report.)

	Fz (mm)
"Plane F" Measurement::	
Measured:	
Specified:	
Verify Measured Equals Specified +/- 6mm:	

- ☒ 6. Passenger Low Risk Deployment – Planes C and D

☒ N/A, no low risk deployment tests scheduled

- ☐ 6.1 Locate the horizontal plane through the geometric center of the opening through which the right front air bag deploys into the occupant compartment. This is referred to as "Plane C." (Check location method below.) (S22.4.1.3)

☐ Plane C located using manufacturer's information supplied by the COTR.  
(Include manufacturer's information in the test report.) OR

☐ Plane C located by test lab personnel and approved by the COTR.  
(Include supporting documentation in the test report.)

	Cz (mm)
"Plane C" Measurement::	
Measured:	
Specified:	
Verify Measured Equals Specified +/- 6mm:	

- ☐ 6.2 Locate the vertical plane parallel to the vehicle longitudinal centerline through the geometric center of the opening through which the right front air bag deploys into the occupant compartment. This is referred to as "Plane D." (Check determination method below.) (S22.4.1.2)

☐ Plane D determined using manufacturer's information supplied by the COTR.  
(Include manufacturer's information in the test report.) OR

☐ Plane D determined by test lab personnel and approved by the COTR.  
(Include supporting documentation in the test report.)

	Dy (mm)
"Plane D" Measurement:	
Measured:	
Specified:	
Verify Measured Equals Specified +/- 6mm:	

- ☐ 6.3 **Mark** the intersection of Planes C and D on the instrument panel.

- ☒ 7. 5<sup>th</sup> Female Dummy  
**Mark** a point on the chin of the dummy 40 mm below the center of the mouth. (Chin Point) (S26.2.6)
- ☐ 8. 6-Year-Old Dummy  
Locate and **mark** a point on the front of the dummy's chest jacket on the midsagittal plane which is 139 mm (5.5 in)  $\pm$  3 mm ( $\pm$  0.1 in) along the surface of the skin down from the top of the skin at the neck line. Designate this point as "Point 1." (S24.4.1.1)  
☐ "Point 1" measurement (mm):
- ☐ 9. 3-Year-Old Dummy  
Locate and **mark** a point on the front of the dummy's chest jacket on the midsagittal plane which is 114 mm (4.5 in)  $\pm$  3 mm ( $\pm$  0.1 in) along the surface of the skin down from the top of the skin at the neck line. Designate this point as "Point 1." (S22.4.1.1)  
☐ "Point 1" measurement (mm +/- 3 mm):

REMARKS:

I certify that I have read and performed each instruction.

Signature: Eva Leach

Date: 3/23/05

## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section B Rear Facing CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Handle With Care 191
DATE OF MANUFACTURE:	5-26-2000

Base: \_\_On \_\_Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward	128	Suppressed	N/A
	Middle	128	Suppressed	N/A
	Rearward	133	Suppressed	N/A
Unbelted Rear Facing	Forward	N/A	Suppressed	N/A
	Middle	N/A	Suppressed	N/A
	Rearward	N/A	Suppressed	N/A
Unbelted Forward Facing	Forward 3 *	N/A	Suppressed	N/A
	Middle	N/A	Suppressed	N/A
	Rearward	N/A	Suppressed	N/A

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)



## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section B Rear Facing CRS

NHTSA No.:	C55101	TEST DATE:	1-07-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	First Choice 204
DATE OF MANUFACTURE:	6-20-2000

Base: \_\_On \_\_Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
 Tested seat back angle: 88.8° On Head Rest Post  
 Manufacturer's specified anchorage position: 2nd Down From Top  
 Tested anchorage position: 2nd Down From Top

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward 7 *	128	N/A	Suppressed
	Middle	131	N/A	Suppressed
	Rearward	131	Suppressed	N/A
Unbelted Rear Facing	Forward	N/A	N/A	Won't Fit
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	Suppressed	N/A
Unbelted Forward Facing	Forward 7 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section B Rear Facing CRS

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Infant 8457
DATE OF MANUFACTURE:	8-31-2000

Base: ☒ On ☐ Off ☐ N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
 Tested seat back angle: 88.8° On Head Rest Post  
 Manufacturer's specified anchorage position: 2nd Down From Top  
 Tested anchorage position: 2nd Down From Top

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward 5 *	133	N/A	Suppressed
	Middle	130	Suppressed	N/A
	Rearward	131	Suppressed	N/A
Unbelted Rear Facing	Forward 5 *	N/A	N/A	Suppressed
	Middle	N/A	Suppressed	N/A
	Rearward	N/A	Suppressed	N/A
Unbelted Forward Facing	Forward 6 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section B Rear Facing CRS

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Infant 8457
DATE OF MANUFACTURE:	8-31-2000

Base: ☐ On ☒ Off ☐ N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
 Tested seat back angle: 88.8° On Head Rest Post  
 Manufacturer's specified anchorage position: 2nd Down From Top  
 Tested anchorage position: 2nd Down From Top

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward 5 *	133	N/A	Suppressed
	Middle	132	Suppressed	N/A
	Rearward	127	Suppressed	N/A
Unbelted Rear Facing	Forward 7 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed
Unbelted Forward Facing	Forward 5 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section C Forward Facing Convertible CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout 161
DATE OF MANUFACTURE:	7-21-2000

Base: \_\_On \_\_Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
 Tested seat back angle: 88.8° On Head Rest Post  
 Manufacturer's specified anchorage position: 2nd Down From Top  
 Tested anchorage position: 2nd Down From Top

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing	Forward	128	Suppressed
	Middle	130	Suppressed
	Rearward	130	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	133	Suppressed
	Middle	132	Suppressed
	Rearward	128	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section C Forward Facing Convertible CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Century
CHILD RESTRAINT MODEL:	Encore 4612
DATE OF MANUFACTURE:	8-16-2000

Base: \_\_On \_\_Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
 Tested seat back angle: 88.8° On Head Rest Post  
 Manufacturer's specified anchorage position: 2nd Down From Top  
 Tested anchorage position: 2nd Down From Top

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing	Forward	133	Suppressed
	Middle	129	Suppressed
	Rearward	128	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	133	Suppressed
	Middle	127	Suppressed
	Rearward	127	Suppressed
Unbelted Rear Facing	Forward 1 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)  
Section C Forward Facing Convertible CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Medallion 254
DATE OF MANUFACTURE:	6-1-2000

Base: \_\_On \_\_Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 89° On Head Rest Post  
 Tested seat back angle: 88.8° On Head Rest Post  
 Manufacturer's specified anchorage position: 2nd Down From Top  
 Tested anchorage position: 2nd Down From Top

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing	Forward	130	Suppressed
	Middle	133	Suppressed
	Rearward	127	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	127	Suppressed
	Middle	127	Suppressed
	Rearward	130	Suppressed
Unbelted Rear Facing	Forward 2 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 16 SUMMARY

### Suppression Test Using Newborn Infant Dummy (Part 572, Subpart K) Section A Car Bed

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	Newborn Infant	DUMMY SERIAL NO.:	003

CAR BED NAME:	Cosco
CAR BED MODEL:	Dream Ride 02-719
DATE OF MANUFACTURE:	6-16-2000

Base: \_\_On \_\_Off X N/A-Constraint does not have a removable base  
(A car bed with a removable base shall be treated as two separate models, i.e. this form and test procedure will be completed with the base on and then repeated on a new form with the base off.

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

### Test Summary

Seat Belt	Seat Slide	Handle Down	Handle Up
Belted	Forward 3 *	Suppressed	N/A
	Middle	Suppressed	N/A
	Rearward	Suppressed	N/A

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 17 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P)  
Section D Forward Facing Belt Positioning Booster

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

BOOSTER SEAT NAME:	Century
BOOSTER SEAT MODEL:	Next Step 4920
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing Without Harness	Forward 5 *	13	Suppressed
	Middle	14	Suppressed
	Rearward	14	Suppressed
Belted Forward Facing Cinched With Harness	Forward 5 *	130	Suppressed
	Middle	131	Suppressed
	Rearward	127	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)



## DATA SHEET 17 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P)  
Section D Forward Facing Toddler Belt Positioning Booster Seat

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

BOOSTER SEAT NAME:	Cosco
BOOSTER SEAT MODEL:	High Back Booster 02-442
DATE OF MANUFACTURE:	4-28-2000

Manufacturer's design seat back angle:	<u>89° On Head Rest Post</u>
Tested seat back angle:	<u>88.8° On Head Rest Post</u>
Manufacturer's specified anchorage position:	<u>2nd Down From Top</u>
Tested anchorage position:	<u>2nd Down From Top</u>

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing Without Harness	Forward	N/A	Won't Fit
	Middle 11 *	13	Suppressed
	Rearward	15	Suppressed
Belted Forward Facing Cinched With Harness	Forward	N/A	Won't Fit
	Middle 11 *	133	Suppressed
	Rearward	129	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The CRS would not fit in this Middle Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 18 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)  
Section C Forward Facing Convertible CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout 161
DATE OF MANUFACTURE:	7-21-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	N/A	Won't Fit
	Middle 11 *	131	Suppressed
	Rearward	129	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

\* The CRS would not fit in this Middle Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

### DATA SHEET 18 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)  
Section C Forward Facing Convertible CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

CHILD RESTRAINT NAME:	Century
CHILD RESTRAINT MODEL:	Encore 4612
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

#### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	N/A	Won't Fit
	Middle	130	Suppressed
	Rearward	127	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

### DATA SHEET 18 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)  
Section C Forward Facing Convertible CRS

NHTSA No.:	C55101	TEST DATE:	1-06-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Medallion 254
DATE OF MANUFACTURE:	6-1-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

#### Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	N/A	Won't Fit
	Middle	128	Suppressed
	Rearward	130	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

## DATA SHEET 19 SUMMARY

Suppression Test Using An Unbelted 3 Year Old Dummy (Part 572, Subpart P)  
No CRS

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

### Test Summary

Position	Seat Slide	Seat Back Angle	Result
Position 1 Sitting on seat with back against seat back	Forward	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 2 Sitting on seat with back against reclined seat back	Forward	64.5	Suppressed
	Middle	64.5	Suppressed
	Rearward	64.5	Suppressed
Position 3 Sitting on seat with back not against seat back	Forward 3 *	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 4 Sitting on seat edge, spine vertical, hands at dummy's sides	Forward	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 5 Standing on seat, facing forward	Forward	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 6 Kneeling on seat, facing forward	Forward	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 7 Kneeling on seat, facing rearward	Forward	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 8 Lying on seat. (Three designated seating positions only)	Forward	N/A	N/A
	Middle	N/A	N/A
	Rearward	N/A	N/A

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

\* The ATD would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 20 SUMMARY

Suppression Test Using 6 Year Old Dummy And Booster Seats (Part 572, Subpart N)  
Section D Forward Facing Toddler Belt Positioning Booster Seat

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	6 Year Old	DUMMY SERIAL NO.:	153

BOOSTER SEAT NAME:	Century
BOOSTER SEAT MODEL:	Next Step 4920
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

### Test Summary

Seat Belt	Seat Slide	Belt Load (N)	Result
Belted	Forward	10	Suppressed
	Middle	16	Suppressed
	Rearward	14	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

## DATA SHEET 20 SUMMARY

Suppression Test Using 6 Year Old Dummy And Booster Seats (Part 572, Subpart N)  
Section D Forward Facing Toddler Belt Positioning Booster Seat

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	6 Year Old	DUMMY SERIAL NO.:	153

BOOSTER SEAT NAME:	Cosco
BOOSTER SEAT MODEL:	High Back Booster 02-442
DATE OF MANUFACTURE:	4-28-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

### Test Summary

Seat Belt	Seat Slide	Belt Load (N)	Result
Belted	Forward	17	Suppressed
	Middle	11	Suppressed
	Rearward	16	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

## DATA SHEET 20 SUMMARY

Suppression Test Using 6-Year-Old Dummy And Booster Seats (Part 572, Subpart N)  
Section D Forward Facing Toddler Belt Positioning Booster Seat

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	6 Year Old	DUMMY SERIAL NO.:	153

BOOSTER SEAT NAME:	Evenflo
BOOSTER SEAT MODEL:	Right Fit 245
DATE OF MANUFACTURE:	6-26-2000

Manufacturer's design seat back angle: 89° On Head Rest Post  
Tested seat back angle: 88.8° On Head Rest Post  
Manufacturer's specified anchorage position: 2nd Down From Top  
Tested anchorage position: 2nd Down From Top

### Test Summary

Seat Belt	Seat Slide	Belt Load (N)	Result
Belted	Forward 5 *	14	Suppressed
	Middle	18	Suppressed
	Rearward	13	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)



## DATA SHEET 21 SUMMARY

Suppression Test Using An Unbelted 6-Year-Old Dummy (Part 572, Subpart N)  
No CRS

NHTSA No.:	C55101	TEST DATE:	1-10-05
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	6 Year Old	DUMMY SERIAL NO.:	111

### Test Summary

Position	Seat Slide	Seat Back Angle	Result
Position 1 Sitting on seat with back against seat back	Forward 7 *	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 2 Sitting on seat with back against reclined seat back	Forward 7 *	64.5	Suppressed
	Middle	64.5	Suppressed
	Rearward	64.5	Suppressed
Position 3 Sitting on seat edge, spine vertical, hands at dummy's sides	Forward 6 *	88.8	Suppressed
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed
Position 4 Sitting on seat with back against seat back then leaning on the door	Forward	N/A	Won't Fit
	Middle	88.8	Suppressed
	Rearward	88.8	Suppressed

Successful Unbelted 5<sup>th</sup> percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

\* The ATD would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 17 = Full Rearward; 17 total Seat Slide detents)

## DATA SHEET 27 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5<sup>th</sup> Percentile Female  
Dummy (Part 572, Subpart O) (S26)  
Position 1 - Chin On Module (S26.2)

NHTSA No.:	C55101	TEST DATE:	1-28-05
LABORATORY:	MGA	TECHNICIANS:	BR/AH
DUMMY TYPE:	5 <sup>th</sup> Percentile Female	DUMMY SERIAL NO.:	506

Manufacturer's design seat back angle: 88.3° On Head Rest Post  
 Tested seat back angle: 88.3° On Head Rest Post  
 Tested seat position: Full Aft

Tested steering wheel angle: 26.8°  
 Thorax cavity angle: 32.5°  
 Chin Point height: 0 mm

### Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	40.0	40.3

### 5<sup>th</sup> Percentile Female SN 506 Position 1 (Chin On Module) 1-28-05

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	76
Peak Nij (Nte)	1.0	0.7
Time (ms)	NA	52.2
Peak Nij (Ntf)	1.0	0.3
Time (ms)	NA	9.8
Peak Nij (Nce)	1.0	0.4
Time (ms)	NA	165.0
Peak Nij (Ncf)	1.0	0.0
Time (ms)	NA	19.8
Neck Tension	2070 N	1607
Neck Compression	2520 N	386
Chest g	60 g	14
Chest Displacement	52 mm	8
Left Femur	6805 N	28
Right Femur	6805 N	36

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))  
 Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

## DATA SHEET 28 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5<sup>th</sup> Percentile Female  
Dummy (Part 572, Subpart O) (S26)  
Position 2 - Chin On Rim (S26.3)

NHTSA No.:	C55101	TEST DATE:	1-28-05
LABORATORY:	MGA	TECHNICIANS:	BR/AH
DUMMY TYPE:	5 <sup>th</sup> Percentile Female	DUMMY SERIAL NO.:	511

Manufacturer's design seat back angle: 88.3° On Head Rest Post  
 Tested seat back angle: 88.3° On Head Rest Post  
 Tested seat position: Full Aft

Tested steering wheel angle: 26.1°\*  
 Thorax cavity angle: 31.7°  
 Chin Point height: 4 mm Below Minus10mm Rim Target

\*The dummy contacted the windshield with the steering wheel at mid position. The steering controls were adjusted to lower the upper steering wheel rim the necessary amount to bring the Chin Point coincident with the upper steering wheel rim. The rear thorax cavity was adjusted along with the steering wheel angle.

### Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	40.0	40.5

### 5<sup>th</sup> Percentile Female SN 511 Position 2 (Chin On Rim) 1-28-05

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	58
Peak Nij (Nte)	1.0	0.6
Time (ms)	NA	52.3
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	88.0
Peak Nij (Nce)	1.0	0.0
Time (ms)	NA	9.8
Peak Nij (Ncf)	1.0	0.3
Time (ms)	NA	92.7
Neck Tension	2070 N	1062
Neck Compression	2520 N	173
Chest g	60 g	18
Chest Displacement	52 mm	13
Left Femur	6805 N	125
Right Femur	6805 N	7

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))  
 Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

### DATA SHEET 30 VEHICLE WEIGHT, FUEL TANK, AND ATTITUDE DATA

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Nick Kosinski

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	X 32 to 40 kmph	0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	5 <sup>TH</sup> female	X 50 <sup>th</sup> Male	
PASSENGER DUMMY:	5 <sup>TH</sup> female	X 50 <sup>th</sup> Male	

- |          |     |   |
|----------|-----|---|
| <b>X</b> | 1.  | Fill the transmission with transmission fluid to the satisfactory range.  |
| <b>X</b> | 2.  | Drain fuel from vehicle   |
| <b>X</b> | 3.  | Run the engine until fuel remaining in the fuel delivery system is used and the engine stops.   |
| <b>X</b> | 4.  | Record the useable fuel tank capacity supplied by the COTR  |
| <b>X</b> |     | Useable Fuel Tank Capacity supplied by COTR: 50.0 liters (13.2 gallons)   |
| <b>X</b> | 5.  | Record the fuel tank capacity supplied in the owner's manual.   |
| <b>X</b> |     | Useable Fuel Tank Capacity in owner's manual: 50.0 liters (13.2 gallons)  |
| <b>X</b> | 6.  | Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," or gasoline, fill the fuel tank. |
| <b>X</b> |     | Amount Added: 50.0 liters (13.2 gallons)  |
| <b>X</b> | 7.  | Fill the coolant system to capacity.  |
| <b>X</b> | 8.  | Fill the engine with motor oil to the Max. mark on the dip stick.   |
| <b>X</b> | 9.  | Fill the brake reservoir with brake fluid to its normal level.  |
| <b>X</b> | 10. | Fill the windshield washer reservoir to capacity.   |
| <b>X</b> | 11. | Inflate the tires to the tire pressure on the tire placard. If no tire placard is available, inflate the tires to the recommended pressure in the owner's manual.   |

Tire placard pressure:	RF:	30 psi	LF:	30 psi	RR:	30 psi	LR:	30 psi
Owner's manual pressure:	RF:	30 psi	LF:	30 psi	RR:	30 psi	LR:	30 psi
Actual inflated pressure:	RF:	30 psi	LF:	30 psi	RR:	30 psi	LR:	30 psi

- |          |     |  |
|----------|-----|--|
| <b>X</b> | 12. | Record the vehicle weight at each wheel to determine the unloaded vehicle weight (UVW), i.e. "as delivered" weight). |
|----------|-----|--|

Right Front (kg):	346.5	Right Rear (kg):	229.1
Left Front (kg):	375.6	Left Rear (kg):	217.7
Total Front (kg):	722.1	Total Rear (kg):	446.8
% Total Weight:	61.8	% Total Weight:	38.2
UVW = TOTAL FRONT PLUS TOTAL REAR (KG):		1168.9	

- |          |      |   |
|----------|------|---|
| <b>X</b> | 13.  | UVW Test Vehicle Attitude: (All dimensions in millimeters)  |
| <b>X</b> | 13.1 | Mark a point on the vehicle above the center of each wheel. |
| <b>X</b> | 13.2 | Place the vehicle on a level surface.                       |

<input checked="" type="checkbox"/>	13.3	Measure perpendicular to the level surface to the 4 points marked on the body and record the measurements																												
		<table border="1"> <tr> <td>RF:</td> <td>683</td> <td>LF:</td> <td>682</td> <td>RR:</td> <td>711</td> <td>LR:</td> <td>707</td> </tr> </table>	RF:	683	LF:	682	RR:	711	LR:	707																				
RF:	683	LF:	682	RR:	711	LR:	707																							
<input checked="" type="checkbox"/>	14.	Calculate the Rated Cargo and Luggage Weight (RCLW): 45 kg																												
<input checked="" type="checkbox"/>	14.1	Does the vehicle have the vehicle capacity weight (VCW) on the certification label or tire placard?																												
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/> Yes, go to 14.3																												
		<input type="checkbox"/> No, go to 14.2																												
	14.2	VCW = Gross Vehicle Weight – UVW																												
		VCW = _____ - _____ = _____																												
<input checked="" type="checkbox"/>	14.3	VCW = <u>385 kg (850 lbs)</u>																												
<input checked="" type="checkbox"/>	14.4	Does the certification or tire placard contain the Designated Seating Capacity (DSC)?																												
		<input checked="" type="checkbox"/> Yes, go to 14.6																												
		<input type="checkbox"/> No, go to 14.5 and skip 14.6																												
	14.5	DSC = Total number of seat belt assemblies = _____																												
<input checked="" type="checkbox"/>	14.6	DSC = <u>5</u>																												
<input checked="" type="checkbox"/>	14.7	RCLW = VCW – (68 kg x DSC) = <u>385 kg</u> - (68 kg x <u>5</u> ) = <u>45 kg</u>																												
<input checked="" type="checkbox"/>	14.8	Is the vehicle certified as a truck, MPV or bus (see the certification label on the door jamb)?																												
		<input type="checkbox"/> Yes, if the calculated RCLW is greater than 136 kg, use 136 kg as the RCLW. (S8.1.1)																												
		<input checked="" type="checkbox"/> No, use the RCLW calculated in 14.7																												
<input checked="" type="checkbox"/>	15.	Fully Loaded Weight (100% fuel fill): 1370.3 kg																												
<input checked="" type="checkbox"/>	15.1	Place the appropriate test dummy in both front outboard seating positions.																												
		Driver: <u>   </u> 5 <sup>th</sup> female <input checked="" type="checkbox"/> 50 <sup>th</sup> male Passenger: <u>   </u> 5 <sup>th</sup> female <input checked="" type="checkbox"/> 50 <sup>th</sup> male																												
<input checked="" type="checkbox"/>	15.2	Load the vehicle with the RCLW from 14.7 or 14.8 whichever is applicable.																												
<input checked="" type="checkbox"/>	15.3	Place the RCLW in the cargo area. Center the load over the longitudinal centerline of the vehicle. (S8.1.1 (d))																												
<input checked="" type="checkbox"/>	15.4	Record the vehicle weight at each wheel to determine the Fully Loaded Weight.																												
		<table border="1"> <tr> <td>Right Front (kg):</td> <td>375.6</td> <td>Right Rear (kg):</td> <td>293.9</td> </tr> <tr> <td>Left Front (kg):</td> <td>412.3</td> <td>Left Rear (kg):</td> <td>288.5</td> </tr> <tr> <td>Total Front (kg):</td> <td>787.9</td> <td>Total Rear (kg):</td> <td>582.4</td> </tr> <tr> <td>% Total Weight:</td> <td>57.5</td> <td>% Total Weight:</td> <td>42.5</td> </tr> <tr> <td>% GVW</td> <td>52.6</td> <td>% GVW</td> <td>48.0</td> </tr> <tr> <td colspan="4">(% GVW = Axle GVW divided by Vehicle GVW)</td> </tr> <tr> <td colspan="2">Fully Loaded Weight = Total Front Plus Total Rear (kg):</td> <td colspan="2">1370.3</td> </tr> </table>	Right Front (kg):	375.6	Right Rear (kg):	293.9	Left Front (kg):	412.3	Left Rear (kg):	288.5	Total Front (kg):	787.9	Total Rear (kg):	582.4	% Total Weight:	57.5	% Total Weight:	42.5	% GVW	52.6	% GVW	48.0	(% GVW = Axle GVW divided by Vehicle GVW)				Fully Loaded Weight = Total Front Plus Total Rear (kg):		1370.3	
Right Front (kg):	375.6	Right Rear (kg):	293.9																											
Left Front (kg):	412.3	Left Rear (kg):	288.5																											
Total Front (kg):	787.9	Total Rear (kg):	582.4																											
% Total Weight:	57.5	% Total Weight:	42.5																											
% GVW	52.6	% GVW	48.0																											
(% GVW = Axle GVW divided by Vehicle GVW)																														
Fully Loaded Weight = Total Front Plus Total Rear (kg):		1370.3																												
<input checked="" type="checkbox"/>	16.	Fully Loaded Test Vehicle Attitude: (All dimensions in millimeters)																												
<input checked="" type="checkbox"/>	16.1	Place the vehicle on a level surface.																												

- X** 16.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13.1 above) and record the measurements

RF:	673	LF:	668	RR:	676	LR:	675
-----	-----	-----	-----	-----	-----	-----	-----

- X** 17. Drain the fuel system

- X** 18. Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," fill the fuel tank to 92 - 94 percent of useable capacity.

**X** Fuel tank capacity x .94 = 50.0 liters (13.2 gallons) x .94 = 47.0 liters (12.4 gallons)

**X** Amount added 46.7 liters (12.3 gallons) 93.4%

- X** 19. Crank the engine to fill the fuel delivery system with Stoddard solvent

- X** 20. Calculate the test weight range.

- X** 20.1 Calculated Weight = UVW (see 12 above) + RCLW (see 14 above) + 2x(dummy weight)

$$1369.9 \text{ kg} = 1168.9 \text{ kg} + 45.0 \text{ kg} + 156.0 \text{ kg}$$

- X** 20.2 Test Weight Range = Calculated Weight (- 4.5 kg, - 9 kg.)  
 Max. Test Weight = Calculated Test Weight - 4.5 kg = 1365.4 kg  
 Min. Test Weight = Calculated Test Weight - 9 kg = 1360.9kg

- X** 21. Remove the RCLW from the cargo area.

- X** 22. Drain transmission fluid, engine coolant, motor oil, and windshield washer fluid from the test vehicle so that Stoddard solvent leakage from the fuel system will be evident.

- X** 23. Vehicle Components Removed For Weight Reduction:  
Rear seat bottom, spare tire, trunk interior, RH rear tail light

- X** 24. Secure the equipment and ballast in the load carrying area and distribute it, as nearly as possible, to obtain the proportion of axle weight indicated by the gross axle weight ratings and center it over the longitudinal centerline of the vehicle.

- X** 25. If necessary, add ballast to achieve the actual test weight.

**X** N/A

**X** Weight of Ballast: 27.2 kg in trunk

- X** 26. Ballast, including test equipment, must be contained so that it will not shift during the impact event or interfere with data collection or interfere with high-speed film recordings or affect the structural integrity of the vehicle or do anything else to affect test results. Care must be taken to assure that any attachment hardware added to the vehicle is not in the vicinity of the fuel tank or lines.

- X** 27. Record the vehicle weight at each wheel to determine the actual test weight.

Right Front (kg):	382.4	Right Rear (kg):	289.4
Left Front (kg):	410.5	Left Rear (kg):	281.2
Total Front (kg):	792.9	Total Rear (kg):	570.6
% Total Weight:	58.2	% Total Weight:	41.8
% GVW	52.6	% GVW	48.0
(% GVW = Axle GVW divided by Vehicle GVW)			
TOTAL FRONT PLUS TOTAL REAR (kg):			1363.5

<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	28.	Is the test weight between the Max. Weight and the Min. Weight (See 20.2)?								
	<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	Yes								
	<div style="border: 1px solid black; padding: 2px; text-align: center;"></div>	No, explain why not.								
<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	29.	Test Weight Vehicle Attitude: (all dimensions in millimeters)								
<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	29.1	Place the vehicle on a level surface								
<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	29.2	Measure perpendicular to the level surface to the 4 points marked on the body (see 13 above) and record the measurements								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">RF:</td> <td style="width: 25%;">677</td> <td style="width: 25%;">LF:</td> <td style="width: 25%;">670</td> <td style="width: 25%;">RR:</td> <td style="width: 25%;">678</td> <td style="width: 25%;">LR:</td> <td style="width: 25%;">678</td> </tr> </table>			RF:	677	LF:	670	RR:	678	LR:	678
RF:	677	LF:	670	RR:	678	LR:	678			
<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	30.	Summary of test attitude								
<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	30.1	AS DELIVERED:								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">RF:</td> <td style="width: 25%;">683</td> <td style="width: 25%;">LF:</td> <td style="width: 25%;">682</td> <td style="width: 25%;">RR:</td> <td style="width: 25%;">711</td> <td style="width: 25%;">LR:</td> <td style="width: 25%;">707</td> </tr> </table>			RF:	683	LF:	682	RR:	711	LR:	707
RF:	683	LF:	682	RR:	711	LR:	707			
AS TESTED:										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">RF:</td> <td style="width: 25%;">677</td> <td style="width: 25%;">LF:</td> <td style="width: 25%;">670</td> <td style="width: 25%;">RR:</td> <td style="width: 25%;">678</td> <td style="width: 25%;">LR:</td> <td style="width: 25%;">678</td> </tr> </table>			RF:	677	LF:	670	RR:	678	LR:	678
RF:	677	LF:	670	RR:	678	LR:	678			
FULLY LOADED:										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">RF:</td> <td style="width: 25%;">673</td> <td style="width: 25%;">LF:</td> <td style="width: 25%;">668</td> <td style="width: 25%;">RR:</td> <td style="width: 25%;">676</td> <td style="width: 25%;">LR:</td> <td style="width: 25%;">675</td> </tr> </table>			RF:	673	LF:	668	RR:	676	LR:	675
RF:	673	LF:	668	RR:	676	LR:	675			
<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	30.2	Is the "as tested" test attitude equal to or between the "fully loaded" and "as delivered" attitude?								
	<div style="border: 1px solid black; padding: 2px; text-align: center;"><b>X</b></div>	Yes								
	<div style="border: 1px solid black; padding: 2px; text-align: center;"></div>	No, explain why not.								

REMARKS:

I certify that I have read and performed each instruction.

Signature: *Nick Kosinski*

Date: 03/23/05

## DATA SHEET 31

### VEHICLE ACCELEROMETER LOCATION AND MEASUREMENT

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Nick Kosinski

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	X 32 to 40 kmph	0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	5 <sup>TH</sup> female	X 50 <sup>th</sup> Male	
PASSENGER DUMMY:	5 <sup>TH</sup> female	X 50 <sup>th</sup> Male	

- X

 1. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the left front outboard seating position intersects the left rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- X

 2. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the right front outboard seating position intersects the right rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- X

 3. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect at the top of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- X

 4. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect the bottom of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- X

 5. Install an accelerometer on the right front brake caliper to record x-direction accelerations. Record the location on the following chart.
- X

 6. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the top of the instrument panel. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- X

 7. Install an accelerometer on the left front brake caliper to record x-direction accelerations. Record the location on the following chart.
- X

 8. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the floor of the trunk. Install an accelerometer on the trunk floor at this intersection to record z-direction accelerations. Record the location on the following chart.

#### REMARKS:

I certify that I have read and performed each instruction.

Signature: \_\_\_\_\_



*Nick Kosinski*

Date: \_\_\_\_\_

03/23/05



## VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY



Dimensions Corresponding To The Letters "A" Through "K" (Excluding "I") Are  
Recorded In The Table On The Following Page.  
Accelerometers Corresponding To The Numbers 1 Through 8 Are Specified On The  
Preceding Page.

**DATA SHEET 31**  
**VEHICLE ACCELEROMETER LOCATION AND MEASUREMENTS**

<u>DIMENSION</u>	<u>LENGTH (mm)</u>			
<u>PRETEST VALUES</u>				
<u>A</u> (LH Rear Seat Xmbr)	354			
<u>B</u> (RH Rear Seat Xmbr)	354			
<u>C</u> (Engine Top)	3636			
<u>D</u> (Engine Bottom)	3770			
<u>E</u> (Caliper)	Right Side	3706	Left Side	3706
<u>F</u> (Left Caliper)	634			
<u>G</u> (IP)	3018			
<u>H</u> (Seat)	1836			
<u>J</u> (Right Caliper)	644			
<u>K</u> (Trunk)	960			
<u>POST TEST VALUES</u>				
<u>A</u> (LH Rear Seat Xmbr)	354			
<u>B</u> (RH Rear Seat Xmbr)	354			
<u>C</u> (Engine Top)	3558			
<u>D</u> (Engine Bottom)	3750			
<u>E</u> (Caliper)	Right Side	3687	Left Side	3674
<u>F</u> (Left Caliper)	613			
<u>G</u> (IP)	3028			
<u>H</u> (Seat)	1830			
<u>J</u> (Right Caliper)	629			
<u>K</u> (Trunk)	955			

## DATA SHEET 32

### PHOTOGRAPHIC TARGETS



Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Nick Kosinski

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u>  </u> 0 to 48 kmph	<u>  </u> 0 to 56 kmph
DRIVER DUMMY:	<u>  </u> 5 <sup>TH</sup> female	<u>X</u> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<u>  </u> 5 <sup>TH</sup> female	<u>X</u> 50 <sup>th</sup> Male	

- |                                     |      |  |
|-------------------------------------|------|--|
| <input checked="" type="checkbox"/> | 1.   | FMVSS 208 vehicle targeting requirements (See Figures 28A and 28B)   |
| <input checked="" type="checkbox"/> | 1.1  | Targets A1 and A2 are on flat rectangular panels.  |
| <input checked="" type="checkbox"/> | 1.2  | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the front on the outboard sides of A1 and A2. The center of each circular target is 100 mm from the one next to it.   |
| <input checked="" type="checkbox"/> |      | Distance between targets (mm): 100 mm  |
| <input checked="" type="checkbox"/> | 1.3  | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the back on the outboard sides of on A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| <input checked="" type="checkbox"/> |      | Distance between targets (mm): 100 mm  |
| <input checked="" type="checkbox"/> | 1.4  | The distance between the first circular target at the front of A1 and A2 and the last circular target at the back of A1 and A2 is at least 915 mm.   |
| <input checked="" type="checkbox"/> |      | Distance between the first and last circular targets (mm): 915 mm  |
| <input checked="" type="checkbox"/> | 1.5  | Firmly fix target A1 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy.   |
| <input checked="" type="checkbox"/> | 1.6  | Firmly fix target A2 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy.  |
| <input checked="" type="checkbox"/> | 1.7  | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the driver door. The centers of each circular target are at least 610 mm apart.              |
| <input checked="" type="checkbox"/> |      | Distance between targets (mm): 610 mm  |
| <input checked="" type="checkbox"/> | 1.8  | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the passenger door. The centers of each circular target are at least 610 mm apart.           |
| <input checked="" type="checkbox"/> |      | Distance between targets (mm): 610 mm  |
| <input checked="" type="checkbox"/> | 1.9  | Place tape with squares having alternating colors on the top portion of the steering wheel.  |
| <input checked="" type="checkbox"/> | 1.10 | Chalk the bottom portion of the steering wheel   |
| <input checked="" type="checkbox"/> | 1.11 | Is this an offset test?  |
| <input type="checkbox"/>            |      | Yes, continue with this section  |
| <input checked="" type="checkbox"/> |      | No, go to 2.   |
| <input type="checkbox"/>            | 1.12 | Measure the width of the vehicle.  |
| <input type="checkbox"/>            |      | Vehicle width (mm):  |

<input type="checkbox"/>	1.13	Find the centerline of the vehicle. ( $\frac{1}{2}$ of the vehicle width)
<input type="checkbox"/>	1.14	Find the line parallel to the centerline of the vehicle and 0.1 x vehicle width from the centerline of the vehicle.
<input type="checkbox"/>	1.15	Apply 25 mm wide tape with alternating black and yellow squares parallel to and on each side of the line found in 1.14. The edge of each tape shall be 50 mm from the line found in 1.14. The tape shall extend from the bottom of the bumper to the front edge of the windshield. (Figure 28D)
<input checked="" type="checkbox"/>	2.	Barrier Targeting
<input checked="" type="checkbox"/>	2.1	Fix two stationary targets D1 and D2 to the barrier as shown in the Figure 28A. One target is in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. The other is in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy
<input checked="" type="checkbox"/>	2.2	Targets D1 and D2 are on a rectangular panel.
<input checked="" type="checkbox"/>	2.3	Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted on the sides of the rectangular panel away from the longitudinal centerline of the vehicle. The center of each circular target is 100 mm from the one next to it.
<input checked="" type="checkbox"/>		Distance between circular targets on D1 (mm): 100mm
<input checked="" type="checkbox"/>		Distance between circular targets on D2 (mm): 100mm
<input checked="" type="checkbox"/>	3.	FMVSS 208 Dummy Targeting Requirements
<input checked="" type="checkbox"/>	3.1	Place a circular target with black and yellow quadrants on both sides of the driver dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
<input checked="" type="checkbox"/>	3.2	Place a circular target with black and yellow quadrants on both sides of the passenger dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
<input checked="" type="checkbox"/>	3.3	Place a circular target with black and yellow quadrants on the outboard shoulder of the driver dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
<input checked="" type="checkbox"/>	3.4	Place a circular target with black and yellow quadrants on the outboard shoulder of the passenger dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
<input checked="" type="checkbox"/>	4.	FMVSS 204 Targeting Requirements
<input checked="" type="checkbox"/>	4.1	Is an FMVSS 204 indicant test ordered on the "COTR Vehicle Work Order?"
<input type="checkbox"/>		Yes, continue with this form.
<input checked="" type="checkbox"/>		No, this form is complete.
<input type="checkbox"/>	4.2	Resection panel (Figure 28C)
<input type="checkbox"/>	4.2.1	The panel deviates no more than 6 mm from perfect flatness when suspended vertically
<input type="checkbox"/>	4.2.2	The 8 targets on the panel are circular targets at least 90 mm in diameter and with black and yellow quadrants.
<input type="checkbox"/>	4.2.3	The center of each of the 4 outer targets are placed within 1 mm of the corners of a square measuring 914 mm on each side.
<input type="checkbox"/>	4.2.4	Locate another square with 228 mm sides and with the center of this square coincident with the center of the 914 mm square.
<input type="checkbox"/>	4.2.5	The center of the 4 inner targets are placed at the midpoints of each of the 228 mm sides.


-  4.3 Place a circular target at least 90 mm in diameter and with black and yellow quadrants on a material (cardboard, metal, etc.) that can be taped to the top of the steering column.
-  4.4 Tape the target from 4.3 to the top of the steering column in a manner that does not interfere with the movement of the steering column in a crash

I certify that I have read and performed each instruction.


Signature: 

Date: 03/23/05


## REFERENCE PHOTO TARGETS




## RESECTION PANEL TARGETING ALIGNMENT



## TEST RUN STEERING COLUMN CAMERA VIEW OF TYPICAL TIME ZERO VEHICLE POSITION



## PRE-RUN STEERING COLUMN HIGH SPEED CAMERA VIEW



LEFT SIDE VIEW



**DATA SHEET 33**  
**CAMERA LOCATIONS**

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance


NHTSA No.: C55101  
Test Date: 3/23/05  
Time: 11:23 am

CAMERA NO.	VIEW	CAMERA POSITIONS (mm) *			LENS (mm)	SPEED (fps)
		X	Y	Z		
1	Real Time Left Side View				13	24
2	Left Side View (Barrier face to front seat backs)	905	-5250	1450	25	1000
3	Left Side View (Driver)	1705	-8420	1325	50	1000
4	Left Side View (B-post aimed toward center of steering wheel)	6665	-5055	2270	50	1000
5	Left Side View (Steering Column)	2225	-5765	1555	19	1000
6	Left Side View (Steering Column)	2190	-5710	1040	19	1000
7	Right Side View (Overall)	2195	6735	1425	19	1000
8	Right Side View (Passenger)	1525	8025	1425	50	1000
9	Right Side View (Angle)	6285	5195	2235	50	1000
10	Right Side View (Front door)	975	5215	1345	24	1000
11	Front View Windshield	-525	0	2760	14	1000
12	Front View Driver	-25	-290	2055	24	1000
13	Front View Passenger	-20	585	2110	24	1000
14	Overhead Barrier Impact View	670	0	5050	19	1000
15	Pit Camera Engine View	1020	0	-3150	24	1000
16	Pit Camera Fuel Tank View	2950	0	-3150	24	1000

**\*COORDINATES:**

+X - forward of impact plane  
+Y - right of monorail centerline  
+Z - above ground level

**CAMERA POSITIONS FOR FMVSS 208**



## DATA SHEET 34

### APPENDIX F DUMMY POSITIONING PROCEDURES FOR DRIVER TEST DUMMY CONFORMING TO SUBPART E OF PART 572

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance  
Test Technician: Eric Peschman

NHTSA No.: C55101  
Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	

- X 1. Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)  
X N/A – No lumbar adjustment
- X 2. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S20.1.8.2)  
X N/A – No additional support adjustment
- X 3. If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S20.1.9.3)  
X N/A – No independent fore-aft seat cushion adjustment
- X 4. Use the seat markings determined during the completion of Data Sheet 14 to set the mid-fore-aft position, full down height position and the seat cushion angle. (S8.1.2)
- X 5. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)  
   N/A – No seat back angle adjustment  
Manufacturer's design seat back angle 88.3° on HRP  
Tested seat back angle 87.7° on HRP
- X 6. If adjustable, set the head restraint at the full up and full forward position. Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. (S8.1.3)  
   N/A – No head restraint adjustment
- X 7. Place any adjustable seat belt anchorages at the vehicle manufacturer's nominal design position for a 50th percentile adult male occupant (S8.1.3)  
   N/A – No adjustable upper seat belt anchorage  
Manufacturer's specified anchorage position. 2<sup>nd</sup> Down  
Tested anchorage position 2<sup>nd</sup> Down (Unbelted Test)
- X 8. Place the adjustable accelerator pedal in the full forward position.  
X N/A – the accelerator pedal is not adjustable.

- ☒ 9. Set the steering wheel hub at the geometric center of the full range of driving positions including any telescoping positions as determined in data sheet 14.
- ☒ 10. Place the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion markings as determined in item 1.18 of Data Sheet 14 and the upper torso rests against the seat back. (S10.4.1.1 & S10.4.1.2)
- ☒ 11. Rest the thighs on the seat cushion. (S10.5)
- ☒ 12. Position the H-point of the dummy within 0.5 inch of the vertical dimension and 0.5 inch of the horizontal dimension of a point 0.25 inch below the H-point determined by using the equipment and procedures specified in SAE J826 (APR 1980). (S10.4.2.1) Then measure the pelvic angle with respect to the horizontal using the pelvic angle gage.

Adjust the dummy position until these three measurements are within the specifications.  
(S10.4.2.1 and S10.4.2.2)

.040 horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.)  
(S10.4.2.1)

.280 vertical inches from the point 0.25 below the determined H-point (0.5 inch max.)  
(S10.4.2.1)

24.9° pelvic angle (20° to 25°)

- ☒ 13. Is the head level within  $\pm 0.5^\circ$ ? (S10.1)

☒ Yes, go to 14

☐ No, go to 13.1

- ☐ 13.1 Adjust the position of the H-point. (S10.1)

- ☐ 13.2 Is the head level within  $\pm 0.5^\circ$ ? (S10.1)

☐ Yes, record the following, then go to 15. ☐ No, go to 13.3

       horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.)  
(S10.4.2.1)

       vertical inches from the point 0.25 below the determined H-point (0.5 inch max.)  
(S10.4.2.1)

       pelvic angle (20° to 25°) (S10.4.2.2)

- ☐ 13.3 Adjust the pelvic angle. (S10.1)

- ☐ 13.4 Is the head level within  $\pm 0.5^\circ$ ? (S10.1)

☐ Yes, record the following, then go to 14. ☐ No, go to 13.5

       horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.)  
(S10.4.2.1)

       vertical inches from the point 0.25 below the determined H-point (0.5 inch max.)  
(S10.4.2.1)

       pelvic angle (20° to 25°) (S10.4.2.2)

- ☐ 13.5 Adjust the neck bracket of the dummy the minimum amount necessary from the non-adjusted "0" setting until the head is level within  $\pm 0.5^\circ$ . (S10.1)  
Record the following, then go to 14  
☐ horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
☐ vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
☐ pelvic angle ( $20^\circ$  to  $25^\circ$ ) (S10.4.2.2)
- ☒ 14. Set the distance between the outboard knee clevis flange surfaces at 10.6 inches.  
10.6" measured distance (10.6 inches) (S10.5)
- ☒ 15. Can the right foot be placed on the accelerator?  
☒ Yes, go to 15.1 and skip 15.2  
☐ No, go to 15.2
- ☒ 15.1. To the extent practicable keep the right thigh and the leg in a vertical plane (S10.5) while resting the foot on the undepressed accelerator pedal with the rearmost point of the heel on the floor pan in the plane of the pedal. (S10.6.1.1)
- ☐ 15.2 Initially set the foot perpendicular to the leg and then place it as far forward as possible in the direction of the pedal centerline with the rearmost point of the heel resting on the floor pan. (S10.6.1.1)
- ☐ 15.2.1 Move the adjustable pedal to its most rearward position or until the right foot is flat on the pedal, whichever occurs first. (S10.6.1.1)  
☐ N/A – the accelerator pedal is not adjustable
- ☒ 16. Does the vehicle have a foot rest?  
☒ Yes, go to 16.1  
☐ No, go to 16.2
- ☒ 16.1 With the left thigh and leg in a vertical plane, place the foot on the foot rest with the heel resting on the floor pan. (S10.6.1.2)
- ☒ 16.1.1 Is the left foot elevated above the right foot?  
☐ Yes, go to 16.1.2 and position the foot off the foot rest  
☒ No, go to 17
- ☐ 16.1.2 Check the ONLY one of the following that applies
- ☐ The foot reaches the toeboard without adjusting the foot or leg. To the extent practicable keep the left thigh and the leg in a vertical longitudinal plane (S10.5) and place the foot on the toeboard, skip 16.1.3 (S10.6.1.2)
- ☐ The foot reaches the toeboard but contacts the brake or clutch pedal and must be rotated to avoid pedal contact. To the extent practicable keep the left thigh and the leg in a vertical longitudinal plane (S10.5) and place the foot on the toeboard. The foot was rotated about the leg to avoid pedal contact, skip 16.1.3 (S10.6.1.2)

☐ The foot reaches the toeboard but contacts the brake or clutch pedal and the foot and leg must be rotated to avoid pedal contact. To the extent practicable keep the left thigh and the leg in a vertical longitudinal plane (S10.5) and place the foot on the toeboard. The foot was rotated about the leg and the leg was rotated outboard about the hip the minimum distance necessary to avoid pedal contact, skip 16.1.3 (S10.6.1.2)

☐ N/A – the foot does not reach the toeboard, go to 16.1.3

☐ 16.1.3 Check the ONLY one of the following that applies

☐ The foot did not contact the brake or clutch pedal. To the extent practicable keep the left thigh and the leg in a vertical longitudinal plane (S10.5). Set the foot perpendicular to the leg and place it as far forward as possible with the heel resting on the floor pan. (S10.6.1.2)

☐ The foot did contact the brake or clutch pedal and the foot was rotated to avoid contact. To the extent practicable keep the left thigh and the leg in a vertical longitudinal plane (S10.5). Set the foot perpendicular to the leg and place it as far forward as possible with the heel resting on the floor pan and rotate the foot the minimum amount to avoid pedal contact. (S10.6.1.2)

☐ The foot did contact the brake or clutch pedal and the foot was rotated about the leg and the leg was rotated outboard about the hip the minimum distance necessary to avoid pedal contact. Set the foot perpendicular to the leg and place it as far forward as possible with the heel resting on the floor pan and rotate the foot about the leg and the thigh and leg outboard about the hip the minimum distance necessary to avoid pedal contact. (S10.6.1.2)

☒ 17. Place the right upper arm adjacent to the torso with the centerline as close to a vertical plane as possible. (S10.2.1)

☒ 18. Is the driver seat belt used for this test?

☐ Yes, continue

☒ No, go to 19

☐ 18.1 Fasten the seat belt around the dummy.

☐ 18.2 Remove all slack from the lap belt portion. (S10.9)

☐ 18.3 Pull the upper torso webbing out of the retractor and allow it to retract; repeat this four times. (S10.9)

☐ 18.4 Apply a 2 to 4 pound tension load to the lap belt. (S10.9)  
\_\_\_\_\_pound load applied

☐ 18.5 Is the belt system equipped with a tension-relieving device?

☐ Yes, continue

☐ No, go to 19

- 18.6 Introduce the maximum amount of slack into the upper torso bet that is recommended by the vehicle manufacturer in the vehicle owner's manual. (S10.9).
- X 19. Place the left upper arm adjacent to the torso with the centerline as close to a vertical plane as possible. (S10.2.1)
- X 20. Place the right hand with the palm in contact with the steering wheel at the rim's horizontal centerline and with the thumb over the steering wheel. (S10.3.1)
- X 21. Place the left hand with the palm in contact with the steering wheel at the rim's horizontal centerline and with the thumb over the steering wheel. (S10.3.1)
- X 22. Tape the thumb of each hand to the steering wheel by using masking tape with a width of 0.25 inch. The length of the tape shall only be enough to go around the thumb and steering wheel one time.

REMARKS:

I certify that I have read and performed each instruction.

Signature: Eiv L. [Signature]

Date: 03/23/05

**APPENDIX F**  
**DUMMY POSITIONING PROCEDURES FOR PASSENGER TEST DUMMY CONFORMING**  
**TO SUBPART E OF PART 572**

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Wayne Dahlke

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	

- X 1. The seat is a bench seat for which the adjustments have already been made for the driver and there are no independent adjustments that can be made for the passenger. Go to 7.  
X N/A- the passenger seat adjusts independently of the driver seat.
- X 2. Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)  
X N/A – No lumbar adjustment
- X 3. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S20.1.8.2)  
X N/A – No additional support adjustment
- X 4. If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S20.1.9.3)  
X N/A – No independent fore-aft seat cushion adjustment
- X 5. Use the seat markings determined during the completion of Data Sheet 14 to set the mid-fore-aft position, full down height position and the seat cushion angle. (S8.1.2)
- X 6. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)  
   N/A – No seat back angle adjustment  
 Manufacturer's design seat back angle      89.0° on HRP  
 Tested seat back angle                              89.2° on HRP
- X 7. If adjustable, set the head restraint at the full up and full forward position. Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. (S8.1.3)  
   N/A – No head restraint adjustment



- X 8. Place any adjustable seat belt anchorages at the vehicle manufacturer's nominal design position for a 50th percentile adult male occupant (S8.1.3)  
\_\_\_ N/A – No adjustable upper seat belt anchorage  
Manufacturer's specified anchorage position. 2<sup>nd</sup> Down  
Tested anchorage position 2<sup>nd</sup> Down (Unbelted Test)  
\_\_\_ N/A - the seat does not have a fore-aft adjustment
- X 9. Place the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion markings as determined in item 2.19 of Data Sheet 14 and the upper torso rests against the seat back. (S10.4.1.1 & S10.4.1.2)
- X 10. Rest the thighs on the seat cushion. (S10.5)
- X 11. Position the H-point of the dummy within 0.5 inch of the vertical dimension and 0.5 inch of the horizontal dimension of a point 0.25 inch below the H-point determined by using the equipment and procedures specified in SAE J826 (APR 1980). (S10.4.2.1) Then measure the pelvic angle with respect to the horizontal using the pelvic angle gage.
- Adjust the dummy position until these three measurements are within the specifications. (S10.4.2.1 and S10.4.2.2)  
.080 horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
.565 vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
21.5° pelvic angle (20° to 25°)
- X 12. Is the head level within  $\pm 0.5^\circ$ ? (S10.1)  
X Yes, go to 13  
\_\_\_ No, go to 12.1
- \_\_\_ 12.1 Adjust the position of the H-point. (S10.1 and S10.4.2.1)
- \_\_\_ 12.2 Is the head level within  $\pm 0.5^\circ$ ? (S10.1)  
\_\_\_ Yes, record the following, then go to 13. \_\_\_ No, go to 12.3  
\_\_\_ horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
\_\_\_ vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
\_\_\_ pelvic angle (20° to 25°) (S10.4.2.2)
- \_\_\_ 12.3 Adjust the pelvic angle. (S10.1)
- \_\_\_ 12.4 Is the head level within  $\pm 0.5^\circ$ ? (S10.1)  
\_\_\_ Yes, record the following, then go to 13. \_\_\_ No, go to 12.5  
\_\_\_ horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
\_\_\_ vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)  
\_\_\_ pelvic angle (20° to 25°) (S10.4.2.2)

☐ 12.5 Adjust the neck bracket of the dummy the minimum amount necessary from the non-adjusted "0" setting until the head is level within  $\pm 0.5^\circ$ . (S10.1)

Record the following, then go to 13

☐ horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)

☐ vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)

☐ pelvic angle ( $20^\circ$  to  $25^\circ$ ) (S10.4.2.2)

☒ 13. Set the distance between the outboard knee clevis flange surfaces at 10.6 inches. 10.6" measured distance (10.6 inches) (S10.5)

☒ 14. Check the only one of the following that applies:

☐ To the extent practicable keep the left thigh and leg in a vertical plane and the right thigh and leg in a vertical plane, place the feet on the toeboard with the heels resting on the floor pan as close as possible to the intersection of the floor pan and toeboard.

☒ The feet cannot be placed flat on the toeboard. To the extent practicable keep the left thigh and leg in a vertical plane and the right thigh and leg in a vertical plane, set the feet perpendicular to the legs and place them as far forward as possible with the heels resting on the floor pan.

☐ The vehicle has a wheelhouse projection. To the extent practicable keep the left thigh and leg in a vertical plane and the right thigh and leg in a vertical plane, set the feet perpendicular to the legs and place them as far forward as possible with the heels resting on the floor pan. Do not set the feet on the wheelhouse projection.

☐ The vehicle has a wheelhouse projection and the feet cannot be placed on the toeboard. To the extent practicable keep the left thigh and leg in a vertical plane and the right thigh and leg in a vertical plane, set the feet perpendicular to the legs and place them as far forward as possible with the heel resting on the floor pan. . Do not set the feet on the wheelhouse projection.

☒ 15. Place the left upper arm in contact with the seat back and side of the torso. (S10.2.2)

☒ 16. Is the passenger seat belt used for this test?

☐ Yes, continue

☒ No, go to 17

☐ 16.1 Fasten the seat belt around the dummy.

☐ 16.2 Remove all slack from the lap belt portion. (S10.9)

☐ 16.3 Pull the upper torso webbing out of the retractor and allow it to retract; repeat this four times. (S10.9)

☐ 16.4 Apply a 2 to 4 pound tension load to the lap belt. (S10.9)  
☐ pound load applied

\_\_\_ 16.5 Is the belt system equipped with a tension relieving device?

\_\_\_ Yes, continue

\_\_\_ No, go to 17

\_\_\_ 16.6 Introduce the maximum amount of slack into the upper torso belt that is recommended by the vehicle manufacturer in the vehicle owner's manual. (S10.9). Go to 17.

X 17. Place the right upper arm in contact with the seat back and side of the torso. (S10.2.2)

X 18. Place the left hand palm in contact with the outside of the left thigh and the little finger in contact with the seat cushion. (S10.3.2)

X 19. Place the right hand palm in contact with the outside of the right thigh and the little finger in contact with the seat cushion. (S10.3.2)

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne J. Ahl

Date: 03/23/05


# DATA SHEET 35

## DUMMY MEASUREMENTS

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Eric Peschman

NHTSA No.: C55101  
 Test Date: 3/23/05

### DUMMY MEASUREMENTS FOR FRONT SEAT OCCUPANTS



**DATA SHEET 35**  
**DUMMY MEASUREMENTS**


Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance  
Test Technician: Eric Peschman

NHTSA No.: C55101  
Test Date: 3/23/05

**TEST DUMMY POSITION MEASUREMENTS**

Code	Measurement Description	Driver SN 401		Passenger SN 403	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA	Windshield Angle		27.1		
SWA	Steering Wheel Angle		62.4		
SCA	Steering Column Angle		28.3		
SA	Seat Back Angle (On Headrest)		2.3		0.8
HZ	Head to Roof (Z)	198		161	
HH	Head to Header	348	21.0	309	20.4
HW	Head to Windshield	624	0.0	532	0.0
HR	Head to Side Header (Y)	198		185	
NR	Nose to Rim	447	12.5		
CD	Chest to Dash	541		528	
CS	Chest to Steering Hub	353	10.1		
RA	Rim to Abdomen	217	0.0		
KDL	Left Knee to Dash	139	23.3	145	
KDR	Right Knee to Dash	128		135	30.4
PA	Pelvic Angle		24.9		21.5
TA	Tibia Angle		58.4		48.1
KK	Knee to Knee (Y)	308		253	
SK	Striker to Knee	584	99.5	614	102.0
ST	Striker to Head	420	10.7	468	15.7
SH	Striker to H-Point	308	136.8	298	132.3
SHY	Striker to H-Point (Y)	242		221	
HS	Head to Side Window	294		280	
HD	H-Point to Door (Y)	144		130	
AD	Arm to Door (Y)	101		90	
AA	Ankle to Ankle	316		218	

## SEAT BELT POSITIONING DATA



### FRONT VIEW OF DUMMY

#### SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU - Top surface of reference to belt upper edge	mm	N/A	N/A
PBL - To surface of reference to belt lower edge	mm	N/A	N/A

## DATA SHEET 36

### CRASH TEST

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Eric Peschman

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u>  </u> 0 to 48 kmph	<u>  </u> 0 to 56 kmph
DRIVER DUMMY:	<u>  </u> 5 <sup>TH</sup> female	<u>X</u> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<u>  </u> 5 <sup>TH</sup> female	<u>X</u> 50 <sup>th</sup> Male	

- |          |   |
|----------|---|
| <b>X</b> | 1. Vehicle underbody painted  |
| <b>X</b> | 2. The speed measuring devices are in place and functioning.  |
| <b>X</b> | 3. The speed measuring devices are <u>1.0</u> m from the barrier (spec. 1.5m) and <u>30</u> cm from the barrier (spec. is 30 cm)  |
| <b>X</b> | 4. Convertible top is in the closed position.   |
| <b>X</b> | <b>X</b> N/A, not a convertible   |
| <b>X</b> | 5. Instrumentation and wires are placed so the motion of the dummies during impact is not affected.   |
| <b>X</b> | 6. Tires inflated to pressure on tire placard or if it does not have a tire placard because it is not a passenger car, then inflated to the tire pressure specified in the owner information. |

<u>210 kpa</u> front left tire	<u>210 kpa</u> specified on tire placard or in owner information
<u>210 kpa</u> front right tire	<u>210 kpa</u> specified on tire placard or in owner information
<u>210 kpa</u> rear left tire	<u>210 kpa</u> specified on tire placard or in owner information
<u>210 kpa</u> rear right tire	<u>210 kpa</u> specified on tire placard or in owner information

- |          |   |
|----------|---|
| <b>X</b> | 7. Time zero contacts on barrier in place.  |
| <b>X</b> | 8. Pre test zero and shunt calibration adjustments performed and recorded                     |
| <b>X</b> | 9. Dummy temperature meets requirements of section 12.2 of the test procedure.                |
| <b>X</b> | 10. Vehicle hood closed and latched   |
| <b>X</b> | 11. Transmission placed in neutral  |
| <b>X</b> | 12. Parking brake off   |
| <b>X</b> | 13. Ignition in the ON position   |
| <b>X</b> | 14. Doors closed and latched but not locked   |
| <b>X</b> | 15. Posttest zero and shunt calibration checks performed and recorded                         |
| <b>X</b> | 16. Actual test speed <u>39.9</u> kmph  |
| <b>X</b> | 17. Vehicle rebound from the barrier <u>164</u> cm  |
| <b>X</b> | 18. Describe whether the doors open after the test and what method is used to open the doors. |
- |          |   |
|----------|---|
| <b>X</b> | Left Front Door: Door remained closed and latched; Door opened without tools  |
| <b>X</b> | Right Front Door: Door remained closed and latched; Door opened without tools |
| <b>X</b> | Left Rear Door: Door remained closed and latched; Door opened without tools   |
| <b>X</b> | Right Rear Door: Door remained closed and latched; Door opened without tools  |

- ☒ 19. Describe the contact points of the dummy with the interior of the vehicle.
- ☒ Driver Dummy: Head to Windshield, Air Bag and Headrest; Chest to Air Bag; Knees to Knee Bolster and Steering Column
- ☒ Passenger Dummy: Head to Air Bag, Header, and Visor; Chest to Air Bag; Knees to Glove Box and Dash

REMARKS:

I certify that I have read and performed each instruction.

Signature: 

Date: 03/23/05



# DATA SHEET NO. 38

## ACCIDENT INVESTIGATION DIVISION DATA

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Nick Kosinski

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	

Vehicle Year/Make/Model/Body Style:	2005 Toyota Corolla Passenger Car
VIN:	JTDBR32E952055812
Wheelbase:	2596 mm
Build Date:	07/04
Vehicle Size Category:	2
Test Weight:	1363.5 kg
Front Overhang:	913 mm
Overall Width:	1698 mm
Overall Length Center:	4506 mm


Accelerometer Data	
Location:	As per measurements on Data Sheet 31
Linearity:	>99.9%

Integration Algorithm:	Trapezoidal
Vehicle Impact Speed:	39.9 kmph
Time of Separation:	95.8 ms
Velocity Change:	43.8 kmph

## CRUSH PROFILE

Collision Deformation Classification: 12FDEW6  
 Midpoint of Damage: Vehicle Longitudinal Centerline  
 Damage Region Length (mm): 1523  
 Impact Mode: Frontal Barrier

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush zone 1 at left side	mm	4316	4084	232
C2	Crush zone 2 at left side	mm	4432	4091	341
C3	Crush zone 3 at left side	mm	4487	4068	419
C4	Crush zone 4 at right side	mm	4487	4048	439
C5	Crush zone 5 at right side	mm	4432	4082	350
C6	Crush zone 6 at right side	mm	4315	4087	228



REMARKS:

I certify that I have read and performed each instruction.

Signature: *Nick Kosinski*

Date: 03/23/05

**DATA SHEET 39**  
**WINDSHIELD MOUNTING (FMVSS 212)**

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Nick Kosinski

NHTSA No.: C55101  
 Test Date: 3/23/05


IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u>  </u> 0 to 48 kmph	<u>  </u> 0 to 56 kmph
DRIVER DUMMY:	<u>  </u> 5 <sup>TH</sup> female	<u>X</u> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<u>  </u> 5 <sup>TH</sup> female	<u>X</u> 50 <sup>th</sup> Male	

- ☒ 1. Pre-Crash
- ☒ 1.1 Describe from visual inspection how the windshield is mounted and describe any trim material.
- Retained with glue  
Rubber trim
- ☒ 1.2 Mark the longitudinal centerline of the windshield
- ☒ 1.3 Measure pre-crash A, B, and C for the left side and record in the chart below.
- ☒ 1.4 Measure pre-crash C, D, and E for the right side and record in the chart below.
- ☒ 1.5 Measure from the edge of the retainer or molding to the edge of the windshield.
- ☒ Dimension G (mm): 16 mm
2. Post Crash
- ☒ 2.1 Can a single thickness of copier type paper (as small a piece as necessary) slide between the windshield and the vehicle body?
- ☒ No – Pass. Skip to the table of measurements, complete it by repeating the pre-crash measurements in the post crash column, and calculate the retention percentage, which will be 100%.
- ☐ Yes, go to 2.2
- ☐ 2.2 Visibly mark the beginning and end of the portions of the periphery where the paper slides between the windshield and the vehicle body.
- ☐ 2.3 Measure and record post-crash A, B, C, D, E, and F such that the measurements do not include any of the parts of the windshield where the paper slides between the windshield and the vehicle body.
- ☐ 2.4 Calculate and record the percent retention for the right and left side of the windshield.
- ☐ 2.5 Is total right side percent retention less than 75%?
- ☐ Yes, Fail
- ☐ No, Pass
- ☐ 6. Is total left side percent retention less than 75%?
- ☐ Yes, Fail
- ☐ No, Pass

## WINDSHIELD RETENTION MEASUREMENTS

	Dimension	Pre-Crash (mm)	Post-Crash (mm)	Percent Retention (Post-Test ÷ Pre-Crash)
Left Side	A	541	541	100%
	B	532	532	100%
	C	696.5	696.5	100%
	Total	1769.5	1769.5	100%
Right Side	D	541	541	100%
	E	532	532	100%
	F	696.5	696.5	100%
	Total	1769.5	1769.5	100%

Indicate area of mounting failure. NONE



REMARKS:

I certify that I have read and performed each instruction.

Signature: *Thick Krsinski*

Date: 03/23/05

**DATA SHEET 40**  
**WINDSHIELD ZONE INTRUSION (FMVSS 219)**


Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Nick Kosinski

NHTSA No.: C55101  
 Test Date: 3/23/05

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	
PASSENGER DUMMY:	<input type="checkbox"/> 5 <sup>TH</sup> female	<input checked="" type="checkbox"/> 50 <sup>th</sup> Male	

- ☒ 1. Place a 165 mm diameter rigid sphere, with a mass of 6.8 kg on the instrument panel so that it is simultaneously touching the instrument panel and the windshield. (571.219 S6.1(a))
- ☒ 2. Roll the sphere from one side of the windshield to the other while marking on the windshield where the sphere contacts the windshield. (571.219 S6.1(b))
- ☒ 3. From the outermost contactable points on the windshield draw a horizontal line to the edges of the windshield. (571.219 S6.1(b))
- ☒ 4. Draw a line on the inner surface of the windshield that is 13 mm below the line determined in items 2 and 3
- ☒ 5. After the crash test, record any points where a part of the exterior of the vehicle has marked, penetrated, or broken the windshield.

Provide all dimensions necessary to reproduce the protected area.



## WINDSHIELD DIMENSIONS

Item	Units	Value
A	mm	1082
B	mm	540
C	mm	1393
D	mm	532
E	mm	512
F	mm	510

### AREA OF PROTECTED ZONE FAILURES:

- B. Provide coordinates of the area that the protected zone was penetrated more than 0.25 inches by a vehicle component other than one which is normally in contact with the windshield.

X	Y
NONE	

- C. Provide coordinates of the area beneath the protected zone template that the inner surface of the windshield was penetrated by a vehicle component.

X	Y
NONE	

### REMARKS:

I certify that I have read and performed each instruction.

Signature: *Thick Kosinski*

Date: 03/23/05

**DATA SHEET 41**  
**FUEL SYSTEM INTEGRITY (FMVSS 301)**

Test Vehicle: 2005 Toyota Corolla  
Test Program: FMVSS 208 Compliance  
Test Technician: Eric Peschman

NHTSA No.: C55101  
Test Date: 3/23/05

TYPE OF IMPACT:	25 mph Unbelted Flat Frontal
-----------------	------------------------------

**Stoddard Solvent Spillage Measurements**


- A. From impact until vehicle motion ceases: 0.0 grams  
(Maximum Allowable = 28 grams)
- B. For the 5 minute period after motion ceases: 0.0 grams  
(Maximum Allowable = 142 grams)
- C. For the following 25 minutes: 0.0 grams  
(Maximum Allowable = 28 grams/minute)
- D. Spillage: NONE

REMARKS: NO SPILLAGE

**DATA SHEET NO. 41**  
**FMVSS 301 STATIC ROLLOVER DATA**

Test Vehicle: 2005 Toyota Corolla  
 Test Program: FMVSS 208 Compliance

NHTSA No.: C55101  
 Test Date: 3/23/05



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage locations: **The post test FMVSS 301 rollover was not conducted due to the apparent noncompliance.**

Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (grams)
0° to 90°			
90° to 180°			
180° to 270°			
270° to 360°			



**APPENDIX A**  
**CRASH TEST DATA**

## TABLE OF DATA PLOTS

		<u>Page No.</u>
Figure No. 1.	Driver Head X Acceleration vs. Time	A-1
Figure No. 2.	Driver Head Y Acceleration vs. Time	A-1
Figure No. 3.	Driver Head Z Acceleration vs. Time	A-1
Figure No. 4.	Driver Head Resultant Acceleration vs. Time	A-1
Figure No. 5.	Driver Head X Velocity vs. Time	A-2
Figure No. 6.	Driver Head Y Velocity vs. Time	A-2
Figure No. 7.	Driver Head Z Velocity vs. Time	A-2
Figure No. 8.	Driver Neck Force X vs. Time	A-3
Figure No. 9.	Driver Neck Force Y vs. Time	A-3
Figure No. 10.	Driver Neck Force Z vs. Time	A-3
Figure No. 11.	Driver Neck Force Resultant vs. Time	A-3
Figure No. 12.	Driver Neck Moment X vs. Time	A-4
Figure No. 13.	Driver Neck Moment Y vs. Time	A-4
Figure No. 14.	Driver Neck Moment Z vs. Time	A-4
Figure No. 15.	Driver Neck Moment Resultant vs. Time	A-4
Figure No. 16.	Driver Chest X Acceleration vs. Time	A-5
Figure No. 17.	Driver Chest Y Acceleration vs. Time	A-5
Figure No. 18.	Driver Chest Z Acceleration vs. Time	A-5
Figure No. 19.	Driver Chest Resultant Acceleration vs. Time	A-5
Figure No. 20.	Driver Chest X Velocity vs. Time	A-6
Figure No. 21.	Driver Chest Y Velocity vs. Time	A-6
Figure No. 22.	Driver Chest Z Velocity vs. Time	A-6
Figure No. 23.	Driver Chest Displacement vs. Time	A-6
Figure No. 24.	Driver Left Femur Force vs. Time	A-7
Figure No. 25.	Driver Right Femur Force vs. Time	A-7
Figure No. 26.	Passenger Head X Acceleration vs. Time	A-8
Figure No. 27.	Passenger Head Y Acceleration vs. Time	A-8
Figure No. 28.	Passenger Head Z Acceleration vs. Time	A-8
Figure No. 29.	Passenger Head Resultant Acceleration vs. Time	A-8





		<u>Page No.</u>
Figure No. 30.	Passenger Head X Velocity vs. Time	A-9
Figure No. 31.	Passenger Head Y Velocity vs. Time	A-9
Figure No. 32.	Passenger Head Z Velocity vs. Time	A-9
Figure No. 33.	Passenger Neck Force X vs. Time	A-10
Figure No. 34.	Passenger Neck Force Y vs. Time	A-10
Figure No. 35.	Passenger Neck Force Z vs. Time	A-10
Figure No. 36.	Passenger Neck Force Resultant vs. Time	A-10
Figure No. 37.	Passenger Neck Moment X vs. Time	A-11
Figure No. 38.	Passenger Neck Moment Y vs. Time	A-11
Figure No. 39.	Passenger Neck Moment Z vs. Time	A-11
Figure No. 40.	Passenger Neck Moment Resultant vs. Time	A-11
Figure No. 41.	Passenger Chest X Acceleration vs. Time	A-12
Figure No. 42.	Passenger Chest Y Acceleration vs. Time	A-12
Figure No. 43.	Passenger Chest Z Acceleration vs. Time	A-12
Figure No. 44.	Passenger Chest Resultant Acceleration vs. Time	A-12
Figure No. 45.	Passenger Chest X Velocity vs. Time	A-13
Figure No. 46.	Passenger Chest Y Velocity vs. Time	A-13
Figure No. 47.	Passenger Chest Z Velocity vs. Time	A-13
Figure No. 48.	Passenger Chest Displacement vs. Time	A-13
Figure No. 49.	Passenger Left Femur Force vs. Time	A-14
Figure No. 50.	Passenger Right Femur Force vs. Time	A-14
Figure No. 51.	Driver Nij ( $N_{TF}$ ) vs. Time	A-15
Figure No. 52.	Driver Nij ( $N_{TE}$ ) vs. Time	A-15
Figure No. 53.	Driver Nij ( $N_{CF}$ ) vs. Time	A-15
Figure No. 54.	Driver Nij ( $N_{CE}$ ) vs. Time	A-15
Figure No. 55.	Passenger Nij ( $N_{TF}$ ) vs. Time	A-16
Figure No. 56.	Passenger Nij ( $N_{TE}$ ) vs. Time	A-16
Figure No. 57.	Passenger Nij ( $N_{CF}$ ) vs. Time	A-16
Figure No. 58.	Passenger Nij ( $N_{CE}$ ) vs. Time	A-16
Figure No. 59.	Driver Occipital Condyle Moment vs. Time	A-17

		<u>Page No.</u>
Figure No. 60.	Passenger Occipital Condyle Moment vs. Time	A-17
Figure No. 61.	Left Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 62.	Left Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 63.	Right Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 64.	Right Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 65.	Top of Engine X Acceleration vs. Time	A-19
Figure No. 66.	Top of Engine X Velocity vs. Time	A-19
Figure No. 67.	Bottom of Engine X Acceleration vs. Time	A-19
Figure No. 68.	Bottom of Engine X Velocity vs. Time	A-19
Figure No. 69.	Left Brake Caliper X Acceleration vs. Time	A-20
Figure No. 70.	Left Brake Caliper X Velocity vs. Time	A-20
Figure No. 71.	Right Brake Caliper X Acceleration vs. Time	A-20
Figure No. 72.	Right Brake Caliper X Velocity vs. Time	A-20
Figure No. 73.	Instrument Panel X Acceleration vs. Time	A-21
Figure No. 74.	Instrument Panel X Velocity vs. Time	A-21
Figure No. 75.	Trunk Z Acceleration vs. Time	A-21
Figure No. 76.	Trunk Z Velocity vs. Time	A-21
Figure No. 77.	Barrier Sum Row 1 vs. Time	A-22
Figure No. 78.	Barrier Sum Row 2 vs. Time	A-22
Figure No. 79.	Barrier Sum Row 3 vs. Time	A-22
Figure No. 80.	Barrier Sum Row 4 vs. Time	A-22
Figure No. 81.	Barrier Sum Row 5 vs. Time	A-23
Figure No. 82.	Barrier Sum Row 6 vs. Time	A-23
Figure No. 83.	Barrier Sum Row 7 vs. Time	A-23
Figure No. 84.	Barrier Sum Row 8 vs. Time	A-23
Figure No. 85.	Barrier Sum Row 9 vs. Time	A-24
Figure No. 86.	Barrier Total Force vs. Time	A-24
Figure No. 87.	Barrier Rows 1 to 9 vs. Time	A-25
Figure No. 88.	Barrier Total Force vs. Time	A-25



25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)




Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)





25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)





25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)





25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)














25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)









25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)








25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)











25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)





25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)









25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)











25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)





25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)







25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)


Pass. nij (NTF) ( ) vs TIME (ms)




Pass. nij (NTE) ( ) vs TIME (ms)



Pass. nij (NCF) ( ) vs TIME (ms)





Pass. nij (NCE) ( ) vs TIME (ms)





25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)





Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)









25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)















25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)

















25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)









25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)







25MPH FRONTAL UNBELTED  
2005 TOYOTA COROLLA (C55101)

Test Date: 03/23/05  
Speed: 24.8 mph (39.9 km/h)

THE VEHICLE IMPACTED THE BARRIER 6 mm LOWER THAN  
THE INITIAL TARGET.



**APPENDIX B**  
**LOW RISK TEST DATA**

## TABLE OF DATA PLOTS

		<u>Page No.</u>
Figure No. 1.	5 <sup>th</sup> Fem. P1 Driver Head X Acceleration vs. Time	B-1
Figure No. 2.	5 <sup>th</sup> Fem. P1 Driver Head Y Acceleration vs. Time	B-1
Figure No. 3.	5 <sup>th</sup> Fem. P1 Driver Head Z Acceleration vs. Time	B-1
Figure No. 4.	5 <sup>th</sup> Fem. P1 Driver Head Resultant Acceleration vs. Time	B-1
Figure No. 5.	5 <sup>th</sup> Fem. P1 Driver Head X Velocity vs. Time	B-2
Figure No. 6.	5 <sup>th</sup> Fem. P1 Driver Head Y Velocity vs. Time	B-2
Figure No. 7.	5 <sup>th</sup> Fem. P1 Driver Head Z Velocity vs. Time	B-2
Figure No. 8.	5 <sup>th</sup> Fem. P1 Driver Neck Force X vs. Time	B-3
Figure No. 9.	5 <sup>th</sup> Fem. P1 Driver Neck Force Y vs. Time	B-3
Figure No. 10.	5 <sup>th</sup> Fem. P1 Driver Neck Force Z vs. Time	B-3
Figure No. 11.	5 <sup>th</sup> Fem. P1 Driver Neck Force Resultant vs. Time	B-3
Figure No. 12.	5 <sup>th</sup> Fem. P1 Driver Neck Moment X vs. Time	B-4
Figure No. 13.	5 <sup>th</sup> Fem. P1 Driver Neck Moment Y vs. Time	B-4
Figure No. 14.	5 <sup>th</sup> Fem. P1 Driver Neck Moment Z vs. Time	B-4
Figure No. 15.	5 <sup>th</sup> Fem. P1 Driver Occipital Condyle Moment vs. Time	B-4
Figure No. 16.	5 <sup>th</sup> Fem. P1 Driver Chest X Acceleration vs. Time	B-5
Figure No. 17.	5 <sup>th</sup> Fem. P1 Driver Chest Y Acceleration vs. Time	B-5
Figure No. 18.	5 <sup>th</sup> Fem. P1 Driver Chest Z Acceleration vs. Time	B-5
Figure No. 19.	5 <sup>th</sup> Fem. P1 Driver Chest Resultant Acceleration vs. Time	B-5
Figure No. 20.	5 <sup>th</sup> Fem. P1 Driver Chest X Velocity vs. Time	B-6
Figure No. 21.	5 <sup>th</sup> Fem. P1 Driver Chest Y Velocity vs. Time	B-6
Figure No. 22.	5 <sup>th</sup> Fem. P1 Driver Chest Z Velocity vs. Time	B-6
Figure No. 23.	5 <sup>th</sup> Fem. P1 Driver Chest Displacement vs. Time	B-6
Figure No. 24.	5 <sup>th</sup> Fem. P1 Driver Left Femur Force vs. Time	B-7
Figure No. 25.	5 <sup>th</sup> Fem. P1 Driver Right Femur Force vs. Time	B-7
Figure No. 26.	Fire Voltage #1 Voltage vs. Time	B-8
Figure No. 27.	Fire Current #1 Voltage vs. Time	B-8
Figure No. 28.	Fire Voltage #2 Voltage vs. Time	B-8
Figure No. 29.	Fire Current #2 Voltage vs. Time	B-8

	<u>Page No.</u>
Figure No. 30. 5 <sup>th</sup> Fem. P1 Driver Nij ( $N_{TF}$ ) vs. Time	B-9
Figure No. 31. 5 <sup>th</sup> Fem. P1 Driver Nij ( $N_{TE}$ ) vs. Time	B-9
Figure No. 32. 5 <sup>th</sup> Fem. P1 Driver Nij ( $N_{CF}$ ) vs. Time	B-9
Figure No. 33. 5 <sup>th</sup> Fem. P1 Driver Nij ( $N_{CE}$ ) vs. Time	B-9
Figure No. 34. 5 <sup>th</sup> Fem. P2 Driver Head X Acceleration vs. Time	B-10
Figure No. 35. 5 <sup>th</sup> Fem. P2 Driver Head Y Acceleration vs. Time	B-10
Figure No. 36. 5 <sup>th</sup> Fem. P2 Driver Head Z Acceleration vs. Time	B-10
Figure No. 37. 5 <sup>th</sup> Fem. P2 Driver Head Resultant Acceleration vs. Time	B-10
Figure No. 38. 5 <sup>th</sup> Fem. P2 Driver Head X Velocity vs. Time	B-11
Figure No. 39. 5 <sup>th</sup> Fem. P2 Driver Head Y Velocity vs. Time	B-11
Figure No. 40. 5 <sup>th</sup> Fem. P2 Driver Head Z Velocity vs. Time	B-11
Figure No. 41. 5 <sup>th</sup> Fem. P2 Driver Neck Force X vs. Time	B-12
Figure No. 42. 5 <sup>th</sup> Fem. P2 Driver Neck Force Y vs. Time	B-12
Figure No. 43. 5 <sup>th</sup> Fem. P2 Driver Neck Force Z vs. Time	B-12
Figure No. 44. 5 <sup>th</sup> Fem. P2 Driver Neck Force Resultant vs. Time	B-12
Figure No. 45. 5 <sup>th</sup> Fem. P2 Driver Neck Moment X vs. Time	B-13
Figure No. 46. 5 <sup>th</sup> Fem. P2 Driver Neck Moment Y vs. Time	B-13
Figure No. 47. 5 <sup>th</sup> Fem. P2 Driver Neck Moment Z vs. Time	B-13
Figure No. 48. 5 <sup>th</sup> Fem. P2 Driver Occipital Condyle Moment vs. Time	B-13
Figure No. 49. 5 <sup>th</sup> Fem. P2 Driver Chest X Acceleration vs. Time	B-14
Figure No. 50. 5 <sup>th</sup> Fem. P2 Driver Chest Y Acceleration vs. Time	B-14
Figure No. 51. 5 <sup>th</sup> Fem. P2 Driver Chest Z Acceleration vs. Time	B-14
Figure No. 52. 5 <sup>th</sup> Fem. P2 Driver Chest Resultant Acceleration vs. Time	B-14
Figure No. 53. 5 <sup>th</sup> Fem. P2 Driver Chest X Velocity vs. Time	B-15
Figure No. 54. 5 <sup>th</sup> Fem. P2 Driver Chest Y Velocity vs. Time	B-15
Figure No. 55. 5 <sup>th</sup> Fem. P2 Driver Chest Z Velocity vs. Time	B-15
Figure No. 56. 5 <sup>th</sup> Fem. P2 Driver Chest Displacement vs. Time	B-15
Figure No. 57. 5 <sup>th</sup> Fem. P2 Driver Left Femur Force vs. Time	B-16
Figure No. 58. 5 <sup>th</sup> Fem. P2 Driver Right Femur Force vs. Time	B-16
Figure No. 59. Fire Voltage #1 Voltage vs. Time	B-17







		<u>Page No.</u>
Figure No. 60.	Fire Current #1 Voltage vs. Time	B-17
Figure No. 61.	Fire Voltage #2 Voltage vs. Time	B-17
Figure No. 62.	Fire Current #2 Voltage vs. Time	B-17
Figure No. 63.	5 <sup>th</sup> Fem. P2 Driver Nij ( $N_{TF}$ ) vs. Time	B-18
Figure No. 64.	5 <sup>th</sup> Fem. P2 Driver Nij ( $N_{TE}$ ) vs. Time	B-18
Figure No. 65.	5 <sup>th</sup> Fem. P2 Driver Nij ( $N_{CF}$ ) vs. Time	B-18
Figure No. 66.	5 <sup>th</sup> Fem. P2 Driver Nij ( $N_{CE}$ ) vs. Time	B-18



LOW RISK DEPLOYMENT  
2005 TOYOTA COROLLA (C55101) (5TH P1)




Test Date: 01/28/05  
Speed: 0.0 mph ( 0.0 km/h)

Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms







Injury Values Calculated between 0ms and 165ms





Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms


FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)



FIRE VOLTAGE #2 (Volts) vs TIME (ms)




FIRE CURRENT #2 (Amps) vs TIME (ms)






Drv. nij (NTF) ( ) vs TIME SPECIAL CHS (ms)




Max: 0.3  
Tmax: 9.8 ms  
Min: 0.0  
Tmin: 0.1 ms  
CFC 600

Drv. nij (NTE) ( ) vs TIME SPECIAL CHS (ms)




Max: 0.7  
Tmax: 52.2 ms  
Min: 0.0  
Tmin: 0.1 ms  
CFC 600

Drv. nij (NCF) ( ) vs TIME SPECIAL CHS (ms)



Max: 0.0  
Tmax: 19.8 ms  
Min: 0.0  
Tmin: 0.4 ms  
CFC 600





Drv. nij (NCE) ( ) vs TIME SPECIAL CHS (ms)



Max: 0.4  
Tmax: 165.0 ms  
Min: 0.0  
Tmin: 0.1 ms  
CFC 600






Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms

5TH FEM. DRIVER NECK MX (Nm) vs TIME (ms)




Max: 3.1 Nm  
Tmax: 15.5 ms  
Min: -3.8 Nm  
Tmin: 25.5 ms  
CFC 600

5TH FEM. DRIVER NECK MY (Nm) vs TIME (ms)




Max: 35.7 Nm  
Tmax: 90.6 ms  
Min: -31.3 Nm  
Tmin: 53.6 ms  
CFC 600

5TH FEM. DRIVER NECK MZ (Nm) vs TIME (ms)



Max: 2.7 Nm  
Tmax: 49.6 ms  
Min: -2.0 Nm  
Tmin: 76.6 ms  
CFC 600





Drv. Occipital Condyle Moment (Nm) vs TIME (ms)



Max: 34.9 Nm  
Tmax: 90.8 ms  
Min: -22.4 Nm  
Tmin: 53.7 ms  
CFC 600







Injury Values Calculated between 0ms and 165ms







Injury Values Calculated between 0ms and 165ms








Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms

FIRE VOLTAGE #1 (Volts) vs TIME (ms)




Max: 17.0 Volts  
Tmax: 0.5 ms  
Min: -0.1 Volts  
Tmin: 52.4 ms  
CFC 1000

FIRE CURRENT #1 (Amps) vs TIME (ms)




Max: 3.6 Amps  
Tmax: 9.0 ms  
Min: -0.3 Amps  
Tmin: 67.2 ms  
CFC 1000

FIRE VOLTAGE #2 (Volts) vs TIME (ms)



Max: 15.8 Volts  
Tmax: 40.8 ms  
Min: -0.2 Volts  
Tmin: 39.8 ms  
CFC 1000

FIRE CURRENT #2 (Amps) vs TIME (ms)




Max: 1.9 Amps  
Tmax: 40.2 ms  
Min: -0.1 Amps  
Tmin: 39.8 ms  
CFC 1000




LOW RISK DEPLOYMENT  
2005 TOYOTA COROLLA (C55101) (5TH P2)

Test Date: 01/28/05  
Speed: 0.0 mph ( 0.0 km/h)


Drv. nij (NTF) ( ) vs TIME SPECIAL CHS (ms)




Drv. nij (NTE) ( ) vs TIME SPECIAL CHS (ms)



Drv. nij (NCF) ( ) vs TIME SPECIAL CHS (ms)



Drv. nij (NCE) ( ) vs TIME SPECIAL CHS (ms)



**APPENDIX C**  
**CRASH TEST PHOTOGRAPHS**

## TABLE OF PHOTOGRAPHS

		<u>Page No.</u>
Photo No. 1.	Vehicle Certification Label	C-1
Photo No. 2.	Tire Placard	C-2
Photo No. 3.	Pre-Test Front View of Test Vehicle	C-3
Photo No. 4.	Post-Test Front View of Test Vehicle	C-4
Photo No. 5.	Pre-Test Left Side View of Test Vehicle	C-5
Photo No. 6.	Post-Test Left Side View of Test Vehicle	C-6
Photo No. 7.	Pre-Test Right Side View of Test Vehicle	C-7
Photo No. 8.	Post-Test Right Side View of Test Vehicle	C-8
Photo No. 9.	Pre-Test Right Front Three-Quarter View of Test Vehicle	C-9
Photo No. 10.	Post-Test Right Front Three-Quarter View of Test Vehicle	C-10
Photo No. 11.	Pre-Test Left Front Three-Quarter View of Test Vehicle	C-11
Photo No. 12.	Post-Test Left Front Three-Quarter View of Test Vehicle	C-12
Photo No. 13.	Pre-Test Right Rear Three-Quarter View of Test Vehicle	C-13
Photo No. 14.	Post-Test Right Rear Three-Quarter View of Test Vehicle	C-14
Photo No. 15.	Pre-Test Left Rear Three-Quarter View of Test Vehicle	C-15
Photo No. 16.	Post-Test Left Rear Three-Quarter View of Test Vehicle	C-16
Photo No. 17.	Pre-Test Rear View of Test Vehicle	C-17
Photo No. 18.	Post-Test Rear View of Test Vehicle	C-18
Photo No. 19.	Pre-Test Windshield View	C-19
Photo No. 20.	Post-Test Windshield View	C-20
Photo No. 21.	Pre-Test Engine Compartment View	C-21
Photo No. 22.	Post-Test Engine Compartment View	C-22
Photo No. 23.	Pre-Test Fuel Filler Cap View	C-23
Photo No. 24.	Pre-Test Front Underbody View	C-24
Photo No. 25.	Post-Test Front Underbody View	C-25
Photo No. 26.	Pre-Test Mid Underbody View	C-26

Page No.

Photo No. 27.	Post-Test Mid Underbody View	C-27
Photo No. 28.	Pre-Test Rear Underbody View	C-28
Photo No. 29.	Post-Test Rear Underbody View	C-29
Photo No. 30.	Pre-Test Driver Dummy Front View (head position)	C-30
Photo No. 31.	Post-Test Driver Dummy Front View (head position)	C-31
Photo No. 32.	Pre-Test Driver Dummy Position Left Side View	C-32
Photo No. 33.	Post-Test Driver Dummy Position Left Side View	C-33
Photo No. 34.	Pre-Test Driver Dummy Position Left Side View (Door Open)	C-34
Photo No. 35.	Post-Test Driver Dummy Position Left Side View (Door Open)	C-35
Photo No. 36.	Pre-Test Driver Dummy Seat Position	C-36
Photo No. 37.	Post-Test Driver Dummy Seat Position	C-37
Photo No. 38.	Pre-Test Driver Dummy Feet Position	C-38
Photo No. 39.	Post-Test Driver Dummy Feet Position	C-39
Photo No. 40.	Pre-Test Driver Side Knee Bolster View	C-40
Photo No. 41.	Post-Test Driver Side Knee Bolster View	C-41
Photo No. 42.	Post-Test Driver Dummy Head Contact (visor)	C-42
Photo No. 43.	Post-Test Driver Head Contact (headrest)	C-43
Photo No. 44.	Post-Test Driver Dummy Airbag Contact	C-44
Photo No. 45.	Pre-Test Passenger Dummy Front View (head position)	C-45
Photo No. 46.	Post-Test Passenger Dummy Front View (head position)	C-46
Photo No. 47.	Pre-Test Passenger Dummy Position Right Side View	C-47
Photo No. 48.	Post-Test Passenger Dummy Position Right Side View	C-48
Photo No. 49.	Pre-Test Passenger Dummy Position Right Side View (Door Open)	C-49
Photo No. 50.	Post-Test Passenger Dummy Position Right Side View (Door Open)	C-50
Photo No. 51.	Pre-Test Passenger Dummy Seat Position	C-51
Photo No. 52.	Post-Test Passenger Dummy Seat Position	C-52
Photo No. 53.	Pre-Test Passenger Dummy Feet Position	C-53
Photo No. 54.	Post-Test Passenger Dummy Feet Position	C-54

Page No.

Photo No. 55.	Pre-Test Passenger Side Knee Bolster View	C-55
Photo No. 56.	Post-Test Passenger Side Knee Bolster View	C-56
Photo No. 57.	Post-Test Passenger Dummy Head Contact	C-57
Photo No. 58.	Post-Test Passenger Dummy Knee Contact	C-58
Photo No. 59.	Post-Test Passenger Dummy Airbag Contact	C-59
Photo No. 60.	Post-Test Passenger Dummy Glove Box View 1	C-60
Photo No. 61.	Post-Test Passenger Dummy Glove Box View 2	C-61
Photo No. 62.	Post-Test Passenger Dummy Glove Box View 3	C-62
Photo No. 63.	Vehicle Impact	C-63
Photo No. 64.	Temperature Plot	C-64
Photo No. 65.	Vehicle in Relation to The Load Cell Grid	C-65

\*  
MFD. BY: TOYOTA MOTOR CORPORATION 07/04  
GVWR 3585LB GAWR FR 1885LB RR 1720LB  
THIS VEHICLE CONFORMS TO ALL APPLICABLE  
FEDERAL MOTOR VEHICLE SAFETY, BUMPER, AND  
THEFT PREVENTION STANDARDS IN EFFECT ON  
THE DATE OF MANUFACTURE SHOWN ABOVE.  
JTDBR32E952055812 PASS. CAR



C/TR: 040/FB41 MODEL: ZZE130L-AEPNKA  
A/TM: -01A/A245E MADE IN JAPAN  
NO. 360





### TIRE AND LOADING INFORMATION

SEATING CAPACITY: TOTAL 5  
FRONT 2: REAR 3

The combined weight of occupants  
and cargo should never exceed 385 kg or 850 lbs.

ORIGINAL TIRE SIZE	COLD TIRE INFLATION PRESSURE	
P195/65R15	FRONT	210kPa, 30PSI
	REAR	210kPa, 30PSI
COMPACT SPARE TIRE	COLD TIRE INFLATION PRESSURE	
T125/70R16	420kPa, 60PSI	

SEE OWNER'S MANUAL FOR  
ADDITIONAL INFORMATION

12A21

### INFORMATION SUR LES PNEUS ET LE CHARGEMENT

NOMBRE DE PLACES ASSISES : TOTAL 5  
AVANT 2 : ARRIÈRE 3

Le poids total des occupants et du chargement ne  
doit jamais être supérieur à 385 kg ou 850 lb.

DIMENSION DES PNEUS D'ORIGINE	PRESSION DE GONFLAGE À FROID	
P195/65R15	AVANT	210kPa, 30PSI
	ARRIÈRE	210kPa, 30PSI
ROUE DE SECOURS COMPACTE	PRESSION DE GONFLAGE À FROID	
T125/70R16	420kPa, 60PSI	

POUR DE PLUS AMPLES INFORMATIONS  
VOIR LE MANUEL DU PROPRIÉTAIRE

**R 0**



Pre-Test Front View of Test Vehicle





Post-Test Front View of Test Vehicle



Pre-Test Left Side View of Test Vehicle





Post-Test Left Side View of Test Vehicle



Pre-Test Right Side View of Test Vehicle






Post-Test Right Side View of Test Vehicle



Pre-Test Right Front Three-Quarter View of Test Vehicle





Post-Test Right Front Three-Quarter View of Test Vehicle



Pre-Test Left Front Three-Quarter View of Test Vehicle





Post-Test Left Front Three-Quarter View of Test Vehicle



Pre-Test Right Rear Three-Quarter View of Test Vehicle





Post-Test Right Rear Three-Quarter View of Test Vehicle




Pre-Test Left Rear Three-Quarter View of Test Vehicle






Post-Test Left Rear Three-Quarter View of Test Vehicle




Pre-Test Rear View of Test Vehicle





Post-Test Rear View of Test Vehicle



Pre-Test Windshield View





Post-Test Windshield View





Pre-Test Engine Compartment View






Post-Test Engine Compartment View




Pre-Test Fuel Filler Cap View






Pre-Test Front Underbody View





Post-Test Front Underbody View






Pre-Test Mid Underbody View




Post-Test Mid Underbody View





Pre-Test Rear Underbody View





Post-Test Rear Underbody View



Pre-Test Driver Dummy Front View (head position)





Post-Test Driver Dummy Front View (head position)



Pre-Test Driver Dummy Position Left Side View





Post-Test Driver Dummy Position Left Side View





Pre-Test Driver Dummy Position Left Side View (Door Open)



Post-Test Driver Dummy Position Left Side View (Door Open)





Pre-Test Driver Dummy Seat Position



Post-Test Driver Dummy Seat Position





Pre-Test Driver Dummy Feet Position



Post-Test Driver Dummy Feet Position






Pre-Test Driver Side Knee Bolster View



Post-Test Driver Side Knee Bolster View





Post-Test Driver Dummy Head Contact (visor)




Post-Test Driver Head Contact (headrest)





Post-Test Driver Dummy Airbag Contact



Pre-Test Passenger Dummy Front View (head position)





Post-Test Passenger Dummy Front View (head position)



Pre-Test Passenger Dummy Position Right Side View





Post-Test Passenger Dummy Position Right Side View



Pre-Test Passenger Dummy Position Right Side View (Door Open)





Post-Test Passenger Dummy Position Right Side View (Door Open)



Pre-Test Passenger Dummy Seat Position





Post-Test Passenger Dummy Seat Position




Pre-Test Passenger Dummy Feet Position





Post-Test Passenger Dummy Feet Position



Pre-Test Passenger Side Knee Bolster View





Post-Test Passenger Side Knee Bolster View



Post-Test Passenger Dummy Head Contact





Post-Test Passenger Dummy Knee Contact





Post-Test Passenger Dummy Airbag Contact





Post-Test Passenger Dummy Glove Box View 1



Post-Test Passenger Dummy Glove Box View 2






Post-Test Passenger Dummy Glove Box View 3



T0: 0 • Frame: 74 • 1,000 fps • 23 Mar 2005 11:23


Vehicle Impact





Temperature Plot





Vehicle in Relation to The Load Cell Grid

**APPENDIX D**  
**LOW RISK PHOTOGRAPHS**

## TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Photo No. 1. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side View	D-1
Photo No. 2. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side View	D-2
Photo No. 3. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side View (Door Open)	D-3
Photo No. 4. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side View (Door Open)	D-4
Photo No. 5. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side View (Door Open)	D-5
Photo No. 6. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side View (Door Open)	D-6
Photo No. 7. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side Head Position View	D-7
Photo No. 8. Post-Test 5 <sup>th</sup> Fem. P1 Drive Dummy Left Side Head Position View	D-8
Photo No. 9. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side Head Position View	D-9
Photo No. 10. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side Head Position View	D-10
Photo No. 11. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side Mid Position View	D-11
Photo No. 12. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side Mid Position View	D-12
Photo No. 13. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side Mid Position View	D-13
Photo No. 14. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side Mid Position View	D-14
Photo No. 15. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Left Side Knee Position View	D-15
Photo No. 16. Pre-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side Knee Position View	D-16
Photo No. 17. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Right Side Knee Position View	D-17
Photo No. 18. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Airbag Left View	D-18
Photo No. 19. Post-Test 5 <sup>th</sup> Fem. P1 Driver Dummy Airbag Right View	D-19
Photo No. 20. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side View	D-20
Photo No. 21. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side View	D-21
Photo No. 22. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side View (Door Open)	D-22
Photo No. 23. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side View (Door Open)	D-23
Photo No. 24. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side View (Door Open)	D-24
Photo No. 25. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side Head Position View	D-25
Photo No. 26. Post-Test 5 <sup>th</sup> Fem. P2 Drive Dummy Left Side Head Position View	D-26
Photo No. 27. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side Head Position View	D-27

	<u>Page No.</u>
Photo No. 28. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side Head Position View	D-28
Photo No. 29. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side Mid Position View	D-29
Photo No. 30. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side Mid Position View	D-30
Photo No. 31. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side Mid Position View	D-31
Photo No. 32. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side Mid Position View	D-32
Photo No. 33. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side Knee Position View	D-33
Photo No. 34. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Left Side Knee Position View	D-34
Photo No. 35. Pre-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side Knee Position View	D-35
Photo No. 36. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Right Side Knee Position View	D-36
Photo No. 37. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Airbag Left View	D-37
Photo No. 38. Post-Test 5 <sup>th</sup> Fem. P2 Driver Dummy Airbag Right View	D-38
Photo No. 39. Driver Geometric Center (2005 Toyota Corolla)	D-39





Pre-Test 5th Fem. P1 Driver Dummy Left Side View





Post-Test 5th Fem. P1 Driver Dummy Left Side View



Pre-Test 5th Fem. P1 Driver Dummy Left Side View (Door Open)





Post-Test 5th Fem. P1 Driver Dummy Left Side View (Door Open)





Pre-Test 5th Fem. P1 Driver Dummy Right Side View (Door Open)





Post-Test 5th Fem. P1 Driver Dummy Right Side View (Door Open)





Pre-Test 5th Fem. P1 Driver Dummy Left Side Head Position View



Post-Test 5th Fem. P1 Drive Dummy Left Side Head Position View





Pre-Test 5th Fem. P1 Driver Dummy Right Side Head Position View




Post-Test 5th Fem. P1 Driver Dummy Right Side Head Position View





Pre-Test 5th Fem. P1 Driver Dummy Left Side Mid Position View





Post-Test 5th Fem. P1 Driver Dummy Left Side Mid Position View



Pre-Test 5th Fem. P1 Driver Dummy Right Side Mid Position View






Post-Test 5th Fem. P1 Driver Dummy Right Side Mid Position View




Pre-Test 5th Fem. P1 Driver Dummy Left Side Knee Position View





Pre-Test 5th Fem. P1 Driver Dummy Right Side Knee Position View





Post-Test 5th Fem. P1 Driver Dummy Right Side Knee Position View



Post-Test 5th Fem. P1 Driver Dummy Airbag Left View






Post-Test 5th Fem. P1 Driver Dummy Airbag Right View





Pre-Test 5th Fem. P2 Driver Dummy Left Side View



Post-Test 5th Fem. P2 Driver Dummy Left Side View





Post-Test 5th Fem. P2 Driver Dummy Left Side View (Door Open)



Pre-Test 5th Fem. P2 Driver Dummy Right Side View (Door Open)





Post-Test 5th Fem. P2 Driver Dummy Right Side View (Door Open)



Pre-Test 5th Fem. P2 Driver Dummy Left Side Head Position View






Post-Test 5th Fem. P2 Drive Dummy Left Side Head Position View





Pre-Test 5th Fem. P2 Driver Dummy Right Side Head Position View






Post-Test 5th Fem. P2 Driver Dummy Right Side Head Position View





Pre-Test 5th Fem. P2 Driver Dummy Left Side Mid Position View



Post-Test 5th Fem. P2 Driver Dummy Left Side Mid Position View





Pre-Test 5th Fem. P2 Driver Dummy Right Side Mid Position View






Post-Test 5th Fem. P2 Driver Dummy Right Side Mid Position View



Pre-Test 5th Fem. P2 Driver Dummy Left Side Knee Position View





Post-Test 5th Fem. P2 Driver Dummy Left Side Knee Position View






Pre-Test 5th Fem. P2 Driver Dummy Right Side Knee Position View



Post-Test 5th Fem. P2 Driver Dummy Right Side Knee Position View






Post-Test 5th Fem. P2 Driver Dummy Airbag Left View





Post-Test 5th Fem. P2 Driver Dummy Airbag Right View





Driver Geometric Center (2005 Toyota Corolla)

**APPENDIX E**  
**SUPPRESSION PHOTOGRAPHS**

## TABLE OF PHOTOGRAPHS

	<u>Page #</u>
Photo No. 1.	Cosco Dream Ride Car Bed With Belt, Forward Seat Track E-1
Photo No. 2.	Cosco Dream Ride Car Bed With Belt, Middle Seat Track E-1
Photo No. 3.	Cosco Dream Ride Car Bed With Belt, Rearward Seat Track E-1
Photo No. 4.	Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track E-1
Photo No. 5.	Britax Handle With Care 191 With Belt, Forward Seat Track, Handle Down E-2
Photo No. 6.	Britax Handle With Care 191 With Belt, Middle Seat Track, Handle Down E-2
Photo No. 7.	Britax Handle With Care 191 With Belt, Rearward Seat Track, Handle Down E-2
Photo No. 8.	Britax Handle With Care 191 Unbelted, Forward Seat Track, Handle Down E-2
Photo No. 9.	Britax Handle With Care 191 Unbelted, Middle Seat Track, Handle Down E-3
Photo No. 10.	Britax Handle With Care 191 Unbelted, Rearward Seat Track, Handle Down E-3
Photo No. 11.	Britax Handle With Care 191 Fwd Facing Unbelted, Forward Seat Track, Handle Down E-3
Photo No. 12.	Britax Handle With Care 191 Fwd Facing Unbelted, Middle Seat Track, Handle Down E-3
Photo No. 13.	Britax Handle With Care 191 Fwd Facing Unbelted, Rearward Seat Track, Handle Down E-4
Photo No. 14.	Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Forward Seat Track E-4
Photo No. 15.	Evenflo First Choice 204 With Belt, Forward Seat Track, Handle Up E-5
Photo No. 16.	Evenflo First Choice 204 With Belt, Middle Seat Track, Handle Up E-5
Photo No. 17.	Evenflo First Choice 204 With Belt, Rearward Seat Track, Handle Down E-5
Photo No. 18.	Evenflo First Choice 204 Unbelted, Middle Seat Track, Handle Up E-5
Photo No. 19.	Evenflo First Choice 204 Unbelted, Rearward Seat Track, Handle Down E-6
Photo No. 20.	Evenflo First Choice 204 Fwd Facing Unbelted, Forward Seat Track, Handle Up E-6
Photo No. 21.	Evenflo First Choice 204 Fwd Facing Unbelted, Middle Seat Track, Handle Up E-6
Photo No. 22.	Evenflo First Choice 204 Fwd Facing Unbelted, Rearward Seat Track, Handle Up E-6
Photo No. 23.	Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track E-7
Photo No. 24.	Graco Infant W/ Base With Belt, Forward Seat Track, Handle Up E-8
Photo No. 25.	Graco Infant W/ Base With Belt, Middle Seat Track, Handle Down E-8
Photo No. 26.	Graco Infant W/ Base With Belt, Rearward Seat Track, Handle Down E-8
Photo No. 27.	Graco Infant W/ Base Unbelted, Forward Seat Track, Handle Up E-8
Photo No. 28.	Graco Infant W/ Base Unbelted, Middle Seat Track, Handle Down E-9
Photo No. 29.	Graco Infant W/ Base Unbelted, Rearward Seat Track, Handle Down E-9
Photo No. 30.	Graco Infant W/ Base Fwd Facing Unbelted, Forward Seat Track, Handle Up E-9
Photo No. 31.	Graco Infant W/ Base Fwd Facing Unbelted, Middle Seat Track, Handle Up E-9
Photo No. 32.	Graco Infant W/ Base Fwd Facing Unbelted, Rearward Seat Track, Handle Up E-10
Photo No. 33.	Graco Infant W/O Base With Belt, Forward Seat Track, Handle Up E-10
Photo No. 34.	Graco Infant W/O Base With Belt, Middle Seat Track, Handle Down E-10
Photo No. 35.	Graco Infant W/O Base With Belt, Rearward Seat Track, Handle Down E-10
Photo No. 36.	Graco Infant W/O Base Unbelted, Forward Seat Track, Handle Up E-11

Photo No. 37.	Graco Infant W/O Base Unbelted, Middle Seat Track, Handle Up	E-11
Photo No. 38.	Graco Infant W/O Base Unbelted, Rearward Seat Track, Handle Up	E-11
Photo No. 39.	Graco Infant W/O Base Fwd Facing Unbelted, Forward Seat Track, Handle Up	E-11
Photo No. 40.	Graco Infant W/O Base Fwd Facing Unbelted, Middle Seat Track, Handle Up	E-12
Photo No. 41.	Graco Infant W/O Base Fwd Facing Unbelted, Rearward Seat Track, Handle Up	E-12
Photo No. 42.	Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track	E-12
Photo No. 43.	Britax Roundabout 161 Fwd Facing With Belt, Forward Seat Track	E-13
Photo No. 44.	Britax Roundabout 161 Fwd Facing With Belt, Middle Seat Track	E-13
Photo No. 45.	Britax Roundabout 161 Fwd Facing With Belt, Rearward Seat Track	E-13
Photo No. 46.	Britax Roundabout 161 Fwd Facing Unbelted, Forward Seat Track	E-13
Photo No. 47.	Britax Roundabout 161 Fwd Facing Unbelted, Middle Seat Track	E-14
Photo No. 48.	Britax Roundabout 161 Fwd Facing Unbelted, Rearward Seat Track	E-14
Photo No. 49.	Britax Roundabout 161 Rear Facing With Belt, Forward Seat Track	E-14
Photo No. 50.	Britax Roundabout 161 Rear Facing With Belt, Middle Seat Track	E-14
Photo No. 51.	Britax Roundabout 161 Rear Facing With Belt, Rearward Seat Track	E-15
Photo No. 52.	Britax Roundabout 161 Rear Facing Unbelted, Forward Seat Track	E-15
Photo No. 53.	Britax Roundabout 161 Rear Facing Unbelted, Middle Seat Track	E-15
Photo No. 54.	Britax Roundabout 161 Rear Facing Unbelted, Rearward Seat Track	E-15
Photo No. 55.	Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track	E-16
Photo No. 56.	Century Encore Fwd Facing With Belt, Forward Seat Track	E-17
Photo No. 57.	Century Encore Fwd Facing With Belt, Middle Seat Track	E-17
Photo No. 58.	Century Encore Fwd Facing With Belt, Rearward Seat Track	E-17
Photo No. 59.	Century Encore Fwd Facing Unbelted, Forward Seat Track	E-17
Photo No. 60.	Century Encore Fwd Facing Unbelted, Middle Seat Track	E-18
Photo No. 61.	Century Encore Fwd Facing Unbelted, Rearward Seat Track	E-18
Photo No. 62.	Century Encore Rear Facing With Belt, Forward Seat Track	E-18
Photo No. 63.	Century Encore Rear Facing With Belt, Middle Seat Track	E-18
Photo No. 64.	Century Encore Rear Facing With Belt, Rearward Seat Track	E-19
Photo No. 65.	Century Encore Rear Facing Unbelted, Forward Seat Track	E-19
Photo No. 66.	Century Encore Rear Facing Unbelted, Middle Seat Track	E-19
Photo No. 67.	Century Encore Rear Facing Unbelted, Rearward Seat Track	E-19
Photo No. 68.	Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track	E-20
Photo No. 69.	Evenflo Medallion 254 Fwd Facing With Belt, Forward Seat Track	E-21
Photo No. 70.	Evenflo Medallion 254 Fwd Facing With Belt, Middle Seat Track	E-21
Photo No. 71.	Evenflo Medallion 254 Fwd Facing With Belt, Rearward Seat Track	E-21
Photo No. 72.	Evenflo Medallion 254 Fwd Facing Unbelted, Forward Seat Track	E-21
Photo No. 73.	Evenflo Medallion 254 Fwd Facing Unbelted, Middle Seat Track	E-22
Photo No. 74.	Evenflo Medallion 254 Fwd Facing Unbelted, Rearward Seat Track	E-22
Photo No. 75.	Evenflo Medallion 254 Rear Facing With Belt, Forward Seat Track	E-22



	<u>Page #</u>
Photo No. 76. Evenflo Medallion 254 Rear Facing With Belt, Middle Seat Track	E-22
Photo No. 77. Evenflo Medallion 254 Rear Facing With Belt, Rearward Seat Track	E-23
Photo No. 78. Evenflo Medallion 254 Rear Facing Unbelted, Forward Seat Track	E-23
Photo No. 79. Evenflo Medallion 254 Rear Facing Unbelted, Middle Seat Track	E-23
Photo No. 80. Evenflo Medallion 254 Rear Facing Unbelted, Rearward Seat Track	E-23
Photo No. 81. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Forward Seat Track	E-24
Photo No. 82. 3-Year-Old Fwd Facing Britax Roundabout Belted, Middle Seat Track	E-25
Photo No. 83. 3-Year-Old Fwd Facing Britax Roundabout Belted, Rearward Seat Track	E-25
Photo No. 84. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track	E-25
Photo No. 85. 3-Year-Old Fwd Facing Century Encore Belted, Middle Seat Track	E-26
Photo No. 86. 3-Year-Old Fwd Facing Century Encore Belted, Rearward Seat Track	E-26
Photo No. 87. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track	E-26
Photo No. 88. 3-Year-Old Fwd Facing Evenflo Medallion Belted, Middle Seat Track	E-27
Photo No. 89. 3-Year-Old Fwd Facing Evenflo Medallion Belted, Rearward Seat Track	E-27
Photo No. 90. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track	E-27
Photo No. 91. 3-Year-Old Century Next Step Belted, Forward Seat Track	E-28
Photo No. 92. 3-Year-Old Century Next Step Belted, Middle Seat Track	E-28
Photo No. 93. 3-Year-Old Century Next Step Belted, Rearward Seat Track	E-28
Photo No. 94. 3-Year-Old Century Next Step Cinched With Harness, Forward Seat Track	E-28
Photo No. 95. 3-Year-Old Century Next Step Cinched With Harness, Middle Seat Track	E-29
Photo No. 96. 3-Year-Old Century Next Step Cinched With Harness, Rearward Seat Track	E-29
Photo No. 97. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track	E-29
Photo No. 98. 3-Year-Old Cosco High Back Booster Belted, Middle Seat Track	E-30
Photo No. 99. 3-Year-Old Cosco High Back Booster Belted, Rearward Seat Track	E-30
Photo No. 100. 3-Year-Old Cosco High Back Booster Cinched With Harness, Middle Seat Track	E-30
Photo No. 101. 3-Year-Old Cosco High Back Booster Cinched With Harness, Rearward Seat Track	E-30
Photo No. 102. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track	E-31
Photo No. 103. 6-Year-Old Century Next Step Belted, Forward Seat Track	E-32
Photo No. 104. 6-Year-Old Century Next Strap Belted, Middle Seat Track	E-32
Photo No. 105. 6-Year-Old Century Next Step Belted, Rearward Seat Track	E-32
Photo No. 106. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track	E-32
Photo No. 107. 6-Year-Old Cosco High Back Booster Belted, Forward Seat Track	E-33
Photo No. 108. 6-Year-Old Cosco High Back Booster Belted, Middle Seat Track	E-33
Photo No. 109. 6-Year-Old Cosco High Back Booster Belted, Rearward Seat Track	E-33
Photo No. 110. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track	E-33
Photo No. 111. 6-Year-Old Evenflo Right Fit Belted, Forward Seat Track	E-34
Photo No. 112. 6-Year-Old Evenflo Right Fit Belted, Middle Seat Track	E-34
Photo No. 113. 6-Year-Old Evenflo Right Fit Belted, Rearward Seat Track	E-34
Photo No. 114. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Rearward Seat Track	E-34

	<u>Page #</u>
Photo No. 115. 3-Year-Old Unbelted, Forward Seat Track, Position 1	E-35
Photo No. 116. 3-Year-Old Unbelted, Forward Seat Track, Position 2	E-35
Photo No. 117. 3-Year-Old Unbelted, Forward Seat Track, Position 3	E-35
Photo No. 118. 3-Year-Old Unbelted, Forward Seat Track, Position 4	E-35
Photo No. 119. 3-Year-Old Unbelted, Forward Seat Track, Position 5	E-36
Photo No. 120. 3-Year-Old Unbelted, Forward Seat Track, Position 6	E-36
Photo No. 121. 3-Year-Old Unbelted, Forward Seat Track, Position 7	E-36
Photo No. 122. 3-Year-Old Unbelted, Middle Seat Track, Position 1	E-37
Photo No. 123. 3-Year-Old Unbelted, Middle Seat Track, Position 2	E-37
Photo No. 124. 3-Year-Old Unbelted, Middle Seat Track, Position 3	E-37
Photo No. 125. 3-Year-Old Unbelted, Middle Seat Track, Position 4	E-37
Photo No. 126. 3-Year-Old Unbelted, Middle Seat Track, Position 5	E-38
Photo No. 127. 3-Year-Old Unbelted, Middle Seat Track, Position 6	E-38
Photo No. 128. 3-Year-Old Unbelted, Middle Seat Track, Position 7	E-38
Photo No. 129. 3-Year-Old Unbelted, Rearward Seat Track, Position 1	E-39
Photo No. 130. 3-Year-Old Unbelted, Rearward Seat Track, Position 2	E-39
Photo No. 131. 3-Year-Old Unbelted, Rearward Seat Track, Position 3	E-39
Photo No. 132. 3-Year-Old Unbelted, Rearward Seat Track, Position 4	E-39
Photo No. 133. 3-Year-Old Unbelted, Rearward Seat Track, Position 5	E-40
Photo No. 134. 3-Year-Old Unbelted, Rearward Seat Track, Position 6	E-40
Photo No. 135. 3-Year-Old Unbelted, Rearward Seat Track, Position 7	E-40
Photo No. 136. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Forward Seat Track	E-40
Photo No. 137. 6-Year-Old Unbelted, Forward Seat Track, Position 1	E-41
Photo No. 138. 6-Year-Old Unbelted, Forward Seat Track, Position 2	E-41
Photo No. 139. 6-Year-Old Unbelted, Forward Seat Track, Position 3	E-41
Photo No. 140. 6-Year-Old Unbelted, Middle Seat Track, Position 1	E-41
Photo No. 141. 6-Year-Old Unbelted, Middle Seat Track, Position 2	E-42
Photo No. 142. 6-Year-Old Unbelted, Middle Seat Track, Position 3	E-42
Photo No. 143. 6-Year-Old Unbelted, Middle Seat Track, Position 4	E-42
Photo No. 144. 6-Year-Old Unbelted, Middle Seat Track, Position 4, View 2	E-42
Photo No. 145. 6-Year-Old Unbelted, Rearward Seat Track, Position 1	E-43
Photo No. 146. 6-Year-Old Unbelted, Rearward Seat Track, Position 2	E-43
Photo No. 147. 6-Year-Old Unbelted, Rearward Seat Track, Position 3	E-43
Photo No. 148. 6-Year-Old Unbelted, Rearward Seat Track, Position 4	E-43
Photo No. 149. 6-Year-Old Unbelted, Rearward Seat Track, Position 4, View 2	E-44
Photo No. 150. Unbelted 5 <sup>th</sup> Percentile Female Reactivation, Middle Seat Track	E-44

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

Newborn

Section A

Car Bed

E-1.



Cosco Dream Ride Car Bed With Belt, Forward Seat Track



Cosco Dream Ride Car Bed With Belt, Middle Seat Track



Cosco Dream Ride Car Bed With Belt  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation  
Rearward Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS

E-2.



Britax Handle With Care 191 With Belt, Forward Seat Track, Handle Down



Britax Handle With Care 191 With Belt, Middle Seat Track, Handle Down



Britax Handle With Care 191 With Belt, Rearward Seat Track, Handle Down



Britax Handle With Care 191 Unbelted, Forward Seat Track, Handle Down



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 Unbelted, Middle Seat Track, Handle Down



Britax Handle With Care 191 Unbelted, Rearward Seat Track, Handle Down



Britax Handle With Care 191 Fwd Facing Unbelted, Forward Seat Track, Handle Down



Britax Handle With Care 191 Fwd Facing Unbelted, Middle Seat Track, Handle Down



Britax Handle With Care 191 Fwd Facing Unbelted,  
Rearward Seat Track, Handle Down



Unbelted 5th Percentile Female Reactivation,  
Forward Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS



Evenflo First Choice 204 With Belt, Forward Seat Track,  
Handle Up



Evenflo First Choice 204 With Belt, Middle Seat Track,  
Handle Up



Evenflo First Choice 204 With Belt, Rearward Seat Track,  
Handle Down



Evenflo First Choice 204 Unbelted, Middle Seat Track,  
Handle Up

E-6



Evenflo First Choice 204 Unbelted,  
Rearward Seat Track, Handle Down



Evenflo First Choice 204 Fwd Facing Unbelted,  
Forward Seat Track, Handle Up



Evenflo First Choice 204 Fwd Facing Unbelted,  
Middle Seat Track, Handle Up



Evenflo First Choice 204 Fwd Facing Unbelted,  
Rearward Seat Track, Handle Up





Unbelted 5th Percentile Female Reactivation, Middle Seat Track



Graco Infant W/ Base With Belt, Forward Seat Track,  
Handle Up



Graco Infant W/ Base With Belt, Middle Seat Track,  
Handle Down



Graco Infant W/ Base With Belt, Rearward Seat Track,  
Handle Down



Graco Infant W/ Base Unbelted, Forward Seat Track,  
Handle Up



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS



Graco Infant W/ Base Unbelted, Middle Seat Track,  
Handle Down



Graco Infant W/ Base Unbelted, Rearward Seat Track,  
Handle Down



Graco Infant W/ Base Fwd Facing Unbelted, Forward Seat Track,  
Handle Up



Graco Infant W/ Base Fwd Facing Unbelted, Middle Seat Track,  
Handle Up

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS



Graco Infant W/ Base Fwd Facing Unbelted,  
Rearward Seat Track, Handle Up



Graco Infant W/O Base With Belt,  
Forward Seat Track, Handle Up



Graco Infant W/O Base With Belt, Middle Seat Track,  
Handle Down



Graco Infant W/O Base With Belt, Rearward Seat Track,  
Handle Down



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS



Graco Infant W/O Base Unbelted, Forward Seat Track, Handle Up



Graco Infant W/O Base Unbelted, Middle Seat Track, Handle Up



Graco Infant W/O Base Unbelted, Rearward Seat Track, Handle Up



Graco Infant W/O Base Fwd Facing Unbelted, Forward Seat Track, Handle Up

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section B

Rear Facing CRS



Graco Infant W/O Base Fwd Facing Unbelted,  
Middle Seat Track, Handle Up



Graco Infant W/O Base Fwd Facing Unbelted,  
Rearward Seat Track, Handle Up



Unbelted 5th Percentile Female Reactivation, Middle Seat Track



E-13.



Britax Roundabout 161 Fwd Facing With Belt,  
Forward Seat Track



Britax Roundabout 161 Fwd Facing With Belt,  
Middle Seat Track



Britax Roundabout 161 Fwd Facing With Belt,  
Rearward Seat Track



Britax Roundabout 161 Fwd Facing Unbelted,  
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section C

Forward Facing Convertible CRS



Britax Roundabout 161 Fwd Facing Unbelted,  
Middle Seat Track



Britax Roundabout 161 Fwd Facing Unbelted,  
Rearward Seat Track



Britax Roundabout 161 Rear Facing With Belt,  
Forward Seat Track



Britax Roundabout 161 Rear Facing With Belt,  
Middle Seat Track





Britax Roundabout 161 Rear Facing With Belt,  
Rearward Seat Track



Britax Roundabout 161 Rear Facing Unbelted,  
Forward Seat Track



Britax Roundabout 161 Rear Facing Unbelted,  
Middle Seat Track



Britax Roundabout 161 Rear Facing Unbelted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Rearward Seat Track





Century Encore Fwd Facing With Belt, Forward Seat Track



Century Encore Fwd Facing With Belt, Middle Seat Track



Century Encore Fwd Facing With Belt, Rearward Seat Track



Century Encore Fwd Facing Unbelted, Forward Seat Track

E-18.



Century Encore Fwd Facing Unbelted, Middle Seat Track



Century Encore Fwd Facing Unbelted, Rearward Seat Track



Century Encore Rear Facing With Belt, Forward Seat Track



Century Encore Rear Facing With Belt, Middle Seat Track





Century Encore Rear Facing With Belt, Rearward Seat Track



Century Encore Rear Facing Unbelted, Forward Seat Track



Century Encore Rear Facing Unbelted, Middle Seat Track



Century Encore Rear Facing Unbelted, Rearward Seat Track



Unbelted 5th Percentile Female Reactivation, Middle Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

12 Month

Section C

Forward Facing Convertible CRS



Evenflo Medallion 254 Fwd Facing With Belt, Forward Seat Track



Evenflo Medallion 254 Fwd Facing With Belt, Middle Seat Track



Evenflo Medallion 254 Fwd Facing With Belt,  
Rearward Seat Track



Evenflo Medallion 254 Fwd Facing Unbelted,  
Forward Seat Track



Evenflo Medallion 254 Fwd Facing Unbelted,  
Middle Seat Track



Evenflo Medallion 254 Fwd Facing Unbelted,  
Rearward Seat Track



Evenflo Medallion 254 Rear Facing With Belt,  
Forward Seat Track



Evenflo Medallion 254 Rear Facing With Belt,  
Middle Seat Track





Evenflo Medallion 254 Rear Facing With Belt,  
Rearward Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,  
Forward Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,  
Middle Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Forward Seat Track



3-Year-Old Fwd Facing Britax Roundabout Belted,  
Middle Seat Track



3-Year-Old Fwd Facing Britax Roundabout Belted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Rearward Seat Track





3-Year-Old Fwd Facing Century Encore Belted,  
Middle Seat Track



3-Year-Old Fwd Facing Century Encore Belted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation, Middle Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Fwd Facing Evenflo Medallion Belted,  
Middle Seat Track



3-Year-Old Fwd Facing Evenflo Medallion Belted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Rearward Seat Track

E-28.



3-Year-Old Century Next Step Belted, Forward Seat Track



3-Year-Old Century Next Step Belted, Middle Seat Track



3-Year-Old Century Next Step Belted,  
Rearward Seat Track



3-Year-Old Century Next Step Cinched With Harness,  
Forward Seat Track





3-Year-Old Century Next Step Cinched With Harness,  
Middle Seat Track



3-Year-Old Century Next Step Cinched With Harness,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Rearward Seat Track



3-Year-Old Cosco High Back Booster Belted,  
Middle Seat Track



3-Year-Old Cosco High Back Booster Belted,  
Rearward Seat Track



3-Year-Old Cosco High Back Booster Cinched With Harness,  
Middle Seat Track



3-Year-Old Cosco High Back Booster Cinched With Harness,  
Rearward Seat Track





Unbelted 5th Percentile Female Reactivation, Middle Seat Track

E-32.



6-Year-Old Century Next Step Belted, Forward Seat Track



6-Year-Old Century Next Strap Belted, Middle Seat Track



6-Year-Old Century Next Step Belted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Rearward Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

6 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



6-Year-Old Cosco High Back Booster Belted,  
Forward Seat Track



6-Year-Old Cosco High Back Booster Belted,  
Middle Seat Track



6-Year-Old Cosco High Back Booster Belted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Middle Seat Track



6-Year-Old Evenflo Right Fit Belted, Forward Seat Track



6-Year-Old Evenflo Right Fit Belted, Middle Seat Track



6-Year-Old Evenflo Right Fit Belted,  
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,  
Rearward Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

No CRS



3-Year-Old Unbelted, Forward Seat Track, Position 1



3-Year-Old Unbelted, Forward Seat Track, Position 2



3-Year-Old Unbelted, Forward Seat Track, Position 3



3-Year-Old Unbelted, Forward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

No CRS

E-36.



3-Year-Old Unbelted, Forward Seat Track, Position 5



3-Year-Old Unbelted, Forward Seat Track, Position 6



3-Year-Old Unbelted, Forward Seat Track, Position 7



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

No CRS



3-Year-Old Unbelted, Middle Seat Track, Position 1



3-Year-Old Unbelted, Middle Seat Track, Position 2



3-Year-Old Unbelted, Middle Seat Track, Position 3



3-Year-Old Unbelted, Middle Seat Track, Position 4

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

No CRS

E-38.



3-Year-Old Unbelted, Middle Seat Track, Position 5



3-Year-Old Unbelted, Middle Seat Track, Position 6



3-Year-Old Unbelted, Middle Seat Track, Position 7



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

No CRS

E-39.



3-Year-Old Unbelted, Rearward Seat Track, Position 1



3-Year-Old Unbelted, Rearward Seat Track, Position 2



3-Year-Old Unbelted, Rearward Seat Track, Position 3



3-Year-Old Unbelted, Rearward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

3 Year Old

No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 5



3-Year-Old Unbelted, Rearward Seat Track, Position 6



3-Year-Old Unbelted, Rearward Seat Track,  
Position 7



Unbelted 5th Percentile Female Reactivation,  
Forward Seat Track



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

6 Year Old

No CRS



6-Year-Old Unbelted, Forward Seat Track, Position 1



6-Year-Old Unbelted, Forward Seat Track, Position 2



6-Year-Old Unbelted, Forward Seat Track, Position 3



6-Year-Old Unbelted, Middle Seat Track, Position 1

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

6 Year Old

No CRS


E-42.



6-Year-Old Unbelted, Middle Seat Track, Position 2



6-Year-Old Unbelted, Middle Seat Track, Position 3



6-Year-Old Unbelted, Middle Seat Track, Position 4



6-Year-Old Unbelted, Middle Seat Track, Position 4, View 2



DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

6 Year Old

No CRS



6-Year-Old Unbelted, Rearward Seat Track, Position 1



6-Year-Old Unbelted, Rearward Seat Track, Position 2



6-Year-Old Unbelted, Rearward Seat Track, Position 3



6-Year-Old Unbelted, Rearward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test – 2005 Toyota Corolla (C55101)

6 Year Old

No CRS



6-Year-Old Unbelted, Rearward Seat Track,  
Position 4, View 2



Unbelted 5th Percentile Female Reactivation,  
Middle Seat Track

**APPENDIX F**  
**INSTRUMENTATION CALIBRATION**

**INSTRUMENTS FOR DRIVER DUMMY NO. 401**

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	AGH11	Endevco	03/16/05
Head Y	AH5N9	Endevco	03/16/05
Head Z	AGH51	Endevco	03/16/05
Neck Load Cell	252	Denton	10/12/04
Chest X	AH5L1	Endevco	03/21/05
Chest Y	AH5H6	Endevco	03/21/05
Chest Z	AH5J3	Endevco	03/21/05
Chest Displacement	401	Servo	03/22/05
Left Femur Load Cell	86	Denton	11/30/04
Right Femur Load Cell	85	Denton	11/30/04

**INSTRUMENTS FOR PASSENGER DUMMY NO. 403**

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	C10727	Endevco	03/17/05
Head Y	AGH70	Endevco	03/17/05
Head Z	AGH78	Endevco	03/17/05
Neck Load Cell	606	Denton	11/12/04
Chest X	C10591	Endevco	03/16/05
Chest Y	AGH72	Endevco	03/16/05
Chest Z	C13046	Endevco	03/17/05
Chest Displacement	403	Servo	12/22/04
Left Femur Load Cell	84	Denton	11/03/04
Right Femur Load Cell	83	Denton	11/03/04



### INSTRUMENTS FOR LOW RISK 5<sup>TH</sup> FEMALE DUMMY NO. 506 (P1)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	J35929	Endevco	01/26/05
Head Y	ALB87	Endevco	01/26/05
Head Z	P24154	Endevco	01/26/05
Neck Load Cell	376	Denton	09/29/04
Chest X	AJ819	Endevco	01/26/05
Chest Y	AJ7A2	Endevco	01/26/05
Chest Z	AJ9J7	Endevco	01/26/05
Chest Displacement	506	Servo	12/17/04
Left Femur Load Cell	1362	Denton	09/01/04
Right Femur Load Cell	1361	Denton	09/01/04

### INSTRUMENTS FOR LOW RISK 5<sup>TH</sup> FEMALE DUMMY NO. 511 (P2)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	AP120	Endevco	01/20/05
Head Y	ALEK9	Endevco	01/20/05
Head Z	AP042	Endevco	01/20/05
Neck Load Cell	1703	Denton	09/14/04
Chest X	J14120	Endevco	10/26/04
Chest Y	ALDM8	Endevco	01/20/05
Chest Z	J13941	Endevco	01/20/05
Chest Displacement	511	Servo	12/23/04
Left Femur Load Cell	1360	Denton	08/19/04
Right Femur Load Cell	1359	Denton	08/19/04

### VEHICLE INSTRUMENTS

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Left Rear Seat Crossmember X	F04-R23	Entran	03/17/05
Right Rear Seat Crossmember X	L18-J07	Entran	03/17/05
Top of Engine X	L17-D08	Entran	03/17/05
Bottom of Engine X	A29-B06	Entran	03/17/05
Left Brake Caliper X	A08-M02	Entran	03/09/05
Right Brake Caliper X	A08-M09	Entran	03/17/05
Instrument Panel X	L17-D29	Entran	12/02/04
Trunk Z	F04-R22	Entran	03/17/05

**APPENDIX G**

**NOTICE OF TEST FAILURE**

# LABORATORY NOTICE OF APPARENT TEST FAILURE TO OVSC

FMVSS NO. 208 TEST DATE: March 23, 2005

LABORATORY: MGA Research Corporation

CONTRACT NO.: DTNH22-03-D-11002 DELV. ORDER NO.: #3

LABORATORY PROJECT ENGINEER'S NAME: Jeff Lewandowski

TEST SPECIMEN DESCRIPTION: 2005 Toyota Corolla Passenger Car

VEHICLE NHTSA NO.: C55101 VIN: JTDBR32E952055812

MFR: Toyota Motor Corporation

APPARENT TEST FAILURE DESCRIPTION: The 50<sup>th</sup> Passenger Dummy SN403 had a Compression Flexion Neck Injury of 1.3 at a 96.9 ms time and a Neck Compression of 5367N during the 25mph unbelted frontal impact test.

FMVSS REQUIREMENT, PARAGRAPH S      :

S.5.1.2 / S6.6 Neck Injury (Critical values: Compression = 6160N; Flexion = 310Nm) The Neck Injury value shall not exceed 1.0 at any time during the event. Neck Compression (Critical value: Compression = 4000N) The Neck Injury value shall not exceed 4000N at any time during the event.


NOTIFICATION TO NHTSA (COTR): Charles Case

DATE: 3-24-2005 BY: Jeff Lewandowski

REMARKS: Post-test inspection of the neck load cell calibration and assembly showed no problems. Toyota representatives inspected and photographed the vehicle and dummy post test. On 3-28-05 the test vehicle passenger H-pt information was provided to Toyota representatives. Photos of the vehicle certification and tire placards are attached.



2005 Toyota Corolla Certification Placard



2005 Toyota Corolla Tire Placard



FMVSS NO. 208 TEST DATE: December 9, 2005

CONTRACT NO.: DTNH22-03-D-11002 DELV. ORDER NO.: #3

LABORATORY PROJECT ENGINEER'S NAME: Jeff Lewandowski / Audrey Hale

TEST SPECIMEN DESCRIPTION: 2005 Toyota Corolla Passenger Car

VEHICLE NHTSA NO.: C55201 VIN: JTDBR32E952055812

MFR: Toyota Motors Corporation

APPARENT TEST FAILURE DESCRIPTION: TP208-12 Data Sheet 5 3.3.1 The driver and passenger sun visor air bag warning labels are not permanently affixed to the sun visor. The labels are easily peeled off of the visor.

FMVSS REQUIREMENT, PARAGRAPH S \_\_\_\_\_ :  
S4.5.1 (b)(3) Each vehicle shall have a label permanently affixed to either side of the sun visor,  
at the manufacturer's option, at each front outboard seating position that is equipped with an  
inflatable restraint.

NOTIFICATION TO NHTSA (COTR): Charles Case

DATE: 12-9-2004 BY: Audrey Hale

REMARKS: See attached photographs of the air bag labels and the certification label.



Driver sun visor air bag warning label



Passenger sun visor air bag warning label



Vehicle certification label